

1
2
3
4
5
6
7
8
9

Marlin – Core System Specification

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25

Version 1.3.6
Final

Source
Date

Marlin Developer Community
March 13, 2013

26 **Notice**

27 THIS DOCUMENT IS PROVIDED "AS IS" WITH NO REPRESENTATION OR
28 WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE COMPLETENESS,
29 ACCURACY, OR APPLICABILITY OF ANY INFORMATION CONTAINED IN
30 THIS DOCUMENT. THE MARLIN DEVELOPER COMMUNITY ("MDC") ON
31 BEHALF OF ITSELF AND ITS PARTICIPANTS (COLLECTIVELY, THE
32 "PARTIES") DISCLAIM ALL LIABILITY OF ANY KIND WHATSOEVER,
33 EXPRESS OR IMPLIED, ARISING OR RESULTING FROM THE RELIANCE OR
34 USE BY ANY PARTY OF THIS DOCUMENT OR ANY INFORMATION
35 CONTAINED HEREIN. THE PARTIES COLLECTIVELY AND INDIVIDUALLY
36 MAKE NO REPRESENTATIONS CONCERNING THE APPLICABILITY OF ANY
37 PATENT, COPYRIGHT (OTHER THAN THE COPYRIGHT TO THE
38 DOCUMENT DESCRIBED BELOW) OR OTHER PROPRIETARY RIGHT OF
39 THIS DOCUMENT OR ITS USE, AND THE RECEIPT OR ANY USE OF THIS
40 DOCUMENT OR ITS CONTENTS DOES NOT IN ANY WAY CREATE BY
41 IMPLICATION, ESTOPPEL OR OTHERWISE, ANY LICENSE OR RIGHT TO
42 OR UNDER ANY PATENT, COPYRIGHT, TRADEMARK OR TRADE SECRET
43 RIGHTS WHICH ARE OR MAY BE ASSOCIATED WITH THE IDEAS,
44 TECHNIQUES, CONCEPTS OR EXPRESSIONS CONTAINED HEREIN.

45 Use of this document is subject to the agreement executed between you and the
46 Parties, if any.

47 Any copyright notices shall not be removed, varied, or denigrated in any manner.

48 Copyright © 2003 - 2013 by MDC, 415-112 North Mary Avenue #383 Sunnyvale, CA
49 94085, USA. All rights reserved. Third-party brands and names are the property of their
50 respective owners.

51 **Intellectual Property**

52 A commercial implementation of this specification requires a license from the Marlin
53 Trust Management Organization.

54 **Contact Information**

55 Feedback on this specification should be addressed to:
56 editor@marlin-community.com

57 Contact information for the Marlin Trust Management Organization can be found
58 at: <http://www.marlin-trust.com/>

60 Contents

61	1	Introduction	6
62	1.1	Document Organization.....	6
63	1.2	Conformance Conventions	6
64	1.3	Namespaces and Identifiers	6
65	1.3.1	Namespaces and Notation	7
66	1.3.2	Names and Identifiers	8
67	1.3.3	Marlin Naming.....	9
68	1.4	Abbreviations	10
69	1.5	Terms and Definitions.....	11
70	1.6	References	12
71	1.6.1	Normative References	12
72	1.6.2	Informative References.....	16
73	2	Marlin Core System Overview (Informative).....	18
74	2.1	Scope of the Marlin Core System Specifications	20
75	2.2	Marlin Core System Entities	20
76	2.3	Marlin Domains.....	23
77	2.4	Content Binding and Movement under Marlin Governance	24
78	3	Marlin DRM Objects.....	26
79	3.1	Octopus Objects	26
80	3.1.1	Node and Link Objects.....	26
81	3.1.2	License Objects	26
82	3.1.3	Lookup Scope for Spawned Controls	26
83	3.1.4	Agent Conveyance for License Transfer	27
84	3.2	Octopus Object Attributes and Extensions.....	27
85	3.2.1	Octopus Nodes	27
86	3.2.2	Octopus Links	30
87	3.2.3	License objects	30
88	3.2.4	License Object Contexts	31
89	3.3	XML Encoding of Octopus Objects	31
90	3.3.1	Overview	31
91	3.3.2	General Schema Design.....	31
92	3.3.3	Additional Constraints on the Schema.....	32
93	3.3.4	Signatures: Use of XML Digital Signature [xmldsig]	37
94	4	Marlin Core System Roles and Services	39
95	4.1	Overview.....	39
96	4.2	Roles Definitions.....	40
97	4.2.1	Device	40
98	4.2.2	Domain Information Provider	40
99	4.2.3	Security Data Provider	40
100	4.2.4	DRM Object Provider	40
101	4.2.5	DRM Client.....	41
102	5	Marlin Core System Protocols	42
103	5.1	NEMO Architecture for Marlin.....	42
104	5.1.1	Concepts and Architecture	42
105	5.2	Message Security Policies.....	43
106	5.2.1	Overview	43
107	5.2.2	Protocol Security Policy Identifiers	44
108	5.2.3	Request Policies	45
109	5.2.4	Response Policies	49
110	5.3	Message Faults	52
111	5.3.1	Faults for SOAP Header Processing.....	52
112	5.3.2	Faults for SOAP Body Processing.....	53

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

113	5.3.3	Fault Addressing	54
114	5.4	Discovery	55
115	5.4.1	Overview	55
116	5.4.2	Description Extension	55
117	5.5	Inspection	57
118	5.5.1	Overview	57
119	5.5.2	Inspection Client and Service interaction.....	57
120	5.6	Subscription and Notification	61
121	5.6.1	Overview	61
122	5.6.2	Topics.....	63
123	5.6.3	Notification Consumer.....	65
124	5.6.4	Notification Producer.....	66
125	5.6.5	Subscription Manager Operations	66
126	5.6.6	Faults	67
127	5.7	Service-specific Protocols	67
128	5.7.1	Proximity Check Protocol (HARPOON).....	67
129	5.7.2	DRM Client Information.....	69
130	5.7.3	Provide Domain Information	72
131	5.7.4	Provide DRM Objects	72
132	5.7.5	Provide Security Data	74
133	5.7.6	License Transfer	75
134	6	Marlin Protocol Bindings	79
135	6.1	HTTP/OBEX Binding	79
136	6.1.1	Connection Establishment.....	80
137	6.1.2	Connection Termination.....	80
138	6.1.3	Message Exchange	81
139	6.1.4	Aborting a Message Exchange.....	81
140	6.1.5	Mapping HTTP Messages to OBEX	81
141	6.2	SOAP 1.1/HTTP 1.1 Binding (Informative).....	84
142	6.2.1	HTTP Headers	84
143	6.3	NEMO Message Binding	85
144	7	Marlin Key Management	87
145	7.1	Introduction (Informative).....	87
146	7.2	HBES Broadcast Key Block Validity.....	87
147	7.3	Content Key Object before Exclusion.....	87
148	7.4	Content Key Object after Exclusion.....	88
149	8	Renewability.....	92
150	8.1	Overview.....	92
151	8.2	Specification Version Attributes.....	92
152	9	Marlin Trust Management.....	94
153	9.1	Certificates.....	94
154		Certificate Contents	94
155	9.1.2	Excluded Certificate Extensions	95
156	9.1.3	Certificate Extensions	96
157	9.1.4	Certificate Validation	98
158	9.2	Certificate Revocation List.....	101
159		CRL Contents	101
160	9.3	Trust Management of Marlin Services (Informative)	103
161	9.3.1	Secure Peer Interactions	103
162	9.3.2	DRM Services	103
163	9.3.3	Data Certification Services	104
164	9.4	Trust Hierarchies and Policies.....	105
165	9.4.1	Peer Application Interaction Trust Hierarchy	106
166	9.4.2	DRM Services Trust Hierarchy	108
167	9.4.3	DRM Client Personalization Trust Hierarchy	109

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

168	9.4.4	Registration Services Trust Hierarchy	113
169	9.4.5	Content Licensing Trust Hierarchy	116
170	9.4.6	Data Certification Trust Hierarchy.....	119
171	10	File Format for Marlin Content	123
172	11	Marlin Usage Rules.....	124
173	11.1	Move and Copy Actions	125
174	11.1.1	Theory of Operation (Informative)	125
175	12	Profiles	128
176	12.1	Cryptographic Algorithm Profiles.....	128
177	12.1.1	Hashing (Digest) algorithms:	128
178	12.1.2	Keyed-Hash Message Authentication Code algorithms.....	128
179	12.1.3	Public Key algorithms	128
180	12.1.4	Signature Hash algorithms	128
181	12.1.5	Symmetric key algorithms	128
182	12.1.6	Canonicalization	129
183	12.2	XML Digital Signature Profile	129
184	12.2.1	<ds:Signature> Element.....	129
185	12.2.2	<ds:SignedInfo>	129
186	12.2.3	<ds:SignatureValue>	131
187	12.2.4	<ds:KeyInfo>	131
188	12.3	NEMO Profile for Basic Secure Messaging	132
189	12.3.1	Notation	132
190	12.3.2	Request Message.....	132
191	12.3.3	Response Message.....	135
192	12.3.4	Confirmation Message.....	137
193	12.3.5	License Transfer Protocol Correlation Processing Rules.....	140
194	12.4	SAML Assertion Profile	140
195	12.4.1	Assertion Conditions.....	141
196	12.4.2	Assertion Subject.....	141
197	12.4.3	Attributes.....	141
198	12.4.4	Subject Confirmation	141
199	12.4.5	Signature	142
200	12.5	Name Management Profile	142
201	12.5.1	SeaShell Object Ownership.....	142
202	12.5.2	Octopus Naming.....	143
203	12.5.3	Extensions	143
204	12.5.4	SeaShell Database ([8pus] §7)	144
205	12.6	Type Mapping of Host Objects.....	147
206	12.6.1	Mapping XML Types to Host Objects.....	147
207	12.6.2	Mapping Octopus Object Attributes to Host Objects	147
208	12.6.3	Mapping Agent Parameters to Host Objects	148
209	12.7	XML Profile.....	150
210	12.7.1	XML Attribute Composition Constraints	150
211	12.7.2	Using QNames	151
212	12.8	Security Metadata Propagation (Informative)	151
213	12.8.1	Common Security Metadata Acquisition Mechanisms	152
214	12.8.2	Alternate Security Metadata Acquisition Mechanisms	152
215			

216 1 Introduction

217 1.1 Document Organization

218 This document covers the complete Marlin Core Specifications. It is organized as
219 follows:

- 220 • (this) introduction, including abbreviations, definitions and references
- 221 • An overview of the Marlin core system architecture
- 222 • Sections for each of the normative specification elements. These are:
 - 223 ○ DRM Objects
 - 224 ○ DRM Roles and Services
 - 225 ○ Client-Service Role Protocols
 - 226 ○ Protocol Bindings
 - 227 ○ Key Management
 - 228 ○ Renewability
 - 229 ○ Trust Management
 - 230 ○ Content File Formats (see [MFF1.0])
 - 231 ○ Usage Rules
 - 232 ○ Naming Conventions (e.g. names that must be used uniformly across
233 implementation to achieve the interoperability goals of marlin
- 234 • A set of attachments:
 - 235 ○ WSDLs and XML Schemas

236 1.2 Conformance Conventions

237 The key words “MUST”, “MUST NOT”, “REQUIRED”, “SHALL”, “SHALL NOT”,
238 “SHOULD”, “SHOULD NOT”, “RECOMMENDED”, “MAY”, and “OPTIONAL” in this
239 specification are to be interpreted as described in IETF RFC 2119 [RFC2119].
240

241 These capitalized key words are used to unambiguously specify requirements and
242 behavior that affect the interoperability and security of implementations. When these key
243 words are not capitalized they are meant in their natural-language sense.
244

245 All Elements of this specification are considered Normative unless specifically marked
246 Informative. All Normative Elements are Mandatory to implement, except where such an
247 element is specifically marked OPTIONAL. Finally, where Normative elements are
248 described as OPTIONAL, they MAY be omitted from an implementation, but when
249 implemented, they MUST be implemented as described.

250 1.3 Namespaces and Identifiers

251 This specification defines schemas conforming to XML Schemas [Schema] and
252 normative text to describe the syntax and semantics of XML-encoded objects and
253 protocol messages. In cases of disagreement between the schema documents and the
254 schema listings in this specification the schema documents take precedence. Note that
255 in some cases the normative text of this specification imposes constraints beyond those
256 indicated by the schema documents.

257 **1.3.1 Namespaces and Notation**

258 The following table summarizes the normative schemas defined by this specification and
 259 their XML namespace [XMLNs] URIs. These URIs MUST be used by implementations of
 260 this specification:
 261

Prefix	XML Namespace	Schema File Name	Description
mc:	urn:marlin:core:1-3:schemas	marline-core.xsd	Marlin core schema
ml:	http://marlin-drm.com/1.0	Marlin.xsd	Marlin DRM schema
mncs:	urn:marlin:core:1-1:nemo:services:schemas	marlin-nemo-core-services.xsd	Marlin NEMO Services
exc:	urn:marlin:core:1-2:nemo:services:schemas:exceptions	marlin-nemo-core-exceptions.xsd	Fault Response schema

262 **Table 1-1 Namespace Definitions**

263 In addition to the schemas defined by this specification, we leverage existing schemas to
 264 achieve our design goals. The following table summarizes the external schemas used in
 265 this specification:
 266

Prefix	XML Namespace	Description
oct:	http://www.octopus-drm.com/profiles/base/1.0	Octopus
pk:	http://www.octopus-drm.com/profiles/base/1.0/plankton	[8pus] §4
sf:	http://marlin-drm.com/starfish/1.2	[Starfish]
nemoc:	http://nemo.intertrust.com/2005/10/core	[NEMO] §2
nemosec:	http://nemo.intertrust.com/2005/10/security	[NEMO] §3
xs:	http://www.w3.org/2001/XMLSchema	[Schema]
xsi:	http://www.w3.org/2001/XMLSchema-instance	[Schema]
ds:	http://www.w3.org/2000/09/xmlsig#	[xmlsig]
xenc:	http://www.w3.org/2001/04/xmlenc#	[xmlenc]
wSDL:	http://schemas.xmlsoap.org/wSDL/	[WSDL]
wsa:	http://www.w3.org/2005/08/addressing	[WS-Addr]
wsx:	http://schemas.xmlsoap.org/ws/2004/09/mex	[WS-MEX]
wsnt:	http://docs.oasis-open.org/wsn/b-2	[WS-BASENOTE]
wsrf-rp:	http://docs.oasis-open.org/wsrp/rp-1	[WSRF-RP]
wsrf-rl:	http://docs.oasis-open.org/wsrp/rl-1	[WSRF-RL]
wsrf-bf:	http://docs.oasis-open.org/wsrp/bf-2	[WSRF-BF]
S11:	http://schemas.xmlsoap.org/soap/envelope	[SOAP11]
wsu:	http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd	[WS-SEC]
wsse:	http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd	[WS-SEC]
wsp:	http://schemas.xmlsoap.org/ws/2004/09/policy	[WS-POL]

267 **Table 1-2 Supporting Namespaces**

268 As a convention throughout this document we use the namespace prefixes described
269 above to qualify XML elements and attributes which are specified elsewhere. That is the
270 typographical convention is: <MarlinElement>, <ns:ForeignElement>, XMLAttribute,
271 **Datatype**, OtherKeyword.

272 1.3.2 Names and Identifiers

273 This section complements naming patterns and names introduced in subsequent
274 sections of this specification. Additional naming conventions are described in Section
275 12.5.

276
277 This specification uses Uniform Resource Identifiers [RFC2396] to identify various
278 entities including resources, algorithms, policies, attributes and other application specific
279 objects. Implementations of this specification **MUST** support URIs of at least 256 bytes
280 long.

281
282 A standard naming pattern is specified to simplify management of the identifiers defined
283 across all systems that leverage the underlying technology (e.g., Nemo and Octopus),
284 as well as across all the implementations of Marlin. The naming pattern used allows
285 each layer/entity to delegate management of namespaces to subordinate layers/entities.
286 This approach guarantees uniqueness of names generated by those subordinate
287 layers/entities without active coordination between them.

288
289 All Marlin names **SHALL** be specified as URIs and use a consistent root (prefix) based
290 on the syntax of the identifier. Two URIs and their respective prefixes are defined in the
291 table below:
292

Identifier Type	Prefix
URN	urn:marlin:
URL	http://marlin-drm.com

293
294 The identifiers defined within the above declared namespaces are normative to this
295 specification. Per [URNMARLIN], URNs **SHALL** be treated in a case sensitive manner.
296 The namespace prefix **SHALL** be the lowercase string “urn:marlin:”.

297
298 Note that this specification uses identifiers defined by other specifications and their
299 normative definition solely comes from the specification that defines them. As a
300 convenience to the reader these identifiers may appear in examples or in giving
301 guidance. However, such uses are informative and do not supercede the identifier
302 definition.

303
304 Device manufacturers, service providers, and perhaps other organizations that
305 implement Marlin specifications may need to define Marlin related object names specific
306 to themselves or their extensions to the Marlin specifications. To keep organization
307 specific object names distinct without requiring active coordination between all such
308 entities, organization specific urns are used. Such organizations can register their own
309 unique URN namespace (e.g. urn:SomeOrganization) and define such names using a
310 URN registered to their organization. In order to not require all such organizations
311 register their own URN namespace, they can be registered with Marlin and issued a

312 unique URN namespace within the Marlin namespace. Thus there are two patterns for
 313 organization specific identifiers.
 314

Identifier Type	Prefix
URN	urn:marlin:organization:<organization-name>
URN	urn:<organizations-own-namespace>

315
 316 In addition to naming patterns, specific attributes names and values SHALL be defined
 317 when these are global in scope (e.g. the value used for a device capability or the role of
 318 a system entity.) In general attribute names are qualified by a namespace. In some
 319 instances an attribute namespace is defined by a URL and for purposes of convenience
 320 we define an URN equivalent to maintain consistency and simplify processing. The
 321 following table gives the set of URLs and their URN equivalent.
 322

URL Attribute Namespace	URN Equivalent
http://nemo.intertrust.com/2004/attribute	urn:marlin:nemo:2004:attribute

323 **Table 1-3 Attribute Namespace Equivalences**

324 To minimize backward compatibility issues we adopt the policy of not putting version
 325 information in the attribute namespace qualifiers. Going forward, we will accommodate
 326 behavioral changes of an entity for which an attribute refers by defining a new attribute
 327 name.

328 1.3.3 Marlin Naming

329 In the following sections we specify naming conventions which will aid implementations
 330 and delivery system specifications in defining identifiers in a consistent and interoperable
 331 manner.

332 The general syntax can be described using the following BNF grammar;

333

urn:marlin:<specid>:<objattrid>:<attribute specific data>

where;

<specid> is a constant identifier for the particular specification

<objattrid> is the object or attribute identifier for which the URN applies

334

335 The <specid> identifier SHALL adopt the prefix identifiers in the following table.

336

Specification Identifiers	Description
core	Prefix identifier defined by this specification.
broadband	Prefix identifier defined in the Broadband Delivery System specification.
broadcast	Prefix identifier defined in the Broadcast Delivery System specification.
omav2gw	Prefix identifier defined in the OMA Gateway specification.
<other>	Future identifiers

337 **Table 1-4 Specification Identifiers**

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

338 The value space of URN identifiers may also need to be standardized so that
 339 independent implementations by the same organization do not collide. Therefore it is
 340 recommended that URN values use the specification id prefix followed by the
 341 organization identifier.
 342 The general syntax can be described using the following BNF grammar;
 343

urn:marlin:organization:<orgid>.*

where;

<orgid> is the organization specific identifier. Note this identifier can include sub-organization identifiers which are managed by the organization itself.

* any valid URN namespace specific string

344 **Table 1-5 Organization Identifiers**

345 **1.4 Abbreviations**

AES	Advanced Encryption Standard
AES-CTR-128	AES Counter mode with 128-bit key
BF	Broadcast Flag
BKB	Broadcast Key Block
CAS	Conditional Access System
CBC	Cipher Block Chaining
CCI	Copy Control Information
CPRM	Content Protection for Recordable Media
CTR	Counter
DCF	DRM Content Format
DCS	Data Certification Service
DLNA	Digital Living Network Alliance
DUS	Data Update Service
HBES	Hierarchical Hash-Chain Broadcast Encryption Scheme
ISO	International Organization for Standardization
MAC	Message Authentication Code
MDCF	Marlin DRM Content Format
MDD	Marlin Device Domain
MG-R	MagicGate Type-R
NEMO	Networked Environment for Media Orchestration
OMA	Open Mobile Alliance
PAT	Program Association Table
PMT	Program Map Table
PSI	Program Specific Information
SAML	Security Assertions Markup Language
SDP	Security Data Provider
SI	Service Information
SOAP	Simple Object Access Protocol
SPTS	Single Program Transport Stream
SSDP	Simple Service Discovery Protocol
TCP	Transmission Control Protocol
TS	Transport Stream
TTS	Timed Transport Stream

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

UPnP	Universal Plug and Play
VCPS	Video Content Protection System
WSDL	Web Services Description Language
XML	Extensible Markup Language

347

348 **1.5 Terms and Definitions**

Usage information	Information that indicates usage rules and governance applied for protected content.
Protection information	Protection-related information along with protected content.
Marlin Device Domain	Set of devices that have established a membership relationship which is reflected by an Octopus link.
Renewability	The process by which security related elements of Marlin Core System implementations can be renewed if necessary
Security Metadata	Metadata necessary for managing the security and trustworthiness of the Marlin System, such as Certificate Revocation Lists
Roles	A combination of client/service functions supported by an implementation
Marlin DRM Client	A Role with the necessary functionality to allow it to render content
Domain Manager	A Role with the necessary functionality to allow it to link devices into domains
Marlin Import Function	A Role with the necessary functionality to allow it to generate licenses and package content
Marlin Device	The most basic Role any implementation must support
Marlin User	The representation of a user
Marlin Subscription Node	The representation of the token that makes it possible to bind many content licenses together
Marlin Delivery System Specifications	Specifications that define how Marlin Content and Licenses are created and how such content is imported into a Marlin User's Device Domain
Marlin User	The Octopus Node that represents the user who "owns" the content
Marlin Content	Media packaged into a Marlin File Format Container
Marlin Content Format	The File Format and Media Codec Profile that Marlin Content is contained in.
Marlin Domain Information Provider	A Role with the necessary functionality to advertise which domains DRM Client can register to and the DRM Object Provider
Content is targeted to a Node	License uses the Node in isHostReachable
Content is bound to a Node	License uses that Node for SCUBA key management purposes.
Content Key	The symmetric key that encrypts the payload of the content

Starfish	The Marlin broadcast encryption scheme based on HBES (Hierarchical Hash-Chain Broadcast Encryption Scheme)
Harpoon	A protocol used to measure the network proximity of 2 devices

349

350 1.6 References

351 1.6.1 Normative References

352

[8pus]	Octopus DRM Technology Platform Specifications, Version 1.0
[AES]	NIST FIPS 197: Advanced Encryption Standard (AES). November 2001. http://csrc.nist.gov/publications/fips/fips197/fips-197.pdf
[AES-MODES]	Recommendation of Block Cipher Modes of Operation. NIST. NIST Special Publication 800-38A. http://csrc.nist.gov/CryptoToolkit/modes/800-38_Series_Publications/SP800-38A.pdf
[CPRM-DVD]	Content Protection for Recordable Media Specification, DVD Book, Revision 0.96, http://www.4centity.com/data/tech/spec/cprm-dvd096.pdf
[CPRM-SD-AUDIO]	Content Protection for Recordable Media Specification, SD Memory Card Book, SD-Audio Part, Revision 0.96, http://www.4centity.com/data/tech/spec/Cprm-sd-audio096.pdf
[CPRM-SD-VIDEO]	Content Protection for Recordable Media Specification, SD Memory Card Book, SD-Video Part, Revision 0.93, http://www.4centity.com/data/tech/spec/Cprm-sd-video-part-093-1.pdf
[DTCP14]	Digital Transmission Content Protection Specification Revision 1.4 Informational Version
[hmacwithsha1]	H. Krawczyk, M. Bellare, and R. Canetti. <i>HMAC: Keyed-Hashing for Message Authentication</i> . IETF RFC 2104. February 1997. http://www.ietf.org/rfc/rfc2104.txt
[hmacwithsha256]	D. Eastlake and T. Hansen. <i>US Secure Hash Algorithms (SHA and HMAC-SHA)</i> . IETF RFC 4634. July 2007. http://www.ietf.org/rfc/rfc4634.txt
[ISMACryp]	"ISMA Encryption and Authentication Specification", version 1.0, February 2004.
[MEXP]	Marlin - Export Parameter Specification
[MFF1.0]	Marlin – File Formats Specification version 1.0. December 2005.
[MIME]	N. Freed & N. Borenstein. <i>Multipurpose Internet Mail Extensions (MIME) Part One: Format of Internet Message Bodies</i> . IETF RFC 2045. November 1996. http://www.ietf.org/rfc/rfc2045.txt

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

[MOCS1.0]	Marlin – Output Control Specification version 1.0. June 2007
[NEMO]	NEMO Technology Platform Specifications, Version 1.1
[OBEX13]	IrDA Object Exchange Protocol (IrOBEX), Version 1.3, January 2003, http://www.IrDA.org/
[PKIX]	R. Housley, W. Ford, W. Polk, D. Solo. <i>Internet X.509 Public Key Infrastructure Certificate and CRL Profile</i> . IETF RFC 3280. April 2002. http://www.ietf.org/rfc/rfc3280.txt
[PKIXALGS]	R. Housley, B. Kaliski, J. Schaad. <i>Additional Algorithms and Identifiers for RSA Cryptography for use in the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile</i> . IETF RFC 4055. June 2005. http://www.ietf.org/rfc/rfc4055.txt .
[QNAMEIDS]	Using Qualified Names (QNames) as Identifiers in XML Content, http://www.w3.org/2001/tag/doc/qnameids
[RFC2119]	S. Bradner, <i>Key words for use in RFCs to Indicate Requirement Levels</i> , IETF RFC 2119, March 1997. http://www.ietf.org/rfc/rfc2119.txt .
[RFC2396]	T. Berners-Lee, R. Fielding, L. Masinter. <i>Uniform Resource Identifiers (URI): Generic Syntax</i> . IETF RFC 2396. August 1998. http://www.ietf.org/rfc/rfc2396.txt
[RFC2585]	R. Housley, P. Hoffman. <i>Internet X.509 Public Key Infrastructure Operational Protocols: FTP and HTTP</i> . IETF RFC 2585. May 1999. http://www.ietf.org/rfc/rfc2585.txt
[RFC2616]	R. Fielding, J. Gettys, J. Mogul, H. Frystyk, L. Masinter, P. Leach, T. Berners-Lee, eds. <i>Hypertext Transfer Protocol – HTTP/1.1</i> . IETF RFC 2616 http://www.ietf.org/rfc/rfc2616.txt
[RFC2630]	Cryptographic Message Syntax. Network Working Group. R. Housley, Request for Comments: 2630. June 1999. http://www.ietf.org/rfc/rfc2630.txt
[RFC3279]	W. Polk, R. Housley, L. Bassham. <i>Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile</i> . IETF RFC 3279. http://www.ietf.org/rfc/rfc3279.txt
[RFC4051]	D. Eastlake 3 rd . <i>Additional XML Security Uniform Resource Identifiers (URIs)</i> . IETF RFC4051. April 2005. http://www.ietf.org/rfc/rfc4051.txt
[RSA-1_5]	B. Kaliski, J. Staddon. <i>PKCS #1: RSA Cryptography Specifications Version 2.0</i> . IETF RFC2437. October 1998. http://www.ietf.org/rfc/rfc2437.txt

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

[SAML1.1]	Eve Maler, Prateek Mishra and Rob Philpott, eds., <i>Assertions and Protocol for the OASIS Security Assertion Markup Language (SAML) V1.1</i> , http://www.oasis-open.org/committees/download.php/3405/oasis-sstc-saml-bindings-1.1.pdf
[Schema]	XML Schema Part 1: Structures. W3C Recommendation. D. Beech, M. Maloney, N. Mendelsohn, H. Thompson. May 2001. http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/ XML Schema Part 2: Datatypes W3C Recommendation. P. Biron, A. Malhotra. May 2001. http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/
[SHA1]	FIPS PUB 180-1. <i>Secure Hash Standard</i> . U.S. Department of Commerce/National Institute of Standards and Technology. http://www.itl.nist.gov/fipspubs/fip180-1.htm
[SHA256]	FIPS PUB 180-2. <i>Secure Hash Standard</i> . U.S. Department of Commerce/National Institute of Standards and Technology. http://csrc.nist.gov/publications/fips/fips180-2/fips180-2.pdf
[SOAP11]	"Simple Object Access Protocol (SOAP) 1.1," Box, Don, Ehnebuske, David , Kakivaya, Gopal, Layman, Andrew, Mendelsohn, Noah, Nielsen, Henrik Frystyk, Winer, Dave, eds. World Wide Web Consortium W3C Note (08 May 2000). http://www.w3.org/TR/2000/NOTE-SOAP-20000508/
[Starfish]	<i>Starfish - Marlin Broadcast Encryption Scheme v1.2</i>
[UPnPDevArch1.0]]	UPnP Device Architecture v1.0 http://upnp.org/resources/documents/CleanUPnPDA101-20031202s.pdf
[UPnPDevArch1.0.1]	UPnP Device Architecture v1.0.1 Draft http://www.upnp.org/resources/documents/CleanUPnPDA101-20031202s.pdf
[UPnPBasicDev]	Basic:1.0 Device Definition Version 1.0 http://upnp.org/standardizeddcps/documents/BasicDevice-1.0.pdf
[UPnPImplGuid]	UPnP Vendors Implementation Guide http://www.upnp.org/download/UPnP_Vendor_Implementation_Guide_Jan2001.htm
[URL]	T. Berners-Lee, L. Masinter, and M. McCahill. <i>Uniform Resource Locators (URL)</i> . IETF RFC 1738. December 1994. http://www.ietf.org/rfc/rfc1738.txt

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

[URN]	R. Moats.. <i>URN Syntax</i> . IETF RFC 2141. May 1997. http://www.ietf.org/rfc/rfc2141.txt L. Daigle, D. van Gulik, R. Iannella, P. Falstrom.. <i>URN Namespace Definition Mechanisms</i> . IETF RFC 2611. June 1999. http://www.ietf.org/rfc/rfc2611.txt
[URNMARLIN]	<i>A Uniform Resource Name (URN) Namespace for the Marlin Development Community L.L.C.</i> IETF Draft 02, June 27, 2007
[VCPS]	Video Content Protection System for the DVD+R/+RW, Video Recording Format System Description, Version 1.2, February 2005 http://www.licensing.philips.com/vcps/
[WS-Addr]	<i>Web Services Addressing 1.0 - Core</i> , W3C Candidate Recommendation, 17 August 2005, http://www.w3.org/TR/2005/CR-ws-addr-core-20050817 <i>Web Services Addressing 1.0 - SOAP Binding</i> , W3C Candidate Recommendation, 17 August 2005, http://www.w3.org/TR/2005/CR-ws-addr-soap-20050817
[WS-BASENOTE]	<i>Web Services Base Notification 1.3</i> , Committee Specification, http://docs.oasis-open.org/wsn/wsn-ws_base_notification-1.3-spec-cs-01.pdf
[WSRF-BF]	<i>Web Services Base Faults 1.2</i> , OASIS Standard. http://docs.oasis-open.org/wsr/wsr-ws_base_faults-1.2-spec-os.pdf
[WSDL]	<i>Web Services Description Language</i> http://www.w3.org/TR/wSDL
[WS-MEX]	<i>Web Services Metadata Exchange</i> , September 2004 http://xml.coverpages.org/WS-MetadataExchange200409.pdf
[WSRF-RP]	<i>Web Services Resource Properties 1.2</i> , OASIS, Committee Draft 01, 18 May 2005 http://docs.oasis-open.org/wsr/wsr-ws_resource_properties-1.2-spec-cd-01.pdf
[WSRF-RL]	<i>Web Services Resource Lifetime 1.2</i> , OASIS, Committee Draft 01, 19 May 2005, http://docs.oasis-open.org/wsr/wsr-ws_resource_lifetime-1.2-spec-cd-01.pdf
[WS-SEC]	<i>Web Services Security (WS-Security)</i> , Version 1.0, OASIS, April 5, 2002. http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-soap-message-security-1.0.pdf
[WS-SECX509]	Phillip Hallam-Baker <i>et al.</i> , eds., <i>Web Services Security X.509 Certificate Token Profile</i> , OASIS Standard 200401, March 2004, http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-x509-token-profile-1.0.pdf

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

[WS-SECX509-ER]	Phillip Hallam-Baker <i>et al.</i> , eds., <i>Web Services Security X.509 Certificate Token Profile</i> , Errata 1.0, December 2005, http://www.oasis-open.org/committees/download.php/16796/oasis-200512x509-token-profile-1.0-errata-005.pdf
[WS-SECSAML]	Phillip Hallam-Baker <i>et al.</i> , eds., <i>Web Services Security: SAML Token Profile</i> , OASIS Standard, December 2004, http://docs.oasis-open.org/wss/oasis-wss-saml-token-profile-1.0.pdf
[WS-TOPICS]	<i>Web Services Topics 1.2</i> , OASIS, Working Draft 01, 22 July 2004
[X509]	<i>ITU-T Recommendation X.509 (1997 E): Information Technology - Open Systems Interconnection - The Directory: Authentication Framework</i> , June 1997.
[XML-1-1]	<i>Extensible Markup Language (XML) 1.1 (Second Edition)</i> , http://www.w3.org/TR/xml11/
[xmldsig]	<i>XML-Signature Syntax and Processing W3C Recommendation</i> http://www.w3.org/TR/xmldsig-core/
[xmlenc]	<i>XML Encryption Syntax and Processing W3C Recommendation</i> http://www.w3.org/TR/xmlenc-core/
[xml-exc-c14n]	<i>Exclusive XML Canonicalization, Version 1.0, W3C Recommendation 18 July 2002</i> http://www.w3.org/TR/xml-exc-c14n/
[XMLNs]	Namespaces in XML. W3C Recommendation. T. Bray, D. Hollander, A. Layman. January 1999. http://www.w3.org/TR/1999/REC-xml-names-19990114

353

354 1.6.2 Informative References

355

[Coral]	Coral Consortium Corporation http://www.coral-interop.org
[3GPP]	3 rd Generation Partnership Project, "Transparent end-to-end packet switched streaming service (PSS); 3GPP file format (3GP) (Release6)", 3GPP TS 26.244 V6.2.0, 2004-12.
[ISDB]	ARIB STANDARD, "SERVICE INFORMATION FOR DIGITAL BROADCASTING SYSTEM" ARIB STD-B10, version 3.8. (http://www.dibeg.org/aribstd/STD-B10-v3.8e.pdf).
[ItruObjectId]	Intertrust X.500 Object Identifier Specification
[MGRSVRMS-Info]	MagicGate Type-R for Secure Video Recording for Memory Stick PRO Specification – Informational Version – ver1.03
[MGRSARMS-Info]	MagicGate Type-R for Secure Audio Recording for Memory Stick and Memory Stick PRO Specification – Informational Version – ver0.9

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

[PKCS7]	RSA Laboratories. <i>PKCS #7: Cryptographic Message Syntax Standard</i> . Version 1.5, November 1993.
[PKCS8]	RSA Laboratories. <i>PKCS #8: Private-Key Information Syntax Standard</i> . Version 1.2, November 1993.
[RFC3852]	R. Housley, <i>Cryptographic Message Syntax (CMS)</i> . IETF RFC 3852. July 2004. http://www.ietf.org/rfc/rfc3852.txt
[WS-POL]	Web Services Security Policy Language (WS-SecurityPolicy), Version 1.0, December 18, 2002

356

357 **2 Marlin Core System Overview (Informative)**

358

359 Marlin defines a Digital Rights Management [DRM] system for consumer-friendly content
360 consumption models that allow consumers to enjoy appropriately licensed content
361 transparently on compliant and capable devices.

362

363 The Marlin functional model (see Figure 2-1) allows content from different content
364 delivery channels to be governed using Marlin DRM. The model also enables content to
365 be made available on a set of compliant devices comprising an affiliation of the user's
366 devices. We commonly refer to this affiliation of devices as a Marlin Domain or
367 "consumer domain" or even more succinctly as simply a "domain."

368

369 Marlin DRM ensures that Marlin Content is handled according to the original content
370 owner's intents. Marlin specifies how content is made available to devices in a
371 consumer domain (Marlin Import Function), how Marlin Licenses express the rights to
372 access such content (Marlin Licenses), the protocols by which Marlin devices
373 communicate so that Content can be transferred between devices in the domain (or
374 exported from it), and the (file) formats for the content (Marlin Content Format.) This
375 level of specificity is necessary so that content can not only be transferred onto a Marlin-
376 compliant device but also consumed on all devices in the Domain.

377

378 Note that in this version of the specification, the Marlin Delivery System Specifications –
379 not the Marlin Core System Specifications - specify the Marlin Domains, as well as how
380 content is made available to the devices in a Domain, how Marlin Licenses are
381 generated from original content licenses or content owner intents, and how content is
382 packaged into a file container (Marlin Content) that can be consumed by other Marlin
383 Devices. In summary:

384

- 385 • The core specifications mandate only what is necessary to enable devices to
386 obtain and play content governed by a basic set of usage rules, become part of
387 or leave a domain, and obtain any necessary security metadata and DRM
388 objects to achieve the above.
- 389 • The delivery system specifications extend the core specifications, to specify how
390 different type of domains are formed and managed, how content is made
391 available on standalone devices or devices part of a domain, the usage rules that
392 govern access to content on devices in the domain and the movement of content
393 and licenses between devices. They enable an end to end DRM system
394 implementation for a given content delivery mechanism.
- 395 • The core specifications may be updated from time to time to include
396 specifications required to support a delivery system specification that was
397 defined later. Domain definitions that are independent of the delivery
398 mechanisms are an example of such an update.

398

399

400 ***Marlin Interoperability***

401

402 Marlin-compliant devices from different manufacturers should be interoperable – once
403 content has been imported into a Marlin Device Domain, it should be possible to play it




Figure 2-1: Marlin Functional Model

404 on any of the Domain's devices as long as the device's implementation of the core
 405 system supports the consumption of that type of content. E.g.
 406 • Any Marlin video-capable Marlin DRM Client should be able to play any Marlin
 407 formatted video content as long as the codec profiles match. That is,
 408 incompatibilities should not reside at the container, content protection, or
 409 "minimum" license expression, functional or protocol level
 410 Note the use of the "minimum" qualifier above: It is expected that specialized DRM
 411 Client features may be necessary in order to support certain market-driven features. In
 412 order to allow implementers to develop light-weight, conformant clients, some features of
 413 the core specifications will be considered optional to be implemented, while those
 414 necessary to ensure minimum interoperability will be mandatory.
 415
 416 In summary, the Marlin Core Specification defines the DRM Objects, the Marlin Content
 417 Formats, and the set of Marlin Device-side functions and protocols that all Marlin Core
 418 System conformant implementations support and that any implementation of a Marlin
 419 Delivery System Specification can rely on.
 420
 421

422 **2.1 Scope of the Marlin Core System Specifications**

423

424 Marlin Core System Specifications are defined as those specifications that, when
425 implemented:

- 426 • Enable consumption of content imported via one of the Marlin Import functions
- 427 • Enable participation in the domains referenced by the licenses of such imported
428 content, using local protocols (broadband connectivity is not mandated for
429 devices implementing the Marlin Core System specification)

430

431 Note that it may be necessary for a proxy application to implement a given Marlin
432 Delivery System mechanism to acquire the DRM objects representing participation in a
433 domain and acquire the necessary security metadata tokens – and other devices in the
434 domain should be able to use this proxy instead of implementing the Marlin Delivery
435 System specifications themselves. An example of this would be a Marlin compliant,
436 USB connected-only device that acquires content, licenses and metadata from a host
437 gateway to a broadband service.

438

439 **2.2 Marlin Core System Entities**

440

441 Marlin Entities are the Marlin objects and roles (client or service functions) that realize
442 the Marlin functional model.

443

444 Marlin Entities are to a large extent specified using Octopus and Nemo technology (not
445 re-defined in this document). The necessary extensions of Octopus Nodes, Link and
446 License objects and of Nemo Nodes needed for Marlin are specified in detail in the later
447 sections of this document.

448

449 Marlin clients or services are hosted by a Nemo Node which binds the client or service to
450 a Marlin certified identity for authentication purpose, and provides it the keys necessary
451 for message confidentiality and integrity. Marlin further groups client and service
452 functionalities into Marlin Roles. The Roles are certified by a Marlin Certificate Authority
453 and required for establishing trust between clients and services.

454

455 Marlin Nemo Nodes should at most only host one Marlin Role of each type.

456

457 The Marlin Entities not already defined by Octopus or Nemo specifications are defined in
458 this section. Note that for ease of expression, “Octopus <type> Node” is equivalent to
459 “Octopus Node of Type <type>”.

460

461 Marlin Content:

- 462 • Marlin Content is any media that has been encoded, encrypted and packaged
463 into a file container according to the specifications in this document. It is
464 expected that any Marlin DRM Client with the appropriate media rendering
465 capabilities can consume any Marlin Content, as long as the license permits it to
466 do so.

467

468 Marlin User (Node & Link objects):

469 • Marlin Content is generally, although not always, associated with a user. A user
470 is a principal that holds the rights to the content. A user in Marlin is called a
471 Marlin User and is represented by an Octopus User Node. Marlin Devices may
472 be linked to User Nodes
473

474 Marlin Domain (Nodes & Link objects) :

475 • A Marlin Domain Node represents an entity to which Marlin Devices may be
476 linked to form a collection of devices which make up a domain. A Marlin Domain
477 is represented by an Octopus Domain Node.
478

479 Marlin Subscription (Node, Link, License objects):

480 • A Marlin Subscription Node is an entity used for grouping access to multiple
481 Marlin Content items under a single token. A Subscription Node is represented
482 by an Octopus Subscription Node. A Subscription License will typically include a
483 condition that a given Subscription Node be reachable from the Octopus
484 Personality node of the DRM Client attempting to access the content. The
485 access to many Marlin Content items can thus be governed by the availability of
486 a Subscription Link to a Subscription Node, and controls on this link may govern
487 the availability of the entire group of content items whose licenses reference this
488 Subscription Node.
489

490 Marlin Device (role):

491 • A Marlin Device defines the minimum role implemented by any physical device
492 that conforms to the Marlin Core Specifications. It offers limited functionality and
493 is used primarily for Discovery and Identification. Usually a physical device will
494 implement additional roles, such as those described below.
495

496 Marlin Domain Manager (role):

497 • A Domain Manager performs such functions as managing the initial formation of
498 a Marlin Devices Domain, allowing Marlin devices to register and remain in the
499 Domain according to the Domain Policy, and administering the departure of
500 Marlin Devices from the Domain. A Domain Manager hosts an Octopus Domain
501 Node, or a Marlin User Node if the domain is defined as linking Octopus
502 Personality Nodes to User Nodes. It implements any and all functions needed to
503 support Marlin Devices including Domain registration and de-registration. It
504 usually is accompanied by a Marlin DRM Object Provider and a Marlin Domain
505 Information Provider.
506

507 Marlin Domain Information Provider (role):

508 • A Marlin Domain Information Provider is able to give information about Marlin
509 domains (ID and associated policy) it knows about and where DRM Clients can
510 register to these domains.
511

512 Marlin DRM Client (role):

513 • A Marlin DRM Client is the entity authorized to evaluate Octopus Licenses and
514 release content keys to a DRM application for the uses indicated in Octopus
515 License. A Marlin DRM Client is represented by an Octopus Personality Node. It
516 hosts an Octopus Plankton DRM engine and other functions necessary to
517 execute the Octopus Controls included in the Octopus License or other objects

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

518 such as Octopus Links and Octopus Agents. It implements any and all functions
519 needed to evaluate licenses, execute the obligations of the licenses, acquire
520 DRM and Security Metadata Objects, and participate in Domain registration and
521 de-registration.

522

523 Marlin Import function (role):

- 524 • A Marlin Import function may package non-Marlin Content into Marlin Content. It
525 generates an Octopus License that encodes the rights that the content owner
526 intends. The license should govern the content as it is accessed on devices.

527

528 Marlin Security Data Provider (role):

- 529 • A Marlin Security Data Provider makes Security Metadata Objects (assertions,
530 CRLs, etc...) available to other entities, primarily Marlin DRM Clients. The
531 Security Data Provider is analogous to a Data Update Service which supplies
532 current security metadata objects (see Section 9.3.3.)

533

534 Marlin DRM Object Provider (role):

- 535 • A Marlin DRM Object Provider makes DRM Objects (links and agents primarily)
536 available to other entities, primarily Marlin DRM Clients. A DRM Object Provider
537 also enforces any conditions required to make these objects available, such as
538 proximity checks if applicable

539

540 Marlin Certification Authorities

- 541 • Marlin Certification Authorities issue certificates to services that directly or
542 indirectly provision other entities with Octopus Nodes, Links and Licenses, Nemo
543 Nodes, and Role or Security Metadata Assertions. They also issue keys and
544 their certificates needed by individual entities to verify the chain of trust and
545 validate signed objects.

546

547 Implementations will most likely group specific sets of roles with a single Nemo node, as
548 for example in the following:

549

- 550 • A typical device enabled for playing content would host a single Nemo node that
551 groups the following roles
 - 552 ○ Marlin Device
 - 553 ○ Marlin DRM Client (which includes the Octopus Personality Node part of
554 any entity that evaluates content licenses)
- 555 • A device that implements a domain manager would host a single Nemo node that
556 groups the following roles
 - 557 ○ Marlin Device
 - 558 ○ Marlin Domain Manager (as defined in a Delivery System specification)
 - 559 ○ Security Data Provider
 - 560 ○ Marlin DRM Object Provider
- 561 • A device that acts as a proxy to a Domain Manager would host a single Nemo
562 node and could group the following roles (note that such as device would not be
563 provisioned with an Octopus Node)
 - 564 ○ Marlin Device
 - 565 ○ Marlin Domain Information Provider
 - 566 ○ Marlin DRM Object Provider

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

567 **2.3 Marlin Domains**

568 This section illustrates the concept of Marlin Device Domains. Domain specifications
569 have direct implications on specifications for protocols and DRM objects, so while this
570 section is informative, this specification may not support other types of domains than
571 those illustrated here.

572
573 In the simplest terms, a Marlin Domain represents a collection of Marlin DRM Clients
574 that a private consumer considers their own and on which they expect to be allowed to
575 enjoy legally acquired digital content.

576
577 By necessity, this collection is a compromise between the desire of the customer and the
578 wants of the content and service industry that originate and distribute the content. Since
579 no unified definition of this compromise is currently available, this collection itself can
580 have several definitions depending on the type of content and the service provider.

581
582 In order to establish and manage these collections of devices while respecting the terms
583 of the consumer-content industry compromise, Marlin defines Domain
584 Managers, Domain Policies and related data objects and functions that Marlin compliant
585 devices may optionally implement but must conform to.

- 586 • A Domain Manager (usually a software entity, defined above) manages the
587 registration/deregistration of Marlin Devices according to a Domain Policy
- 588 • A Domain Policy expresses the rules for forming, registering and deregistering
589 devices to and from domains. It also defines what is permissible once a device
590 has left a domain. Domain Policies are enforced by the Domain Manager. While
591 DRM Clients may participate in the enforcement of the policy (e.g. participating in
592 a proximity control check), interpretation of the policies of the domains DRM
593 Clients are linked to is not required for the DRM Clients themselves.

594
595 A domain is implemented by establishing and managing Nodes for Users and Domains,
596 and links between Marlin DRM Clients and Marlin User Nodes or Domain Nodes.
597 Presently, the policies that govern these are defined in the Delivery System
598 Specifications. The definition of the resulting nodes and links are part of the core
599 specification.

600
601 **Marlin Domain Topologies**

602
603 A Marlin Domain Topology describes how Marlin Users, DRM Clients and Domain
604 Nodes are associated in a domain.

- 605
606 Topologies are described in terms of:
- 607 • DRM Clients – represented by an Octopus Personality Node that is the root of
608 the DRM engine that consumes content.
 - 609 • Domain Managers – represented by an Octopus Domain or User Node that
610 represents the domain they administer.
 - 611 • Marlin Users – represented by an Octopus User Node
 - 612 • Octopus Links – that express relationships between Octopus Nodes of DRM
613 Clients, User Nodes, and Domain Nodes according to a desired domain topology
- 614

615 The Marlin Core Specifications define Octopus Object extensions that can be used
616 by domain managers to encode in nodes, links and licenses the necessary domain-
617 related metadata and controls for demonstrating active membership in a domain.
618 They also define protocols by which the objects can be obtained, and the metadata
619 queried.

620
621 A certain subset of these domain-related metadata and controls is mandatory to
622 implement.

623 **Marlin Domain Policies**

624
625
626 The rules that govern whether a DRM Client can register with a Domain, and what the
627 consequences are when a device deregisters from a domain, are implemented by the
628 Domain Manager and the DRM Client Device in accordance with the Domain Policy.
629

630 Note that different types of contents may be processed differently in a same domain,
631 according to the usage rules that govern the content.
632

633 This version of the specifications defines DRM Objects and functions that can support a
634 set of Domain Policies Elements such as those defined below.
635

636 **Marlin Domain Policy Elements - Examples**

637
638 Domain Policies can be defined in terms of the following elements

- 639 • Domain Policy Identifier
- 640 • Registering Policy (per device type if differentiated)
 - 641 ○ Number of domains of this type a device can register
 - 642 ○ Max number of devices of a certain type that can be linked to a domain
643 node
 - 644 ○ Max age of link before self-deactivation if not renewed
 - 645 ○ Proximity check required for registering & acceptable RT delay.
646
- 647 • Deregistration Policy - one of (per device type if differentiated)
 - 648 ○ The deregistration policy uses Marlin Core System Protocols and
649 Octopus Objects in order to implement the intent of the policy, such as
650 whether the content that used to be accessible on the device prior to the
651 deregistration action should
 - 652 ▪ still play after the deregistration, or
 - 653 ▪ no longer play after the deregistration

654 **2.4 Content Binding and Movement under Marlin Governance**

655 Marlin Content is usually bound to an Octopus User Node, Domain Node, or Personality
656 Node and targeted to an Octopus User Node, Subscription Node or Personality Node
657

658 When the content is bound to a Node, the key that encrypts the content key is one of the
659 Scuba Sharing keys of that Node. To decrypt the content key, the DRM engine will look
660 for a set of links with scuba extensions, from the Octopus Personality Node of the DRM
661 client that attempts to access the content key, to the Node that the content is bound to.
662

663 When the content is targeted to a Node, the control in the license will have a condition
664 that checks whether that Node is reachable. When the control is executed, the DRM
665 engine will look for a set of links (with or without scuba extensions) from the Octopus
666 Personality Node of the DRM client that attempts to access the content key, to the Node
667 that the content is targeted to
668

669 Note: If the content is bound to another node than it is targeted to, it is good practice to
670 also include a condition of node reachability for the node that the content is bound to.
671 This will allow the license evaluation to fail should the content be bound to a node that is
672 not reachable from the Octopus node of the DRM engine that attempts to access the
673 content.
674

675 Combining Binding and Targeting offers a variety of content handling options:

- 676 • Binding and Targeting content to a (User or Domain) node linked to a set of
677 Marlin DRM clients (with scuba extensions on the links) allows the content to be
678 equally accessed on all the DRM clients (all other things such as device
679 capabilities and controls on the links being equal)
- 680 • Binding and/or Targeting the content to the Octopus Personality Node of a Marlin
681 DRM Client node prevents this content from being accessed on any other device
682 than that one
683

684 Marlin defines move/copy protocols and actions that allow for the following:

- 685 • The license of content bound and/or targeted to the Octopus Personality Node of
686 a source DRM client can be “copied” or “moved” to the Octopus Personality Node
687 of a sink DRM Client. The conditions on this copy or move differ, depending on
688 whether or not the source and sink are linked to the same Octopus User or
689 Domain Node. For example:
 - 690 ○ If the source and sink are linked to the same node, the action is a simple
691 re-binding of the license
 - 692 ○ If the source and sink are not linked to the same node, or not linked to
693 any node, the action requires a proximity check between source and sink
694 The difference between move and copy is whether or not access to the
695 content on the source device is maintained after the completion of the
696 transaction. Move disables access on the source device, copy does not. All
697 other terms of the license remain in effect.
698

699 Whether copy or move or both are allowed is expressed in the license of the
700 content, and therefore determined entirely by the import function of the
701 domain the content is imported into.
702

703 **Export from Marlin to Other DRM systems**

704 Export is an operation by which Marlin contents are transferred to other DRM systems.
705 Whether the export operation is permitted is specified by usage rules in a license. Also
706 specified must be the usage rules to apply to the content in the target DRM.
707

708 In export operations, Marlin export functionality does not specify the means of
709 transformation of license or contents for other DRM systems.
710

711 For basic export mode, the original content (license) remains valid at the source Marlin
712 DRM Client after the export operations.

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

713 **3 Marlin DRM Objects**

714

715 Marlin DRM Objects are Octopus objects ([8pus] §2) with Marlin-specific attributes
716 extensions, and encoding.

717

718 Note: Certain Octopus Object Attributes or Extensions defined in this section are
719 optional. Unless expressly mentioned otherwise, when they are present in the Object,
720 they MUST be made available to the DRM engine for reference in control programs.

721 **3.1 Octopus Objects**

722 **3.1.1 Node and Link Objects**

723 As explained in [8pus] §2, Octopus Nodes represent entities that content can be “bound
724 to” in the DRM system (e.g. a device, a device group or a user). The Octopus node
725 representing a “license evaluating” entity (e.g. a device) is represented by a Personality
726 Node.

727

728 Links are directed assertions between two Nodes. For example, a link from a device
729 node to a user node may indicate that the device belongs to the user. Links can be
730 thought of as “license enablers” in the sense that if a license requires user Node X to be
731 reachable, then the condition would be met if the device has a link from its personality
732 node to user Node X.

733 **3.1.2 License Objects**

734 As explained in [8pus] §2, the Octopus license objects are the following:

- 735 • ContentKey: represents the key, CK. CK is the key which encrypts the content.
736 The ContentKey object MAY contain one or more expressions of the encrypted
737 CK.
- 738 • Protector: associates one or more Content objects and a ContentKey object.
739 There is no need for a secure association here as the ContentKey object is
740 needed to decrypt the content.
- 741 • Control: represents how the content key, and therefore the content, is governed.
742 A Control object embeds [Plankton] bytecode that is executed according to a
743 protocol (see [8pus] §3) that returns a result for a particular Action query (e.g.
744 PLAY). Note that the Controls can be used in a different context than a License:
745 they can be used as “Agents” in order to execute plankton bytecode on a DRM
746 Client in order to initialize a counter for example.
- 747 • Controller: associates securely one or more ContentKey objects and a Control
748 object.

749 **3.1.3 Lookup Scope for Spawned Controls**

750 When a control program uses the System.Host.SpawnVm system call [8pus] §4.7.2.10
751 the ‘ModuleId’ parameter identifies a Control object to load. In this specification, the
752 following lookup rule to locate the Control object with the specified ID SHALL be used:

- 753 • Look in the same Bundle in which the control program issuing the system call is
754 located.

755 Since Control objects have globally unique IDs, the lookup search order is not relevant,
756 because in the case where more than one representation of the same Control object
757 with the specified ID exist, they all represent the same Control object.

758 **3.1.4 Agent Conveyance for License Transfer**

759 The Agent for Transfer action (see Section 5.7.6) included in a Control object MUST be
760 carried as an External Extension. The External Extension MUST have the following
761 properties:

- 762 • The External Extension is placed as the direct child element of the corresponding
763 License Bundle.
- 764 • The External Extension has the subject attribute which value has the same value
765 as the uid attribute of a Control object which includes the corresponding Transfer
766 action.

767
768 The Control object which includes the Agent and carried in External Extension MUST
769 have PKI signature. The External Extension MUST contain one Bundle element. The
770 Control object and the PKI signature MUST be placed as the direct child elements of that
771 Bundle element. The PKI signature MUST have the following properties:

- 772 • The PKI signature has only one Reference which refers to the Control object for
773 the Agent.
- 774 • The signer of the PKI signature is same as the signer of the Controller object
775 associated with the Control object including the corresponding Transfer action.

776 If a license contains an Agent which uses the System.Host.SpawnVm system call to load
777 other Control objects, such Control objects SHALL be placed in the same Bundle
778 element in which the Agent issuing the system call is placed. Therefore, during License
779 Transfer, all the elements in the Bundle element containing the Agent SHALL be
780 included in the Agent Carrier.

781
782 Note that HMAC and PKI signature for the Controller objects SHALL NOT have the
783 Reference for the External Extension nor the Control object for the Agent.

784 **3.2 Octopus Object Attributes and Extensions**

785 **3.2.1 Octopus Nodes**

786 Marlin defines various types of Octopus nodes with different attributes and extensions. A
787 DRM Client is NOT REQUIRED to check whether the required attributes appear in the
788 Octopus Object but it MAY return an error if a required attribute is not in the object.

789
790 As introduced in Section 1.3.2, attribute and extension identifiers must begin with the
791 appropriate prefix. The following table defines the attribute prefix, types of nodes, their
792 values and the REQUIRED extensions. Unspecified attribute types have a default type
793 of string.

794

urn:marlin:core:node:attribute:type	
Node Type	Attribute Value(s)
Personality	personality
Domain	domain
User	user

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

Subscription	subscription
Other	*

795 **Table 3-1 Octopus Node Types**

796 The Scuba key requirements for the above Octopus Node types are outlined below.
797 When present these keys SHALL be carried in Octopus Node object extensions as
798 defined in [MCSV13] §3.3.3.1 and [8pus] §6.2.2. Server implementations MAY provision
799 and process Scuba keys for the Octopus Node types described below. Client
800 implementations SHALL support the Octopus Node and Octopus Link types it acquires
801 through the client implemented protocols. Client implementations SHALL be able to
802 derive Scuba Sharing keys carried in these acquired Octopus Links as defined in [8pus]
803 §6.5.

- 804 • Personality nodes SHALL include a Public/Private Scuba Sharing key pair
- 805 • Personality nodes SHALL include a Secret Scuba Sharing key
- 806 • Personality nodes SHALL include a HBES Device Keyset [Starfish]
- 807 • Personality nodes MAY include a Public/Private Scuba Confidentiality key pair
- 808 • User nodes SHALL include a Public/Private Scuba Sharing key pair and/or a
809 Secret Scuba Sharing key
- 810 • User nodes MAY include a Public/Private Scuba Confidentiality key pair
- 811 • Subscription nodes MAY include a Public/Private Scuba Sharing key pair and/or a
812 Secret Scuba Sharing key
- 813 • Domain nodes SHALL include a Secret Scuba Sharing key
- 814 • Domain nodes MAY include a Public/Private Scuba Sharing key pair

815
816 Note that services distribute and use Scuba keys based on the business models they
817 implement. Octopus Nodes, Links and Scuba keys are generic technologies, when
818 implemented accordingly, enable services and clients to interoperate in a semantic-free
819 manner.

820
821 Whenever an Octopus node contains one or more scuba public keys, the format of these
822 public key SHALL be the DER encoding of the ASN.1 structure SubjectPublicKeyInfo
823 defined in [RFC3280] §4.1. The identifier for this format is "SPKI".
824

825 In addition to the attributes which identify the node to be of a particular type, the
826 following attributes SHALL also be specified for certain node types:
827

Node Type	Attribute Identifier	Attribute Type	Attribute Value(s)
Personality	urn:marlin:core:node:attribute:device-class	string	Dedicated Device Personal Computer Portable Device
	urn:marlin:core:node:attribute:device-features	array	To be defined
Domain	urn:marlin:core:node:attribute:domain-policy-type	string	To be defined in each delivery system specification

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

828 **Table 3-2 Node Attributes Values**

829 The attribute values defined in Table 3-2 are terms which enable classification of the
 830 node at a very coarse granularity. The following table provides guidance on the
 831 semantics of these terms.
 832

Attribute Value	Description
Dedicated Device	A node in this class implies that it hosts a dedicated application which, in general, permanently resides in a home setting.
Personal Computer	A node in this class implies that it hosts the DRM application on an open application platform which, in general, permanently resides in a home setting.
Portable Device	A node in this class implies that it hosts the DRM application on a dedicated platform which, in general, is not necessarily permanently resident in a home setting.

833 **Table 3-3 urn:marlin:core:node:attribute:device-class Attribute Value Descriptions**

834 The urn:marlin:core:node:attribute:device-features attribute is an array of attributes (see
 835 [8pus] §2.2.1.2). This OPTIONAL attribute is used as a container for describing the
 836 permanent features of a device¹.

837 **3.2.1.1 Octopus Personality Nodes**

838 The following data elements SHALL be included in the private part of an Octopus
 839 personality node.
 840

Data	Description
Data for Secret Key of Scuba Sharing Key	
Key Id	URN for the scuba sharing secret key
Key Data	Key data of the secret key
Data for Private Key of Scuba Sharing Key	
Key Pair Id	URN for the scuba sharing public/private key pair
Key Data	Key data of the private key
Data for Device Key Set [Starfish]	
Device Id	Device Id defined in [Starfish] §3.2.2
Key Tree Id	URN for the HBES Key Tree.
Algorithm Id	Algorithm Identifier for the Starfish. It MUST be set to http://marlin-drm.com/starfish/algorithmID/1.0
Device Key Set	Device Key Set defined in [Starfish] §3.3.1

841 **Table 3-4 Data elements in the private part of an Octopus personality node**

¹ This attribute is intended to provide additional qualifiers to further distinguish the capabilities of a device. Values will be defined in the future.

842 Refer to Section 3.3.3.1.1 for a description of the XML encoding of an Octopus
843 personality node.

844 3.2.2 Octopus Links

845 Links MAY have Scuba extensions that carry the encrypted private and secret scuba
846 sharing keys of the node “to” with the public or secret sharing key of the node “from”.
847 Links from personality to domain nodes MAY have several attributes:
848

urn:marlin:link:attribute	
Attribute Identifier	Description
urn:marlin:link:attribute:domain-serial-number	Domain serial number of the link
urn:marlin:link:attribute:link-type	Type of link
urn:marlin:link:attribute:domain-policy	Domain Policy
urn:marlin:link:attribute:domain-id	Domain ID Context

849 **Table 3-5 Link Attributes**

- 850
- 851 • domain-serial-number: This OPTIONAL attribute carries the domain serial
852 number of the link. The presence of this attribute depends on whether the policy
853 of the domain requires it.
 - 854 • link-type: This OPTIONAL attribute type of link. An example of value would be
855 device-to-domain.
 - 856 • domain-policy: This attribute specifies the policy ID identifying the domain policy.
857 It is REQUIRED for all domain related links.
 - 858 • domain-id: This attribute indicates the domain context for which this link is apart
859 of. It is REQUIRED for all domain related links.²

860 If the Link includes a Control Object, the attributes of the Link Object SHALL be visible to
861 the Plankton Virtual Machine running this Control under the following container:
862

/Octopus/Link/Attributes/

863

864 External Extensions SHALL have uid attributes that follow the URN definitions and
865 conventions defined in Section 1.3.3.

866 3.2.3 License objects

867 When the Control is run, all the attributes of the Control and Controller Objects SHALL
868 be visible to the Plankton Virtual Machine under the following containers (as specified in
869 [8pus] §3):
870

/Octopus/Control/Attributes
/Octopus/Controller/Attributes

871

² A domain-id attribute MUST be a globally unique value. The representation MAY be a URI and it may be best implemented as a random value encoded in the URI. A UUID would also be a reasonable URI representation.

872 **3.2.4 License Object Contexts**

873 The purpose of license object contexts is to allow an implementation to delay the loading
874 of certain persistent objects, such as links, until it encounters a license that indicates that
875 those objects are needed for a successful evaluation of the license.

876 **3.2.4.1 Contexts IDs**

877 A Context ID is simply a unique ID that is used to tag objects, in order to indicate that
878 these objects are associated with a certain context.

879 **3.2.4.2 Context Tag in Objects**

880 For Link and Node objects, the context ID, if any exists, SHALL be carried as the value
881 of an object attribute named 'ContextTag'.

882 **3.2.4.3 Contexts in Bundles**

883 When content licenses are created, and stored as a set of objects, signatures and other
884 elements in a Bundle, the license issuer MAY include one or more context IDs. This
885 signals to the host application that is processing the bundle that it SHOULD load in the
886 runtime environment all persistent objects that have a context tag equal to one of the
887 context IDs present in the Bundle. If the persistent objects with matching tags had
888 already been loaded, no action is required of the application or device. The application
889 or device MAY unload or cleanup those objects when it is done processing the content
890 related to that Bundle.
891

892 **3.3 XML Encoding of Octopus Objects**

893 **3.3.1 Overview**

894 Marlin defines its own XML schema. This schema imports the Octopus XML schema and
895 adds elements specific to Marlin (for example, the revocation extension.)
896 The encoding of Octopus objects in XML MUST be valid instances of the schema
897 elements defined by this specification.

898 **3.3.2 General Schema Design**

899 The XML representation of all the Octopus objects is based on the complex type
900 <oct:OctopusObjectType>. Thus, all the Octopus objects SHALL support attributes and
901 extensions. The type of each Octopus Object element is derived from this base type.
902 These types may aggregate other elements such as the <oct:SecretKey> element for
903 the <oct:ContentKeyType> for instance.
904

905 The key distribution system keys ([8pus] §6) SHALL be described in the terms of an
906 extension: the <oct:ScubaKeys> element SHALL then be a child of the <oct:Extension>
907 element. The same SHALL be true for revocation keys with the <oct:Torpedo>
908 revocation extension defined in Marlin schema.
909

910 As explained in [8pus] §2, there are different kinds of Octopus Objects (ContentKey,
911 Protector, Controller, Control, Node and Link). These objects can be bundled together as
912 well as Extensions using the <oct:Bundle> element. If objects or extensions are signed

913 within the <oct:Bundle>, the <oct:Bundle> SHALL contain <ds:Signature> elements
914 defined in [xmldsig] and in accordance with the profile in Section 3.3.4.
915
916 In the case where a license uses a revocation extension such as broadcast encryption (a
917 DRM Client has been revoked), the <sf:BroadcastKeyblock> SHALL be carried inside
918 the <oct:Bundle> (see Section 7.4).
919
920 In the case where the license creator wants to advertise that this license needs a certain
921 context to be loaded (which maps to a set of Octopus Links), the <oct:Bundle> MAY also
922 embed a <ml:ContextList> element carrying all the needed <ml:Context> URIs.

923 **3.3.3 Additional Constraints on the Schema**

924 **3.3.3.1 Nodes**

925 Nodes contain keys (in Extensions such as ScubaKeys.) It should be possible to
926 separate the public information of the Node (the id, attributes and public keys) and its
927 private extensions (that will carry the secret and private keys). Moreover, there should
928 be one signature per part (the public and the private) so that the public node with its
929 signature can be exported as is (as a parameter of the request to a registration service
930 for example.)

931
932 According to the taxonomy of [8pus] §2, the private extensions must be carried in an
933 ExternalExtension and signed. Thus for the XML representation of the public Node and
934 its private Extensions MAY be packaged in the same <oct:Bundle> element or MAY
935 arrive separately.

936
937 Whenever an Octopus node contains one or more scuba public keys, the attributes of
938 the KeyData element carrying these keys SHALL be:

- 939 • encoding="base64"
- 940 • format="X509SPKI"

941 **3.3.3.1.1 Personality Nodes**

942 Personality Nodes may include confidential information. When the data elements
943 concerning a Secret Key and/or a Private Key of a Scuba Sharing Key are encoded in
944 an XML format, then the schema defined by the namespace [http://www.octopus-](http://www.octopus-drm.com/profiles/base/1.0)
945 [drm.com/profiles/base/1.0](http://www.octopus-drm.com/profiles/base/1.0) may be used for the encoding.

946 The following is an example of an XML fragment of the private part of an Octopus
947 personality node within a Scuba extension. Note that the namespace
948 xmlns:oct="http://www.octopus-drm.com/profiles/base/1.0" is assumed for this example.
949

```
[01] <oct:ScubaKeys>
[02]   <oct:SecretKey
           uid="urn:marlin:organization:phony:octopus-personality:01:secret-sharing"
           usage="KeySharing">
[03]     <oct:KeyData encoding="base64"
                   format="RAW">Z8Zpc1H...=</oct:KeyData>
[04]   </oct:SecretKey>
[05]   <oct:PrivateKey
           uid="urn:marlin:organization:phony:octopus-personality:01:private-sharing"
```

```

pair="urn:marlin:organization: phony:octopus-personality:01:pair-sharing"
usage="KeySharing">
[06] <oct:KeyData encoding="base64"
format="PKCS#8">MIIC...=</oct:KeyData>
[07] </oct:PrivateKey>
[08] </oct:ScubaKeys>

```

950

951 Line [02], in the above example, uid attribute indicates Key Id in Table 3-4.

952

953 Line [03], in the above example, the <oct:KeyData> element carries the base64 encoded
954 value of the secret key.

955

956 Line [05], in the above example, pair attribute indicates Key Pair Id in Table 3-4.

957

958 Line [06], in the above example, the <oct:KeyData> element carries the base64 encoded
959 value of the private key in the format specified by [PKCS8].

960

961 When data elements concerning a Device Key Set [Starfish] are encoded in an XML
962 format, the schema defined by the *http://marlin-drm.com/starfish/1.2* namespace MAY
963 be used for the encoding.

964

965 The following is an example of an XML fragment of the Torpedo extension of the private
966 part of an Octopus personality node. Note that we assume the *xmlns:ml="http://marlin-
967 drm.com/1.0"* attribute has been defined in this example.

```

[01] <ml:Torpedo>
[02] <ml:BroadcastKey uid="0F2A130003000002"
[03] source=" urn:marlin:starfish:keytree:1">
[04] <ml:BroadcastKeyMethod
[05] Algorithm="http://marlin-drm.com/starfish/algorithmID/1.0"/>
[06] <oct:KeyData encoding="base64"
[07] format="RAW">Z8Zpc1H...=</oct:KeyData>
[08] </ml:BroadcastKey>
[09] </ml:Torpedo>

```

968

969 Line [02], in the above example, uid attribute indicates ASCII hex representation of
970 Device ID, and source attribute indicates the name of the Key Tree Id in Table 3-4.

971

972 Line [04], in the above example, algorithm attribute indicates Algorithm Id in Table 3-4.

973

974 On Line [06], in the above example, the <oct:KeyData> element carries the base64
975 encoded value of the Device Key Set in Table 3-4.

976 3.3.3.1.2 Attributes

977

978 Each XML encoding of a Node object SHALL carry an <oct:AttributeList> with the
979 <oct:Attribute>(s) as defined in Section 3.2.1.

979

980 Example:

```

<oct:AttributeList xmlns="http://www.octopus-drm.com/profiles/base/1.0">
<oct:Attribute name="urn:marlin:core:node:attribute:type">user</oct:Attribute>

```

```
</oct:AttributeList>
```

981 **3.3.3.1.3 Extensions**

982 All the public keys SHALL be carried inside the <oct:Node> element (in an
983 <oct:Extension> element in the <oct:ExtensionList>). Other keys SHALL be carried in a
984 separate <oct:Extension> element outside of the <oct:Node> element.

985
986 Marlin SHALL follow the Octopus Objects specification ([8pus] §2). The
987 <oct:ScubaKeys> extensions SHALL be signed in the <oct:Node>. This means that the
988 internal <oct:Extension> carrying <oct:ScubaKeys> inside the <oct:Node> (public keys)
989 SHALL include a <ds:DigestMethod> element as well as a <ds:DigestValue> element.
990 These elements MUST follow the guidance given in Section 3.3.4.

991 **3.3.3.2 Links**

992 The <oct:LinkTo> and <oct:LinkFrom> elements SHALL only carry a <oct:Uid> element
993 (i.e. no <oct:Digest> element).

994
995 The <oct:Control> element is optional.

996 **3.3.3.2.1 Attributes**

997 Link attributes defined in Section 3.2.2. MUST be encoded in XML following the Octopus
998 schema and packaged in an <oct:AttributeList>.

999
1000 Example:

```
<oct:AttributeList xmlns=" http://www.octopus-drm.com/profiles/base/1.0">  
  <oct:Attribute name="urn:marlin:link:attribute:domain-id">  
    urn:marlin:domain:29490343</oct:Attribute>  
  <oct:Attribute name="urn:marlin:link:attribute:domain-policy">  
    urn:marlin:broadcast:domain-policy:organization:phony:fuse:policy:0  
  </oct:Attribute>  
</oct:AttributeList>
```

1001 **3.3.3.2.2 Extensions**

1002 Links MAY have <oct:ScubaKeys> internal extensions carried inside the <oct:Link>
1003 element. When they do, the <oct:ExtensionList> element MUST be present.

1004
1005 According to [8pus] §2, within a Link, the <oct:ScubaKeys> extension is not signed.
1006 Therefore, the <ds:DigestMethod> and <ds:DigestValue> elements SHALL NOT be
1007 carried inside the <oct:Extension> element.

1008
1009 The <oct:ScubaKeys> extension contains an encrypted version of the private/secret
1010 Scuba Sharing keys (in a <oct:PrivateKey> and a <oct:SecretKey> element) of the “to”
1011 Node with the public or secret Scuba Sharing key of the “from” Node. This encryption
1012 SHALL be expressed using the syntax specified in [xmlenc].

1013
1014 The oct:encoding attribute of the <oct:KeyData> element, a child of the both the
1015 <oct:PrivateKey> and <oct:SecretKey> elements, MUST be set to “xmlenc”.
1016

1017 The child of this <oct:KeyData> element MUST be an <xenc:EncryptedData> element.
1018 The name of the encryption key MUST be advertised in the
1019 <ds:KeyInfo>/<ds:KeyName> element.

1020

1021 **Note: Encrypting with a public key**

1022 If the encryption key is a public key, then:

- 1023 • The <ds:KeyName> element MUST be the name of the pair to which the key belongs
1024 to. This element MUST reflect the same identity as paired field specified in [8pus]
1025 §2.4.5.
- 1026 • In case the encrypted data (a private key for example) is too big to be encrypted
1027 directly with a public key, an intermediary 128 bit secret key is generated. The data
1028 MUST be encrypted with this intermediary key using [aes-128-cbc] and the
1029 intermediary key MUST be encrypted with the public key. The encrypted
1030 intermediary key MUST be encoded in a <ds:EncryptedKey> element. A example
1031 follows:

1032

```
<!-- E(I, data) -->
<EncryptedData xmlns="http://www.w3.org/2001/04/xmlenc#">
  <EncryptionMethod
Algorithm="http://www.w3.org/2001/04/xmlenc#aes128-cbc"/>
  <KeyInfo xmlns="http://www.w3.org/2000/09/xmldsig#">
    <!-- E(PUBa, I) -->
    <EncryptedKey xmlns="http://www.w3.org/2001/04/xmlenc#">
      <EncryptionMethod
Algorithm="http://www.w3.org/2001/04/xmlenc#rsa-1_5"/>
      <KeyInfo xmlns="http://www.w3.org/2000/09/xmldsig#">
        <KeyName>urn:x-octopus:key-pair:300a</KeyName>
      </KeyInfo>
      <CipherData>
        <CipherValue>
fFeGD4KAPeMESz/jW6CkbRegpM5kyH0Oy/o/uDQ78PaShtvUMoozeO4a0b785YnB
13Qa1ZUEYqR9V5TCUa0cH7wxxvBEIsdlnYKkVOgW/kFnRr98UDFvU90PRqaEP/SA
Bb+JuAUmvxYX47qOVQqBQGGqzFssBDKmuK+s98dkPR8=
        </CipherValue>
      </CipherData>
    </EncryptedKey>
  </KeyInfo>
  <CipherData>
    <CipherValue>
c8LBJ4BLzGOYv/GT3Y4w2XcwTYbr8fHNJhCOQjULuvoha/QYvZKKCPUY+nuCXC/s
t9TU+8tMtaMt1GUPkCZQhSaTNcluCSxOyBoA6Xh/bmyZLDJ78+aJ/sITmfNpJGdb
vTaI7x9DD1MplmvFEjpAUjTTvruN32g4bxsf7FD8C1RWNac4hS96nFDgrmzoO5pR
dda6mswFKG5B0kY7mYbhacblowXkAk1Wc/OuXA+QLHdUthxea joXNPFAGRz9FM3b
puJxbxDAAA AJDxoReiTtSlnGaHhqa1hvLCpKk1zHBowHyvTvDLElLjHYEPeG6xSH
BbzpT298tdKUHxfaY6vvdceMdVXuBVL3eZP1jkJHDxeaBylce8xlQKZpo6Pjuxlb
bn5KUMt/PxWp7rLa5s786S740cwuN63+ZRgienxPK1CnYO3htMJ7hh/agvO9IyUD
RvcgnSEY9KA5Exy/6gIS/gouIjFU8r7056XcE4/IBodTWDkfyli/y8q5QA/0VaD9
Y3oER1p3pYuHwn/IeXM4gsBD31cgd7nfvK7lKYkZjowR9P6pSy57a+K4LZKDMfUH
zG/gZs2XcPb9o6mVAEEej7+aLwqmoileykR+0pkFntvqvXYRpkphhcVdzjz1MV
scpXBXfWx7wbQURXkiew7R4RihQy3wcv+ZFJpl9NsAElyqyWy4rBobzZ7cTNMtfR
znhVlt+Wwq5G0IBxzU9WIFzFd/Rn2H9L4TI71LCa4VR3uNpf+XM8lp9LjLPRUnNh
28KrMdAddceyopYyiIF5p8idfh0//a/LKdE7JAK0q9ewk19ryqfl6CFeKI5oOmjh
kzNx3BR/iHxm31HIe3ZKtA==
    </CipherValue>
  </CipherData>
</EncryptedData>
```

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

```
</CipherValue>
</CipherData>
</EncryptedData>
```

1033 **3.3.3.3 Protector**

1034 The <oct:ContentKeyReference> element MUST contain a <oct:Uid> element and
1035 MUST NOT include a <oct:Digest> element.

1036
1037 The <oct:ContentReference> elements (inside the <oct:ProtectedTargets> element)
1038 MUST contain a <oct:Uid> element and MUST NOT include a <oct:Digest> element.

1039
1040 Protector objects contain no mandatory attributes or extensions.

1041 **3.3.3.4 ContentKey**

1042 ContentKey objects contain no mandatory attributes or extensions. Therefore the
1043 <oct:AttributeList> and <oct:ExtensionList> elements are optional and MAY be ignored.

1044
1045 <oct:ContentKey> elements contain a <oct:SecretKey> element which represent the
1046 actual key needed to decrypt the content. The <oct:KeyData> associated with the
1047 <oct:SecretKey> MUST be encrypted. Therefore the oct:encoding attribute of
1048 <oct:KeyData> MUST be set to "xmlenc". There MAY be several <oct:KeyData>
1049 elements if there are multiple expressions of the encrypted content key in the object.

1050
1051 There are two distinct cases for ContentKey objects (see Section 7):

- 1052 a. Before the first revocation of a device or a PC application: in this case, the
1053 content key CK represented by the <oct:SecretKey> element MUST be
1054 encrypted by a Scuba key (public or secret) of the entity to which the content is
1055 bound to (for example the user.) See Section 7.3.
- 1056 b. After the first revocation the content key MUST first be encrypted according to
1057 the [Starfish] broadcast encryption scheme. The resulting data is then encrypted
1058 with a Scuba key (public or secret) of the entity to which the content is bound to.
1059 See Section 7.4.

1060 **3.3.3.5 Controller**

1061 Controller objects MAY contain attributes or internal extensions. However, when these
1062 elements are present in either a <oct:AttributeList> or <oct:ExtensionList> elements then
1063 these elements SHALL be processed.

1064
1065 An optional Domain Serial Number MAY be attached to the Controller object depending
1066 on the domain policy. When present it SHALL be visible to the Plankton Virtual Machine
1067 as described in Section 3.2.3.

1068
1069 The <oct:ControlReference> MUST have a <oct:Digest> element. The <ds:DigestValue>
1070 element MUST contain the base64 [MIME] encoding of the digest of the referenced
1071 control (see [8pus] §2).

1072
1073 The <oct:ContentKeyReference> MUST have a <oct:Digest> element. The
1074 <ds:DigestValue> element MUST contain the base64 [MIME] encoding of the digest of

1075 the referenced ContentKey (see [8pus] §2). The the algorithms, identifiers and
1076 representation of the <oct:Digest> MUST follow the guidance given in Section 3.3.4

1077 **3.3.3.6 Control**

1078 Control objects MAY contain attributes or internal extensions. When these elements are
1079 present in either a <oct:AttributeList> or <oct:ExtensionList> elements, these elements
1080 SHALL made available to the DRM engine.

1081
1082 The oct:protocol attribute of the <oct:ControlProgram> element MUST be signaled using
1083 the Standard Control Protocol identifier defined in [8pus] §3.2.3.

1084
1085 The oct:type attribute of the <oct:CodeModule> element MUST be signaled using the
1086 Plankton Control Module identifier defined in [8pus] §3.2.4.

1087 **3.3.4 Signatures: Use of XML Digital Signature [xmldsig]**

1088 According to the Octopus Objects specification ([8pus] §2) the Octopus objects that are
1089 directly signed (unless an exception is given) include:

- 1090 • Nodes
- 1091 • Links
- 1092 • Controllers
- 1093 • Controls
 - 1094 ○ A Control need not be directly signed if it is indirectly covered by a secure
1095 digest in a referring Controller object.
 - 1096 ○ A Control need not be independently signed if it is covered by the
1097 signature of a containing Link object.
- 1098 • Extensions (depending on the data they carry)

1099
1100 The signatures MUST follow the profile given in Section 12.2. A <ds:Signature> element
1101 SHALL be present in the <oct:Bundle> object that contains the XML representation of
1102 the signed Octopus objects. There MAY be multiple signatures covering the same object
1103 such as a Controller being covered by a (certified) public key signature and an HMAC
1104 (symmetric key) signature.

1105 **3.3.4.1 Controller Objects**

1106 Controller objects MUST have at least one HMAC signature for each ContentKey
1107 referenced in its list of controlled targets. The key used for each of those signatures
1108 MUST be the content key contained in the ContentKey object referenced.

1109 The DRM Client MUST verify the HMAC signature for every Controller object prior to
1110 invoking the Perform routine of any Action [8pus] §3.2.6.3 on an Octopus Control.

1111
1112 Controllers MAY also have a public key signature. If such a signature is present, this
1113 signature MUST also appear as a <ds:Reference> in each of the HMAC signatures for
1114 the object. To achieve this, this <ds:Signature> element MUST have an xs:ID-typed
1115 attribute (unique within the enclosing XML document) which is used as the ds:URI
1116 attribute in one of the <ds:Reference> elements of each of the HMAC signatures. The
1117 verifier MUST verify the public key signature if it is present. The verifier MUST reject
1118 public key signatures that are not corroborated by the HMAC signature.

1119
1120 Example:

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

```

<ds:Signature Id="Signature.0" >
  <ds:SignedInfo>
    <ds:CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
    <ds:SignatureMethod Algorithm="http://www.w3.org/2000/09/xmldsig#rsa-sha1" />
    <ds:Reference URI="#Controller">
      <ds:Transforms>
        <ds:Transform Algorithm="http://www.octopus-drm.com/octopus/specs/cbs-1_0" />
      </ds:Transforms>
      <ds:DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
      <ds:DigestValue>G1zXF9Sz/zCwH6MaFm0ObOQcxuk=</ds:DigestValue>
    </ds:Reference>
  </ds:SignedInfo>

  <ds:SignatureValue>mjoyW+w2S9iZDG/ha4eWYD1RmhQuqRuuSN977NODpzwUD02FdsAIC
  VjAcw7f4nFWuvtawW/clFzY
  P/pjFebESCvurHUsEaR1/LYLDkpWWxh/LIEp4r3yR9kUs0AU5a4BDxDxQE7nUdqU9YMpnjAZ
  EGpu
  xdPeZJM1vyKqNDpTk94=</ds:SignatureValue>
  <ds:KeyInfo>
    <ds:X509Data><ds:X509Certificate>MICh...</ds:X509Certificate></ds:X509Data>
  </ds:KeyInfo>
</ds:Signature>
<ds:Signature>
  <ds:SignedInfo>
    <ds:CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
    <ds:SignatureMethod Algorithm="http://www.w3.org/2000/09/xmldsig#hmac-sha1" />
    <ds:Reference URI="#Signature.0">
      <ds:DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
      <ds:DigestValue>AqPV0nvNj/vc51lcMyKJngGNkMtM=</ds:DigestValue>
    </ds:Reference>
    <ds:Reference URI="#Controller">
      <ds:Transforms>
        <ds:Transform Algorithm="http://www.octopus-drm.com/octopus/specs/cbs-1_0" />
      </ds:Transforms>
      <ds:DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
      <ds:DigestValue>G1zXF9Sz/zCwH6MaFm0ObOQcxuk=</ds:DigestValue>
    </ds:Reference>
  </ds:SignedInfo>
  <ds:SignatureValue>TcKBsZZy+Yp3doOkZ62LTfY+ntQ=</ds:SignatureValue>
  <ds:KeyInfo>
    <ds:KeyName>urn:x-octopus:secret-key:2001</ds:KeyName>
  </ds:KeyInfo>
</ds:Signature>

```

1122 **4 Marlin Core System Roles and Services**

1123 Marlin Core system entities implement the defined Marlin Roles and Services. Certain
 1124 Roles are optional. However, when implemented, they MUST conform to the
 1125 specification. Certain typical device functions MAY require the aggregation of several
 1126 Roles. For example, a Media Device that wants to render Marlin content MUST
 1127 implement the Device Role and the DRM Client Role.

1128 **4.1 Overview**

1129 This section defines the roles and services part of the Marlin specifications. This section
 1130 will enumerate these roles and the services and clients they correspond to. A later
 1131 section of this document specifies the messages and protocols by which the client and
 1132 services communicate.
 1133

Roles	Services	Clients
Device	Inspection	Inspection Provide Security Data
Domain Information Provider (opt)	Provide Domain Information	
Security Data Provider (opt)	Provide Security Data (event-driven)	DRM Client Information
DRM Object Provider (opt)	Provide DRM Objects (event-driven)	Proximity Check DRM Client Information
DRM Client (opt)	Proximity Check License Transfer DRM Client Information	Proximity Check License Transfer Provide DRM Objects Domain Information (opt)

1134 **Table 4-1 Role to Client/Service Mapping**

1135 (opt) indicates that the implementation of this service/client is OPTIONAL
 1136 (event-driven) means that clients MAY subscribe to receive triggers to access this
 1137 service, see the section on protocols.
 1138

1139 The following table summarizes the set of URIs used as attribute values for conveying
 1140 the above roles.

Role	URI
Device	urn:marlin:core:role:device
Domain Info Provider	urn:marlin:core:role:domain-information-provider
Security Data Provider	urn:marlin:core:role:security-data-provider
DRM Object Provider	urn:marlin:core:role:drm-object-provider
DRM Client	urn:marlin:core:role:drm-client

1141 **Table 4-2 Role Identifiers**

1142 Refer to Section 12.5.4.2 for a description of the mechanism used to convey the role
 1143 information.

1144 **4.2 Roles Definitions**

1145

1146 Note: According to [NEMO] §4, roles SHALL be encoded as SAML 1.1 [SAML1.1]
1147 attribute assertions. Also note that we have defined namespace equivalence for this
1148 specific attribute namespace (see Table 1-3.)

1149 **4.2.1 Device**

1150 Each NEMO Node implemented on a Marlin core host SHALL have this role. This means
1151 that all the nodes in Marlin MUST implement an Inspection service and client based on
1152 WS-MetadataExchange [WS-MEX].

1153

1154 All Marlin devices SHALL be able to access a Security Data Provider so that they can
1155 update themselves with new security metadata. They MAY subscribe to Security Data
1156 Events and receive notifications when new Security Metadata is available for them.

1157 **4.2.2 Domain Information Provider**

1158 Each NEMO Node implementing this role SHALL be able to get domain information
1159 requests from DRM Clients and provide DRM Clients with the information about the
1160 domains they know about including the Provide DRM Objects service endpoint where
1161 they can register/deregister to the domain.

1162

1163 The interaction between the Domain Information Provider, the Domain Manager and the
1164 DRM Object Provider is not part of the core specification and will be specified for each
1165 type of domain in the delivery system specifications.

1166 **4.2.3 Security Data Provider**

1167 Each NEMO Node implementing this role SHALL be able to provide Devices with
1168 Security Metadata. The Provide Security Data Service is event-driven so that Marlin
1169 Devices can subscribe to Security Data Events in order to receive notifications when
1170 new Security Metadata is available for them (the same way DRM Clients do for DRM
1171 Object Providers, see below).

1172 **4.2.4 DRM Object Provider**

1173 Each NEMO node implementing this role SHALL be able to provide DRM clients with
1174 DRM objects in a generic way. Such a role MAY be used in conjunction with a domain
1175 manager and serve as a repository for getting the latest membership tokens of a
1176 domain.

1177

1178 The service hosted by a DRM Object Provider SHALL be event-driven, which means
1179 that clients (here DRM Clients) MAY subscribe to notifications that trigger the invocation
1180 of the DRM Object Provider service.

1181 DRM Clients MAY ask to subscribe to DRM Objects notifications. In this case, when the
1182 DRM Object Provider has new objects for the subscriber, it SHALL notify the client.
1183 Subsequent to notification the DRM client can invoke the DRM Object Provider service
1184 and get the objects (Event-driven invocation). The DRM Client MAY also invoke the
1185 DRM Object Provide service directly without notification (direct invocation).

1186

1187 DRM Clients SHOULD subscribe to notification events of DRM Object Providers

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

1188

1189 **4.2.5 DRM Client**

1190 Each NEMO node implementing this role SHALL be able to:

- 1191 • Export information about its Octopus Personality Node as well as its Security
- 1192 Metadata.
- 1193 • Be the sink device in a proximity check (so that a Domain Manager, if required by
- 1194 the domain policy, can determine whether or not the DRM Client can be
- 1195 registered to the domain.
- 1196 • Check the proximity to another DRM.
- 1197 • Invoke a Provide DRM Objects Service (directly or through
- 1198 subscription/notification)
- 1199

1200 Each NEMO node implementing this role MAY:

- 1201 • Request information of the Domain Information Provider (the IDs of the Octopus
- 1202 Nodes representing the Domains that the Domain Information Provider can
- 1203 access, as well as the type of Policy of these Domains and which DRM Object
- 1204 Provider to talk to in order to register to these domains).
- 1205
- 1206
- 1207

1208 **5 Marlin Core System Protocols**

1209
1210
1211

This section defines the core connectivity of Marlin devices.


1212 **5.1 NEMO Architecture for Marlin**

1213 **5.1.1 Concepts and Architecture**

1214 In Marlin, communicating entities are NEMO nodes. These nodes have a set of
1215 credentials which are keys and attributes. The attributes of primary importance in Marlin
1216 are called roles. When a NEMO node has been certified as having a certain role, it
1217 implies that this node implements a number of services and clients. Of course, a single
1218 NEMO node may have multiple roles.

1219
1220
1221

The figure below details the components of the NEMO Marlin Architecture



1222

1223 **Figure 5-1 Example: NEMO Marlin Architecture**

1224

1225 **NOTE:**

1226 In Figure 5-1, the Announcer and the Discoverer are not part of a NEMO node but a
1227 given implementation could include them in the boundaries of a NEMO Node.

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

1228 **5.1.1.1 NEMO Nodes**

1229 NEMO nodes are logical entities that have two types of credentials:

- 1230 • Authentication and Encryption keys: these are certified by an identity provider
- 1231 that binds the ID of the NEMO node and these keys.
- 1232 • Certified attributes that are issued for the Node (bound to the node ID).
- 1233 Specifically, Marlin defines role and specification version attributes. A Node can
- 1234 have (or “implement”) multiple roles. Roles are further described below.

1235
1236 Logically there can be multiple NEMO nodes on a Marlin Host. However, such an
1237 implementation decision would not impact the Discovery, Inspection and Service Access
1238 architecture.

1239 **5.1.1.2 NEMO Roles**

1240 As in [Coral], having a NEMO role implies that a set of services (and clients) are
1241 implemented by a NEMO node. The NEMO roles for Marlin are defined in Section 4.1 of
1242 this document.

1243 **5.1.1.3 Announcer**

1244 The announcer is the building block that implements the Discovery advertisements for
1245 the NEMO node. The announcer MAY be shared between multiple NEMO nodes. It is
1246 also responsible for answering Discovery search requests sent by other hosts
1247 discoverers.

1248 **5.1.1.4 Discoverer**

1249 The discoverer is responsible for sending the Discovery search requests and handling
1250 the Discovery search responses and advertisements. It SHOULD pass information to the
1251 Inspection client so that the service being searched for can be inspected. Like the
1252 announcer, it MAY be shared between multiple NEMO nodes.

1253 **5.1.1.5 Inspection Client**

1254 The inspection client utilizes [WS-MEX] for the inspection phase. It will get the necessary
1255 information (e.g., WSDL) so that the requesting NEMO node can invoke the service
1256 being searched for.
1257

1258 **5.2 Message Security Policies**

1259 **5.2.1 Overview**

1260 The NEMO Security Bindings specification ([NEMO] §3) defines the NEMO basic
1261 security protocol. This protocol SHALL be used in Marlin for message security.

1262
1263 Trusted time SHALL be used in order to check all the NEMO credentials ([X509] public
1264 key certificates and SAML Assertions). Trusted time SHALL also be used when a
1265 message timestamp is required (in the case of ‘Integrity + Freshness’ or ‘Full Security’).

1266
1267 The table below summarizes the different modes of this protocol:
1268

Protocol Policy	Integrity	Nonce	Timestamp	Confidentialia
-----------------	-----------	-------	-----------	----------------

				lity
No Security	NO	NO	NO	NO
Freshness Only	NO	YES	OPTIONAL	NO
Integrity Only	YES	NO	NO	NO
Integrity + Freshness	YES	YES	YES	NO
Confidentiality Only	NO	NO	NO	YES
Full Security	YES	YES	YES	YES

1269 **Table 5-1 Protocol Policy Characteristics**

1270 For a given message exchange, compatible message security policies SHALL be
 1271 implemented. Compatible message security policies which will not hinder a receiver from
 1272 implementing its policy. The following matrix outlines the compatible policies.
 1273

Receiver Protocol Policy	Compatible Sender Protocol Policy
No Security	No Security, Freshness Only, Integrity Only, Integrity + Freshness
Freshness Only	Freshness Only, Integrity + Freshness
Integrity Only	Integrity Only, Integrity + Freshness
Integrity + Freshness	Integrity + Freshness
Confidentiality Only	Confidentiality Only, Full Security
Full Security	Full Security

1274 **Table 5-2 Compatible Policies**

1275 5.2.2 Protocol Security Policy Identifiers

1276 Each of the services defined by this specification informatively describes the protocol
 1277 security policies of the service. This specification normatively defines the each of the
 1278 desired policies using URIs.
 1279

1280 We anticipate that the protocol security policies defined in this specification and in
 1281 delivery system specifications will be added or change. With that in mind it is desirable to
 1282 maintain a uniform identification scheme as outlined in Section 1.3.3. However, we do
 1283 deviate from this slightly in order to indicate the version of the specification the identifier
 1284 is introduced and to support the possibility that two or more policies for the same service
 1285 could be introduced in that specification version.

1286 For example;

1287
 1288 urn:marlin:core:1-2:nemo:services:foobar:policy:0
 1289 urn:marlin:core:1-2:nemo:services:foobar:policy:1

1290
 1291 reflect the policies of the “foobar” service. This identifier also indicates that the policy
 1292 was introduced in version 1.2 (“1-2”) of the specification and that there are two distinct
 1293 policies for the service (policy “0” and policy “1”).³

³ Note that in previous specifications we used “1.x” rather than “1-x” but going forward we intend to use the dash form. Since this is merely an identifier to be evaluated as a whole this does not pose any incompatibilities.

1294 **5.2.3 Request Policies**

1295 The request policies (except the 'No Security') may mandate the inclusion of some or all
1296 the security credentials of the client. The following example depicts these credentials:
1297

```
<!-- Client's NEMO Encryption Key -->
<wssp:SecurityToken
  nemosec:Usage="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0#response-encryptionKey">
  <wssp:TokenType>
    http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-x509-token-profile-
1.0#X509PKIPathv1
  </wssp:TokenType>
</wssp:SecurityToken>

<!-- Client's NEMO Authentication Key -->
<wssp:SecurityToken
  nemosec:Usage="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0#request-signingKey">
  <wssp:TokenType>
    http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-x509-token-profile-
1.0#X509PKIPathv1
  </wssp:TokenType>
</wssp:SecurityToken>

<!-- Client's Roles (application policy attribute tokens) -->
<wssp:SecurityToken> + <!-- one or more -->
  <wssp:TokenType>
    http://nemo.intertrust.com/2004/attribute/role</wssp:TokenType>
</wssp:SecurityToken>
```

1298
1299 To minimize repetition the above example will be referenced in the following sections as
1300 &client-credentials;

1301 **5.2.3.1 No Security**

1302 This policy does not add any protection to the message. Note that the use of this policy
1303 may be sub-optimal with respect to the requirements of the response policy. For
1304 example, if the response policy requires 'Freshness' then it is incumbent upon the
1305 requester to seed the protocol with the proper data.

1306 **5.2.3.2 Freshness Only**

1307 This policy enables seeding of the response policy when it requires 'Freshness'. This
1308 message exchange pattern assumes that the requestor retains the request nonce for
1309 comparison with the response message.

1310
1311 The Core devices in the home environment may have their clocks out of
1312 synchronization. Thus the timestamp on the messages SHOULD be considered
1313 informative.

1314
1315 The following [WS-POL] example expresses an 'Freshness' policy

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

```

<!-- Request Policy ===== -->
<wsp:Policy>
  <!-- Protocol -->
  <nemop:ProtocolAssertion>
    <nemop:Reference URI="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0"/>
    <nemosec:Step type="request"/>
  </nemop:ProtocolAssertion>

  &client-credential;

  <!-- Nonce -->
  <nemop:Nonce
nemop:Usage="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0/policyAssertion#nonce"/>

  <!-- Message Age -->
  <wssp:MessageAge Age="3600"
nemop:Usage="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0/policyAssertion#timestamp"/>

</wsp:Policy>

```

1316

5.2.3.3 Integrity Only

1317

The following [WS-POL] example expresses an 'Integrity Only' policy:

```

<!-- Request Policy ===== -->
<wsp:Policy>
  <!-- Protocol -->
  <nemop:ProtocolAssertion>
    <nemop:Reference URI="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0"/>
    <nemosec:Step type="request"/>
  </nemop:ProtocolAssertion>

  &client-credentials;

  <!-- Integrity -->
  <wssp:Integrity
nemop:Usage="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0/policyAssertion#integrity">
    <wssp:MessageParts Dialect="http://nemo.intertrust.com/2004/policy#part">
      wsp:Body()
      nemop:Token(http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0#request-toNode")
    </wssp:MessageParts>
  </wssp:Integrity>
</wsp:Policy>

```

1318 **5.2.3.4 Integrity + Freshness**

1319 The Core devices in the home environment may have their clocks out of
1320 synchronization. Thus the timestamp on the messages SHOULD be considered
1321 informative.

1322
1323 The following [WS-POL] example expresses an 'Integrity + Freshness' policy

```
<!-- Request Policy ===== -->
<wsp:Policy>
  <!-- Protocol -->
  <nemop:ProtocolAssertion>
    <nemop:Reference URI="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0"/>
    <nemosec:Step type="request"/>
  </nemop:ProtocolAssertion>

  &client-credential;

  <!-- Nonce -->
  <nemop:Nonce
nemop:Usage="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0/policyAssertion#nonce"/>

  <!-- Message Age -->
  <wssp:MessageAge Age="3600"
nemop:Usage="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0/policyAssertion#timestamp"/>

  <!-- Integrity -->
  <wssp:Integrity
nemop:Usage="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0/policyAssertion#integrity">
    <wssp:MessageParts Dialect="http://nemo.intertrust.com/2004/policy#part">
      wsp:Body()
      nemop:Token(http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0#request-nonce)]
      nemop:Token(http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0#request-timestamp)]
      nemop:Token(http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0#request-toNode)]
    </wssp:MessageParts>
  </wssp:Integrity>
</wsp:Policy>
```

1324 **5.2.3.5 Confidentiality Only**

1325 The following [WS-POL] example expresses a 'Confidentiality Only' policy:

```
<!-- Request Policy ===== -->
<wsp:Policy>
  <!-- Protocol -->
  <nemop:ProtocolAssertion>
```

```

    <nemop:Reference URI="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0"/>
    <nemosec:Step type="request"/>
</nemop:ProtocolAssertion>

&client-credentials;

<!-- Confidentiality -->
<wssp:Confidentiality
nemop:Usage="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0/policyAssertion#confidentiality">
    <wssp:MessageParts Dialect="http://nemo.intertrust.com/2004/policy#part">
        nemop:Token(http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0#request-messageKey"')]
        wsp:Body()
    </wssp:MessageParts>
</wssp:Confidentiality>
</wssp:Policy>

```

1326

5.2.3.6 Full Security

1327

The following [WS-POL] example expresses a 'Full Security' policy:

```

<!-- Request Policy ===== -->
<wssp:Policy>
<!-- Protocol -->
<nemop:ProtocolAssertion>
    <nemop:Reference URI="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0"/>
    <nemosec:Step type="request"/>
</nemop:ProtocolAssertion>

&client-credential;

<!-- Nonce -->
<nemop:Nonce
nemop:Usage="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0/policyAssertion#nonce"/>

    <!-- Message Age -->
    <wssp:MessageAge Age="3600"
nemop:Usage="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0/policyAssertion#timestamp"/>

    <!-- Integrity -->
    <wssp:Integrity
nemop:Usage="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0/policyAssertion#integrity">
        <wssp:MessageParts Dialect="http://nemo.intertrust.com/2004/policy#part">
            wsp:Body()
            nemop:Token(http://nemo.intertrust.com/2005/10/security/secure-

```

```

protocol/basic/1.0#request-messageKey"']]
    nemop:Token(http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0#request-nonce"']]
    nemop:Token(http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0#request-timestamp"']]
    nemop:Token(http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0#request-toNode"']]
  </wssp:MessageParts>
</wssp:Integrity>

<!-- Confidentiality -->
<wssp:Confidentiality
nemop:Usage="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0/policyAssertion#confidentiality">
  <wssp:MessageParts Dialect="http://nemo.intertrust.com/2004/policy#part">
    nemop:Token(http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0#request-messageKey"']]
    wsp:Body()
  </wssp:MessageParts>
</wssp:Confidentiality>

</wsp:Policy>

```

1328 **5.2.4 Response Policies**

1329 **5.2.4.1 No Security**

1330 This policy does not add any protection to the message. It just leaves the message as is.

1331 **5.2.4.2 Integrity Only**

1332 The following [WS-POL] example expresses an 'Integrity Only' policy:

```

<!-- Response Policy ===== -->
<wsp:Policy>
  <!-- Protocol -->
  <nemop:ProtocolAssertion>
    <nemop:Reference URI="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0"/>
    <nemosec:Step type="response"/>
  </nemop:ProtocolAssertion>

  <!-- Integrity -->
  <wssp:Integrity
nemop:Usage="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0/policyAssertion#integrity">
  <wssp:MessageParts Dialect="http://nemo.intertrust.com/2004/policy#part">
    wsp:Body()
    nemop:Token(http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0#response-toNode"']]
  </wssp:MessageParts>
</wssp:Integrity>

```

```
</wsp:Policy>
```

1333 **5.2.4.3 Integrity + Freshness**

1334 Core devices in the home environment may have their clocks out of synchronization.
1335 Thus the timestamp on the messages SHOULD be considered informative.

1336
1337 The following [WS-POL] example expresses an 'Integrity + Freshness' policy

```
<!-- Response Policy ===== -->
<wsp:Policy>
  <!-- Protocol -->
  <nemop:ProtocolAssertion>
    <nemop:Reference URI="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0"/>
    <nemosec:Step type="response"/>
  </nemop:ProtocolAssertion>

  <!-- Nonce -->
  <nemop:Nonce
nemop:Usage="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0/policyAssertion#nonce"/>

  <!-- Message Age -->
  <wssp:MessageAge Age="3600"
nemop:Usage="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0/policyAssertion#timestamp"/>

  <!-- Integrity -->
  <wssp:Integrity
nemop:Usage="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0/policyAssertion#integrity">
    <wssp:MessageParts Dialect="http://nemo.intertrust.com/2004/policy#part">
      wsp:Body()
      nemop:Token(http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0#request-nonce)]
      nemop:Token(http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0#response-nonce)]
      nemop:Token(http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0#response-timestamp)]
      nemop:Token(http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0#response-toNode)]
    </wssp:MessageParts>
  </wssp:Integrity>
</wsp:Policy>
```

1338 **5.2.4.4 Confidentiality Only**

1339 The following [WS-POL] example expresses a 'Confidentiality Only' policy:

```
<!-- Response Policy ===== -->
<wsp:Policy>
  <!-- Protocol -->
```

```

<nemop:ProtocolAssertion>
  <nemop:Reference URI="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0"/>
  <nemosec:Step type="response"/>
</nemop:ProtocolAssertion>

<!-- Confidentiality -->
<wssp:Confidentiality
nemop:Usage="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0/policyAssertion#confidentiality">
  <wssp:MessageParts Dialect="http://nemo.intertrust.com/2004/policy#part">
    nemop:Token(http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0#response-messageKey"")]
    wsp:Body()
  </wssp:MessageParts>
</wssp:Confidentiality>
</wssp:Policy>

```

1340

5.2.4.5 Full Security

1341

The following [WS-POL] example expresses a 'Full Security' policy:

```

<!-- Response Policy ===== -->
<wssp:Policy>
  <!-- Protocol -->
  <nemop:ProtocolAssertion>
    <nemop:Reference URI="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0"/>
    <nemosec:Step type="response"/>
  </nemop:ProtocolAssertion>

  <!-- Nonce -->
  <nemop:Nonce
nemop:Usage="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0/policyAssertion#nonce"/>

  <!-- Message Age -->
  <wssp:MessageAge Age="3600"
nemop:Usage="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0/policyAssertion#timestamp"/>

  <!-- Integrity -->
  <wssp:Integrity
nemop:Usage="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0/policyAssertion#integrity">
    <wssp:MessageParts Dialect="http://nemo.intertrust.com/2004/policy#part">
      wsp:Body()
      nemop:Token(http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0#response-messageKey"")]
      nemop:Token(http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0#request-nonce"")]

```

```

        nemop:Token(http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0#response-nonce" ])
        nemop:Token(http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0#response-timestamp" ])
        nemop:Token(http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0#response-toNode" ])
    </wssp:MessageParts>
</wssp:Integrity>

<!-- Confidentiality -->
<wssp:Confidentiality
nemop:Usage="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0/policyAssertion#confidentiality">
    <wssp:MessageParts Dialect="http://nemo.intertrust.com/2004/policy#part">
        nemop:Token(http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0#response-messageKey" ])
        wsp:Body()
    </wssp:MessageParts>
</wssp:Confidentiality>

</wsp:Policy>

```

1342 **5.3 Message Faults**

1343 Marlin utilizes SOAP for much of its messaging substrate. SOAP defines a mechanism
1344 to return fault indications to clients of a service. This section defines the general
1345 mechanisms by which a service can report a fault to a client of the service.

1346
1347 There are two types of fault responses in Marlin System Protocols. One is for errors
1348 pertaining to a SOAP header processing. Another is for errors pertaining to a SOAP
1349 body processing.

1350
1351 The schema which supports the fault mechanism is in Appendix A.7.

1352 **5.3.1 Faults for SOAP Header Processing**

1353 When an error occurs during the processing of the <S11:Header> element, the
1354 processor SHOULD return a fault code. In accordance with the mechanism defined in
1355 [SOAP11] the <S11:Fault> element MUST appear within the <S11:Body> element. Per
1356 this profile additional detail information MAY be returned by using the
1357 <nemoc:FaultDetails> element.

1358
1359 The detail information MUST be supplied as attributes of a <exc:ServiceException>
1360 element or conveyed as a child element of an <exc:ServiceException> element(s).

1361
1362 The syntax for <exc:ServiceException> element follows:

1363 exc:ServiceException

1364 A child element of the <nemoc:FaultDetails> element.

1365

1366 exc:ServiceException/@name

1367 This attribute MUST either contain the following string identifier or a value defined in a
1368 delivery system specification:

- 1369 • exc:NemoMessageProcessingException: This indicates that an exception
1370 occurred while processing the SOAP header.

1371

1372 exc:ServiceException/exc:RedirectURL

1373 The <exc:RedirectURL> element is OPTIONAL. However when present, it MUST
1374 contain a valid URL. This URL is intended to give guidance to the user to help resolve
1375 the problem. The processor of the fault message should direct the user to resolve the
1376 URL.

1377

1378 exc:ServiceException/exc:Details

1379

1380 The following behaviors for <exc:Details> element are defined in Marlin Core.

- 1381 • For
1382 exc:ServiceException/@name="exc:NemoMessageProcessingException":
1383 The <exc:Details> element is OPTIONAL.

1384

1385 When several distinct errors occur during a processing of a SOAP header, multiple
1386 <exc:ServiceException> elements MAY be returned in the <nemoc:FaultDetails>
1387 element.

1388

1389 Note: When the value of the name attribute in <exc:ServiceException> element is other
1390 than values defined in above, it MUST be defined a delivery system specification or be
1391 an organization specific URI defined for its proprietary purpose. If a client encounters an
1392 unknown value of the name attribute in <exc:ServiceException> element, the client
1393 SHOULD log the information in the <exc:RedirectURL> and <exc:Details> elements..

1394 **5.3.2 Faults for SOAP Body Processing**

1395 When an error occurs during processing of the <S11:Body> element, the processor
1396 SHOULD return a fault code. In accordance with the mechanism defined in [SOAP11]
1397 the <S11:Fault> element MUST appear within the <S11:Body> element. For body
1398 faults, detail information MAY be returned using <S11:detail> element.
1399 The <exc:ServiceException> element MUST appear as a child element of the
1400 <S11:detail> element. The <exc:ServiceException> element is used to convey the actual
1401 detail information.

1402

1403 The syntax for <exc:ServiceException> element is as follows:

1404 exc:ServiceException

1405 The child element of <S11:detail> element.

1406

1407 exc:ServiceException/@name

1408 This attribute MUST either contain the following string identifier or a value defined in a
1409 delivery system specification:

- 1410 • exc:NemoMessageProcessingException: This indicates that an exception
1411 occurred while processing the SOAP body.

1412

1413 exc:ServiceException/exc:RedirectURL

1414 The <exc:RedirectURL> element is OPTIONAL. However when present, it MUST
1415 contain a valid URL. This URL is intended to give guidance to the user to help resolve
1416 the problem. The processor of the fault message should direct the user to resolve the
1417 URL.

1418

1419 exc:ServiceException/exc:Details

1420 The following behavior for <exc:Details> element are defined in Marlin Core.

- 1421 • For
1422 exc:ServiceException/@name="exc:NemoMessageProcessingException":
1423 The <exc:Details> element is OPTIONAL.

1424

1425 Note: When the value of the name attribute in <exc:ServiceException> element is other
1426 than values defined in above, it MUST be defined a delivery system specification or be
1427 an organization specific URI defined for its proprietary purpose. If a client encounters an
1428 unknown value of the name attribute in <exc:ServiceException> element, the client
1429 SHOULD log the information in the <exc:RedirectURL> and <exc:Details> elements..

1430 5.3.3 Fault Addressing

1431 When the wsdl:operation includes a soapAction attribute and wsdl:input, wsdl:output,
1432 and wsdl:fault, the specified soapAction attribute value is used in the <wsa:Action>
1433 element for request, response, and fault messages.

1434 For example, in the following wsdl definition, the value "foo" is used for the value of the
1435 <wsa:Action> element for request, response, and fault messages:

```
1436 <wsdl:binding ...>  
1437 ...  
1438 <wsdl:operation ..>  
1439 <wsdlsoap:operation soapAction="foo"/>  
1440 <wsdl:input>...</wsdl:input>  
1441 <wsdl:output>...</wsdl:output>  
1442 <wsdl:fault ...>...</wsdl:fault>  
1443 </wsdl:operation>  
1444 </wsdl:binding>
```

1445

1446 When the wsdl:operation includes a soapAction attribute but does not include a
1447 <wsdl:fault> element, the default value is used in the <wsa:Action> element for fault
1448 messages.

1449 For example, in the following wsdl definition, the default value

1450 "http://www.w3.org/2005/08/addressing/soap/fault " is used as the value of the
1451 <wsa:Action> element in a fault message:

1452

```
1453 <wsdl:binding ...>  
1454 ...  
1455 <wsdl:operation ..>  
1456 <wsdlsoap:operation soapAction="foo"/>  
1457 <wsdl:input>...</wsdl:input>  
1458 <wsdl:output>...</wsdl:output>  
1459 </wsdl:operation>  
1460 </wsdl:binding>
```

1461

1462 The default value is the string "http://www.w3.org/2005/08/addressing/soap/fault".

1463 **5.4 Discovery**

1464 **5.4.1 Overview**

1465 The goal of the discovery layer is to enable Marlin services to be found.

1466

1467 This binding is based on the more general Nemo Discovery/Inspection Bindings
1468 specification ([NEMO] §6). This section further specifies discovery to ensure
1469 interoperability between two implementations of this specification.

1470

1471 The discovery mechanism is compatible with [UPnPDevArch1.0.1] §1 and §2. When a
1472 device is added to the network, the UPnP discovery protocol allows that device to
1473 advertise essential specifics about the device or one of its services, e.g., its type, its
1474 identifier, and a reference which can be used to acquire more detailed information.

1475

1476 Marlin Discovery leverages the UPnP discovery protocol. It compatibly extends it to
1477 advertise NEMO node specifics. When a NEMO node coexists within the context of an
1478 UPnP device, the Device Description document of an UPnP device is extended with
1479 information and end-point addresses for an UPnP Control Point (discoverer) to further
1480 inspect the NEMO node.

1481

1482 When no UPnP device can be leveraged, the Marlin device SHALL implement an UPnP
1483 Basic Device as defined in the [UPnPBasicDev1.0.1] document. In this case, the UPnP
1484 device simply extends it with UPnP compatible NEMO node Marlin extension.

1485

1486 Marlin devices SHALL conform to UPnP 1.0 [UPnPDevArch1.0.1] including the
1487 implementers guide errata [UPnPImplGuid]. Note that the UPnP 1.0.1 draft specification
1488 [UPnPDevArch1.0.1] is an update of UPnP 1.0 that includes all the latest errata.

1489 **5.4.2 Description Extension**

1490 In UPnP, after a control point has discovered a device, the control point has minimal
1491 information about the device. To obtain more device information and its capabilities, the
1492 control point retrieves the device's description from the URL supplied in the LOCATION
1493 header of the search response. The UPnP description for a device is expressed in XML
1494 and includes a list of embedded devices and services as well as vendor specific
1495 information.

1496

1497 The NEMO node specific information SHALL be listed as an extension to the UPnP root
1498 device description and includes URLs and parameters which are used to invoke an
1499 inspection service which implements [WS-MEX].

1500

1501 The description SHOULD be based on a standard UPnP Device Template.
1502 [UPnPBasicDev] specifies an extension mechanism so that vendors can differentiate
1503 their devices. The extension syntax enables extensibility by mandating devices and
1504 control points ignore all unknown elements and their sub elements or content and
1505 unknown attributes and their values.

1506

1507 To retrieve an UPnP Description a Control point (Discoverer) issues a HTTP GET
1508 request to the URL supplied in the LOCATION header of the search response message.
1509 The device returns the device description.

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

1510
1511
1512
1513

The following is an example of an UPnP Basic Device description with an extension defining a NEMO Node with two roles and sub-services (X_MarlinDeviceInfo):

```
<?xml version="1.0"?>
<root xmlns="urn:schemas-upnp-org:device-1-0">
  <specVersion>
    <major>1</major>
    <minor>0</minor>
  </specVersion>
  <URLBase>/</URLBase>
  <device>
    <deviceType>urn:schemas-upnp-org:device:Basic:1</deviceType>
    <friendlyName>Marlin Rendering Device</friendlyName>
    <manufacturer>InterTrust Technologies</manufacturer>
    <manufacturerURL>http://www.intertrust.com</manufacturerURL>
    <modelDescription>Marlin Rendering Device 1.0</modelDescription>
    <modelName>MRD</modelName>
    <modelName>MRD</modelName>
    <modelNumber>1.0</modelNumber>
    <modelURL>http://www.intertrust.com/MRD/</modelURL>
    <serialNumber>123123123123123</serialNumber>
    <UDN>uuid:UUID</UDN>
  </device>
  <X_MarlinDeviceInfo xmlns="urn:marlin:core:1-3:schemas"
    xmlns:wsp="http://schemas.xmlsoap.org/ws/2004/09/policy"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
    <InspectionServiceLocation binding="urn:marlin:core:1-0:services:ws-
mex:binding:http:soap11" policyId="urn:marlin:core:1-0:services:ws-mex:policy:0">
      http://192.168.1.23:8080/ws-mex
    </InspectionServiceLocation>
    <NemoNodeInfo nodeId="urn:marlin:nemo:node:2344">
      <NemoRoleInfo roleURI="urn:marlin:core:role:drm-client">
        <PortType>proximity-check</PortType>
        <PortType>license-transfer</PortType>
        <PortType>drm-client-information</PortType>
      </NemoRoleInfo>
      <NemoRoleInfo roleURI="urn:marlin:core:role:security-data-provider">
        <PortType>provide-security-data</PortType>
        <PortType>EventSource</PortType>
        <PortType>SubscriptionManager</PortType>
      </NemoRoleInfo>
    </NemoNodeInfo>
  </X_MarlinDeviceInfo>
</root>
```

1514
1515
1516
1517
1518

An UPnP Device description indicating a device that implements Marlin SHALL include a X_MarlinDeviceInfo element (see marlin-core.xsd) and SHALL contain at least the following elements: InspectionServiceLocation and NemoNodeInfo.

1519 The contents of X_MarlinDeviceInfo SHALL NOT contain <NemoRoleInfo> elements for
1520 services that are not yet operational. For example, a device which is functionally capable
1521 of acting fulfilling the domain information provider but has yet to be configured would not
1522 advertise this until provisioned. Once the device has been provisioned and ready to fulfill
1523 the role then it should advertise the availability of the service.

1524 **5.5 Inspection**

1525 **5.5.1 Overview**

1526 Following the discovery phase, the client, SHALL have access to the X_MarlinDeviceInfo
1527 structure which SHALL supply all the information needed to invoke the inspection
1528 service.

1529 This specification, defines static values for the protocol binding and the policyId
1530 attributes of the <InspectionServiceLocation> element:
1531
1532

Attribute	Identifier
binding	urn:marlin:core:1-0:services:ws-mex:binding:http:soap11
policyId	urn:marlin:core:1-0:services:ws-mex:policy:0

1533
1534 The URI, urn:marlin:core:1-0:services:ws-mex:policy:0, maps to “no security” (plain ws-
1535 metadata exchange request/response).
1536

1537 These parameters SHOULD be used to invoke an inspection service using [WS-MEX].
1538 The inspection service allows the client to get more information about the discovered
1539 service.

1540 **5.5.2 Inspection Client and Service interaction**

1541 **5.5.2.1 Supported Dialects**

1542 Marlin implementation of the inspection service SHOULD support the following dialect
1543 defined in Appendix I of the [WS-MEX]:

- 1544 1. WSDL 1.1

1545
1546 Additionally, the NEMO Node Info dialect as defined in [NEMO] §6 SHALL be supported.
1547 The namespace URI is:

1548 <http://nemo.intertrust.com/2004/inspection/mex/nemonodeinfo>

1549 **5.5.2.2 GetMetadata request**

1550 The GetMetadata request message SHALL conform to [WS-MEX] §3.1 with the following
1551 parameters:

1552
1553 /s:Header/wsa:ReplyTo

1554 This field SHALL carry the endpoint of the inspection client of the requesting NEMO
1555 Node.

1556
1557 /s:Header/wsa:To

1558 This field SHALL carry the endpoint address of the inspection service extracted from the
1559 <X_MarlinDeviceInfo> element.

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

1560
 1561 /s:Body/ws:GetMetadata/ws:Identifier
 1562 This field SHALL carry the scope of the inspection request as defined below for each
 1563 dialect.

1564 **5.5.2.3 GetMetadata response**

1565 Depending on the size of the metadata to return, the service MAY respond with a
 1566 ws:MetadataReference to the metadata. The client SHOULD follow-up this response
 1567 with a second phase where it obtains the metadata. When using this option, the
 1568 metadata SHALL be obtained using the HTTP-Get method [RFC2616].

1569
 1570 The server MAY return a number of ws:Metadata Sections depending on the dialect and
 1571 the wsa:To field of the request.

1572 **5.5.2.3.1 WSDL 1.1 dialect**

ws:Identifier	What should be returned
<NEMO Node ID>	All the WSDLs under the NEMO Node scope
<NEMO Node ID>::<NEMO Role>	All the WSDLs of the services belonging to this role under the NEMO Node scope
<NEMO Node ID>::<NEMO Role>::<WSDL port type>	The WSDL of the service uniquely identified within the scope of the NEMO Node and the indicated role.

1573 **5.5.2.3.2 NEMO Node Information dialect**

1574 All the ws:Identifier contain a node ID so the response SHALL always contain the
 1575 NEMO Node information for the specified NEMO Node ID.

1576
 1577 This response SHALL carry all the security credentials in a <nemoc:NodeInfo> element.
 1578 This includes:

- 1579 • The signing and encryption NEMO keys
- 1580 • All the asserted Role attributes for this NEMO Node
- 1581 • The asserted Specification Version attributes as defined in Section 8.2.

1582
 1583 The credentials delivered in the <nemoc:NodeInfo> element MUST adhere to the
 1584 following:

- 1585 1. The <wsse:SecurityTokenReference> elements SHALL signal the credential
 1586 usage with a nemosec:TargetUsage attribute. The nemosec:Usage attribute
 1587 SHALL NOT be present.
- 1588 2. The credentials and values for the nemosec:TargetUsage attribute are as
 1589 follows:
 - 1590 • Signing key for response messages SHALL be signaled with:
 1591 [http://nemo.intertrust.com/2005/10/security/secure-
 1592 protocol/basic/1.0#response-signingKey](http://nemo.intertrust.com/2005/10/security/secure-protocol/basic/1.0#response-signingKey)

1593
 1594 The <wsse:SecurityTokenReference> element SHALL contain an
 1595 <wsse:Embedded> element. The <wsse:Embedded> element SHALL include
 1596 a <wsse:BinarySecurityToken>. The <wsse:BinarySecurityToken> element
 1597 SHALL include a ValueType attribute with the value:
 1598 <http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-x509-token->

- 1599 profile-1.0#X509PKIPathv1
 1600
 1601 • Encryption key for request messages SHALL be signaled with:
 1602 http://nemo.intertrust.com/2005/10/security/secure-
 1603 protocol/basic/1.0#request-encryptionKey
 1604
 1605 The <wsse:SecurityTokenReference> element SHALL contain an
 1606 <wsse:Embedded> element. The <wsse:Embedded> element SHALL include
 1607 a <wsse:BinarySecurityToken>. The <wsse:BinarySecurityToken> element
 1608 SHALL include a ValueType attribute with the value:
 1609 http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-x509-token-
 1610 profile-1.0#X509PKIPathv1
 1611
 1612 • SAML Assertion with role attributes SHALL be signaled with:
 1613 http://nemo.intertrust.com/2004/attribute/role
 1614
 1615 The <wsse:SecurityTokenReference> element SHALL contain an
 1616 <wsse:Embedded> element. The <wsse:Embedded> element SHALL include
 1617 a <saml:Assertion> element (with role attributes.)
 1618 3. When one key is used for both signing response messages and encrypting
 1619 request messages then there SHALL be two <wsse:SecurityTokenReference>
 1620 elements, one indicating the response signing target usage and the other
 1621 indicating the request encryption target usage. In other words, these two
 1622 <wsse:SecurityTokenReference> elements include the same X.509 key with
 1623 different target usages. Example 5-1 demonstrates this.
 1624

```

<nemoc:NodeInfo>
  <nemoc:NodeId>urn:marlin:nemo:node:2344</nemoc:NodeId>
  <!-- DRM Client's Encryption Key -->
  <wsse:SecurityTokenReference
    nemosec:TargetUsage="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0#request-encryptionKey">
    <wsse:Embedded>
      <wsse:BinarySecurityToken wsu:Id="PKIPath0"
        ValueType="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-x509-
token-profile-1.0#X509PKIPathv1"
        EncodingType="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-soap-
message-security-1.0#Base64Binary">
        MIAwggM0MIICHKADAgECAgFIMA0GCSqGSIb3DQEBBQUAMCEXHzA...
      </wsse:BinarySecurityToken>
    </wsse:Embedded>
  </wsse:SecurityTokenReference>
  <!-- DRM Client's Signing Key -->
  <wsse:SecurityTokenReference
    nemosec:TargetUsage="http://nemo.intertrust.com/2005/10/security/secure-
protocol/basic/1.0#response-signingKey">
    <wsse:Embedded>
      <wsse:BinarySecurityToken wsu:Id="PKIPath1"
        ValueType="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-x509-
token-profile-1.0#X509PKIPathv1"
  
```

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

```
EncodingType="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-soap-  
message-security-1.0#Base64Binary">  
  MIAwggM0MIICHKADAgECAgFIMA0GCSqGSIb3DQEBBQUAMCExHzA...  
  </wsse:BinarySecurityToken>  
  </wsse:Embedded>  
  </wsse:SecurityTokenReference>  
  ...  
</nemoc:NodeInfo>
```


1625 **Example 5-1: NodeInfo indicating the same key is used for signing and encryption.**

1626

1627 **5.6 *Subscription and Notification***

1628 **5.6.1 Overview**

1629 Simple interaction such as request/response with web services is not enough and not
1630 very dynamic. There are some cases where a client wants to subscribe to an event such
1631 as “new security data available” and be notified when this event occurs. The solution we
1632 propose here is based on, and compatible with [WS-BASENOTE]. This is illustrated
1633 below:



1634

1635 **Figure 5-2 Subscription-based Notification Overview**

1636

1637 In the first of the following sections, we explain how to subscribe to a topic and how to
 1638 filter the data the client wants to receive notifications for.

1639 **5.6.2 Topics**

1640 In order to scope notification subscriptions, all subscription services MUST support the
 1641 Simple Topic Expression Dialect specified in [WS-TOPICS] §7.1. This dialect is identified
 1642 by the following URI:

1643 `http://docs.oasis-open.org/wsn/t-1/TopicExpression/Simple`
 1644

1645 This enables a subscriber to choose specific topics for notifications. Optionally,
 1646 additional restrictions can be specified by qualifying the subscription with an expression
 1647 which describes a particular system entity (e.g., Octopus Personality Node or Nemo
 1648 Node.)

1649 **5.6.2.1 Provide Security Data Topics**

1650 This topic enables a subscriber to receive notifications for security metadata updates.
 1651 The scope of the subscription MAY be narrowed by the root topic identifiers specified in
 1652 the following table.

Topic Namespace Identifier	Root Topics	Semantic
urn:marlin:core:1-0:subscription:topic	security-data	Any security metadata
	crl	Newest CRL ⁴
	broadcastkeyblock	Newest BKB ⁴
	assertion	SAML Assertions
	trustedtime	Trusted Time

1653 **Table 5-3 Provide Security Data Root Topic Namespaces**

1654 The subscriber MUST specify the scope of the subscription by qualifying the
 1655 <wsnt:TopicExpression> element with one of the root topics defined in Table 5-3.
 1656

1657 Device implementations are REQUIRED to subscribe to the “crl” topic from an available
 1658 SDP. Implementations with Internet connectivity are REQUIRED to resolve the CRL
 1659 distribution point URI.
 1660

1661 Device implementations that issues licenses are REQUIRED to subscribe to the
 1662 “broadcastkeyblock” topic. Implementations with Internet connectivity are
 1663 RECOMMENDED to acquire the BKB by resolving the distribution attributes in the BKB.
 1664

1665 The following is an example of a request to subscribe to the “crl” root topic:

```

1666 <wsnt:Subscribe>
1667   <wsnt:ConsumerReference>
1668     <wsa:Address>...</wsa:Address>
1669     <wsa:Metadata xsi:type="mc:NemoNodeInfo">
1670       <mc:NemoNodeInfo nodeID="urn:marlin:nemo:node:2344"/>
1671     </wsa:Metadata>
1672   </wsnt:ConsumerReference>
1673   <wsnt:Filter>
1674     <wsnt:TopicExpression
1675       Dialect=" http://docs.oasis-open.org/wsn/t-1/TopicExpression/Simple"
1676
```

⁴ Certificate Revocation Lists and Broadcast Key Blocks are large data objects which update infrequently. The notification messages for these root topics include specific information to aid the Notification Consumer in determining whether the data object is more current than the object possessed by the Notification Consumer. See Section 5.6.3.1.1.

```

1677         xmlns:tns="urn:marlin:core:1-0:subscription:topic">
1678         tns:crl
1679     </wsnt:TopicExpression>
1680 </wsnt:Filter>
1681 </wsnt:Subscribe>
1682

```

1683 The subscription request MAY be further qualified in the filter by including a
1684 <mc:SecurityMetadataTopicExpression> and including the <mc:NemoNodeId> element.
1685 In the absence of this element the subscription service SHOULD limit the information
1686 published to that which is safe to broadcast to all subscribers. Otherwise the subscription
1687 service must limit the distribution to the NEMO Node ID specified in the <wsa:Metadata>
1688 element within the <wsnt:ConsumerReference>.

1689 5.6.2.2 Provide DRM Objects Topic

1690 This topic enables a subscriber to receive notifications for Octopus DRM Objects. The
1691 supported root topic identifiers are specified in the following table.
1692

Topic Namespace Identifier	Root Topics	Semantic
urn:marlin:core:1-0:subscription:topic	drm-objects	DRM Objects for the indicated Octopus personality

1693 **Table 5-4 Provide DRM Objects Root Topic Namespaces**

1694 The subscriber MUST specify the scope of the subscription by qualifying the
1695 <wsnt:TopicExpression> element with one of the root topics defined in Table 5-4.
1696 The following is an example of a request to subscribe to the “*drm-objects*” root topic:

```

1697 <wsnt:Subscribe>
1698   <wsnt:ConsumerReference>
1699     <wsa:Address>...</wsa:Address>
1700     <wsa:Metadata xsi:type="mc:NemoNodeInfo">
1701       <mc:NemoNodeInfo nodeID="urn:marlin:nemo:node:2344"/>
1702     </wsa:Metadata>
1703   </wsnt:ConsumerReference>
1704   <wsnt:Filter>
1705     <wsnt:TopicExpression
1706       Dialect="http://docs.oasis-open.org/wsn/t-1/TopicExpression/Simple"
1707       xmlns:tns="urn:marlin:core:1-0:subscription:topic">
1708       tns:drm-objects
1709     </wsnt:TopicExpression>
1710     <mc:DRMObjectsTopicExpression>
1711       <mc:OctopusNodeID>...</mc:OctopusNodeID>
1712     </mc:DRMObjectsTopicExpression>
1713   </wsnt:Filter>
1714 </wsnt:Subscribe>
1715

```

1716
1717 The subscription request SHOULD further qualify the filter by including a
1718 <mc:DRMObjectsTopicExpression> which designates the Octopus Personality Node of
1719 interest in the <mc:OctopusNodeId> element. (Informative Note: This identifier is
1720 derived from the oct:uid attribute of the <oct:Node> when the Octopus personality node
1721 is encoded in XML.) In the absence of the <mc:DRMObjectsTopicExpression> element
1722 the subscription service may utilize the inspection services of the NEMO Node described

1723 in the <wsa:Metadata> element within the <wsnt:ConsumerReference> in order to
1724 determine the Octopus node(s).

1725 **5.6.3 Notification Consumer**

1726 Notification Consumers SHALL implement the Notification Consumer interface as
1727 specified in [WS-BASENOTE] §3.

1728 **5.6.3.1 Notify**

1729 This message exchange MUST be implemented as specified in [WS-BASENOTE] §3.
1730 Notification consumers MUST understand Notify messages as specified in [WS-
1731 BASENOTE] §3.2.

1732
1733 The payload of the <wsnt:Notify> message is carried within a <wsnt:Message> element.
1734 It is RECOMMENDED that the payload carry a <mc:NotificationID> element. The value
1735 of this element is opaque to the Notification Consumer and serves as a simple identifier
1736 which the subscription resource may utilize to locate the specific data being published.

1737 **5.6.3.1.1 Qualified Notification Message**

1738 The <wsnt:Notify> generally carries sufficient context for the Notification Consumer to
1739 obtain the published data. However, the root topics “crl” and “broadcastkeyblock” defined
1740 in Section 5.6.2.1 supply updates to critical security metadata which change infrequently.
1741

1742 To avoid excessive consumption of bandwidth retrieving a large data object which is
1743 already known to the Notification Consumer a Notification Producer SHOULD insert
1744 information in the payload of the <wsnt:NotificationMessage> to identify the instance of
1745 these data objects.

1746
1747 For a CRL the payload should bear a <mc:CRLNumber> element. The value of this
1748 element is the integer value of the *id-ce-cRLNumber* extension field of a CRL as defined
1749 in [PKIX] §5.2.3. The following example depicts a notify message for a CRL.

```
1750 <wsnt:Notify>  
1751   <wsnt:NotificationMessage>  
1752     <wsnt:SubscriptionReference>  
1753       <wsa:Address>...</wsa:Address>  
1754     </wsnt:SubscriptionReference>  
1755     <wsnt:Topic  
1756       Dialect=" http://docs.oasis-open.org/wsn/t-1/TopicExpression/Simple"  
1757       xmlns:tns="urn:marlin:core:1-0:subscription:topic">  
1758       tns:crl  
1759     </wsnt:Topic>  
1760     <wsnt:ProducerReference>  
1761       <wsa:Address>...</wsa:Address>  
1762     </wsnt:ProducerReference>  
1763     <wsnt:Message>  
1764       <mc:NotificationID>...</mc:NotificationID>  
1765       <mc:CRLNumber>9</mc:CRLNumber>  
1766     </wsnt:Message>  
1767   </wsnt:NotificationMessage>  
1768 </wsnt:Notify>
```

1771 For a Broadcast Key Block the payload SHOULD include a
1772 <mc:BKBRevocationVersion> element. The value of this element is the same as the
1773 sf:revocationVersion attribute defined in the [Starfish] schema.

1774 **5.6.4 Notification Producer**

1775 Marlin Notification producers MUST implement the Notification Producer interface as
1776 specified in [WS-BASENOTE] §4. Each Notification Producer endpoint MUST have a
1777 unique URI.

1778
1779 The following sections define the message exchanges utilized by Marlin entities to
1780 leverage a Notification Producer interface.

1781 **5.6.4.1 Subscribe**

1782 This message exchange MUST be implemented as specified in [WS-BASENOTE] §4.2.
1783 In addition to the above requirement the following components MUST be included in a
1784 subscription request message.

1785
1786 The mandatory <wsnt:ConsumerReference> element MUST indicate the NEMO Node
1787 ID of the notification consumer within a <wsa:Metadata> element. This MUST be
1788 accomplished by inserting a <mc:NemoNodeInfo> element as a child of the
1789 <wsa:Metadata> element. This element only need to supply the mc:nodeID attribute.
1790 Instance of a <wsa:Metadata> element indicating the NEMO Node ID information
1791 SHALL assert its element type by specifying the xsi:type attribute with a value of
1792 “mc:NemoNodeInfo” string identifier.

1793
1794 The subscription request MUST include a <wsnt:Filter> element. This element MUST
1795 carry a <wsnt:TopicExpression> element. The <wsnt:TopicExpression> element MUST
1796 specify the simple dialect attribute. The root topics supported by this specification are
1797 described in Section 5.6.2.1 and Section 5.6.2.2.

1798 **5.6.5 Subscription Manager Operations**

1799 Subscription management in Marlin MUST implement the Base Subscription Manager
1800 interface as specified in [WS-BASENOTE] §6 and §6.1.

1801
1802 The web services representing individual subscription resources SHALL reside at the
1803 same location as the Notification Producer service. That is, individual subscriptions
1804 SHALL be represented by endpoint references composed of the information matching
1805 the endpoint reference of the subscription manager service. The [WS-Addr]
1806 <wsa:Action> message address property helps to disambiguate the service consumer
1807 intentions.

1808
1809 The following sections define the interfaces that MUST be exposed by a Marlin
1810 Subscription Manager service.

1811 **5.6.5.1 Renew**

1812 This message exchange MUST be implemented as specified in [WS-BASENOTE] §6.1.1
1813

1814 **5.6.5.2 Unsubscribe**

1815 This message exchange MUST be implemented as specified in [WS-BASENOTE]
1816 §6.1.2.

1817 **5.6.6 Faults**

1818 The SOAP faults used in context of the notification framework comply with the
1819 specifications of the respective message exchanges. As such, they extend
1820 <wsnt:BaseFault> as specified in [WSRF-BF] and have the <wsa:Action> URI:
1821 <http://docs.oasis-open.org/wsrp/fault>

1822 **5.7 Service-specific Protocols**

1823 **5.7.1 Proximity Check Protocol (HARPOON)**

1824 **5.7.1.1 Overview**

1825 The proximity check SHALL allow an anchor (client) to check the proximity of a target
1826 (service).

1827
1828 This protocol is asymmetric as the anchor (client) generates a secret seed and is the
1829 only one that requires a secure timer. Moreover, the target (service) does not need to
1830 trust the anchor (client). It is also cryptographically efficient requiring only two public key
1831 operations.

1832
1833 The XML schema for this protocol is defined in the XML Namespace

1834 <urn:marlin:core:1-1:nemo:services:schemas>

1835
1836 A copy of the XML schema and WSDL is in Appendix A.1 and B.1, respectively.
1837

1838 **5.7.1.2 Generation of the set R of Q pairs from a Seed S**

1839 The set R is obtained from randomly generated seed using the following method:

1840 $R_i = H^{2^{Q-i}}(S)$

1841

1842 $H(M)$ is the digest value of the hash function H over the message M .

1843 $H^n(M) = H(H^{n-1}(M))$ for $n \geq 1$ and $H^0(M) = M$

1844

1845 The algorithm used for the hash function $H()$ SHALL be [SHA1].

1846 **5.7.1.3 Sequence**

1847 a) A generates a set R of Q pairs of random numbers $\{R_0, R_1\}, \{R_2, R_3\} \dots \{R_{2Q-2},$
1848 $R_{2Q-1}\}$.

1849 b) A sends to B: $E(\text{PubB}, \{Q,S\})$.

1850 c) B decrypts $\{Q,S\}$ and precomputes R according to Section 5.7.1.2

1851 d) B sends back an acknowledgement to indicate that it is ready to proceed

1852 e) A sets the loop counter $i=0$

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

1853

f) A measures $T_0 = \text{now}$

1854

g) A sends to B: $\{i, R_{2^i}\}$

1855

h) If the value of R_{2^i} is correct, B responds with $R_{2^{i+1}}$

1856

i) A measures $D = \text{now} - T_0$

1857

j) If B is responded to with the correct value for $R_{2^{i+1}}$, and $D < \text{Threshold}$: success, stop.

1858

1859


k) If $i+1 < Q$, A can retry a new measurement by incrementing i and going to step f)

1860

If it is needed to perform more than Q measurements, A needs to start from step a) with

1861

a new set R .



1862

1863 5.7.1.4 Security Considerations⁵

1864

When engaging in this protocol, care must be taken to follow some basic requirements:

1865

- The loop f-i MUST NOT be repeated with the same value of i for any set R

1866

- The protocol MUST be aborted if any unexpected message is received by either party. That includes:

1867

1868

- If B receives an incorrect value for R_{2^i} in step g.

1869

- If Q is not within a specified range in step a

1870

- If i is repeated in the loop

⁵ It is the purview of a compliance regime to define the values for Q and Threshold. Therefore, implementations should be flexible in configuring these values. Also it is assumed that implementation should support a minimum value of 64 for Q and 8ms for the Threshold.

1871 o If i exceeds Q

1872 **5.7.1.5 Messages**

1873 **5.7.1.5.1 Setup Request**

- 1874 • $E(\text{PubB}, \{Q, S\})$: The number of pairs Q as well as the secret pairs seed S
- 1875 encrypted with B 's NEMO public encryption key

1876

1877 $\{Q, S\}$ is the byte stream concatenation of Q (1 byte) and S (16 bytes) in network byte

1878 order.

1879

1880 The encryption is performed with [RSA-1_5]. PubB has been previously accessed

1881 through inspection and its certificate **MUST** have been verified.

1882 **5.7.1.5.2 Setup Response**

1883 None

1884 **5.7.1.5.3 Challenge Request**

- 1885 • $[i, R_{2^*i}]$: The index i and the corresponding secret computed from the seed.

1886

1887 $[i, R_{2^*i}]$ is the byte stream concatenation of i (1 byte) and R_{2^*i} (20 bytes) in network byte

1888 order, encoded in base64 for transport.

1889

1890 **5.7.1.5.4 Challenge Response**

- 1891 • R_{2^*i+1} : the corresponding secret from the Challenge Request

1892

1893 R_{2^*i+1} is the byte stream of R_{2^*i+1} (20 bytes) in network byte order, encoded in base64 for

1894 transport.

1895 **5.7.1.6 Protocol Security Policies**

1896 'No Security' policy is needed for this protocol. The identifier for this policy is:

urn:marlin:core:1.0:nemo:services:proximity-check:policy:0

1897

1898 **5.7.2 DRM Client Information**

1899 **5.7.2.1 Overview**

1900 This service can be used to get metadata on the DRM client (second level of inspection).

1901 This service includes four operations:

- 1902 • get the Octopus Node of the DRM Client
- 1903 • get the current Security Metadata of the client so that a decision can be made by
- 1904 a Security Data Provider to update it or not.
- 1905 • get the active Octopus links of a DRM Client
- 1906 • get the secret scuba sharing key of a client

1907

1908 The XML schema for this protocol is defined in the XML Namespace

1909

1910 urn:marlin:core:1-1:nemo:services:schemas

1911

1912 A copy of the XML schema and WSDL is in Appendix A.2 and B.2, respectively.

1913

1914 **5.7.2.2 Get Octopus Node**

1915 **5.7.2.2.1 Request Parameters**

1916 None

1917 **5.7.2.2.2 Response Data**

- 1918 • *Octopus Bundle*: the data structure containing the public Octopus Personality
1919 Node representing the DRM Client

1920 **5.7.2.2.3 Protocol Security Policies**

1921 The response must be signed by the NEMO authentication key of the DRM Client. This
1922 creates a secure binding between the NEMO Node ID of the DRM Client and the
1923 Octopus Node it hosts.

1924

1925 The request SHOULD obey 'No Security' policy (Section 5.2.3.1) and the response
1926 MUST obey the 'Integrity Only' policy (Section 5.2.4.2.)

1927

1928 The identifier for this policy is:

urn:marlin:core:1.0:nemo:services:drm-client-information:get-octopus-node:policy:0

1929

1930 **5.7.2.3 Get Security Metadata**

1931 **5.7.2.3.1 Request Parameters**

1932 None

1933 **5.7.2.3.2 Response Data**

- 1934 • *Security Metadata*: The opaque data structure representing the current security
1935 metadata of the DRM Client

1936 **5.7.2.3.3 Protocol Security Policies**

1937 The response must be signed by the NEMO authentication key of the DRM Client. This
1938 allows for the authenticity of the security metadata to be verified.

1939

1940 Because the response requires freshness the request SHOULD obey the 'Freshness'
1941 only policy (Section 5.2.3.2) and the response MUST obey the 'Integrity+Freshness'
1942 policy (Section 5.2.4.3.)

1943

1944 The identifier for this policy is:

urn:marlin:core:1-2:nemo:services:drm-client-information:get-security-metadata:policy:0

1945 **5.7.2.4 Get Domain Links**

1946 **5.7.2.4.1 Request Parameters**

- 1947 • domain-policy: This OPTIONAL element specifies the URI used to identify the
1948 domain policy.
1949

1950 **5.7.2.4.2 Response Data**

- 1951 • *Bundle*: structure carrying the current valid Octopus Links of the DRM Client

1952 **5.7.2.4.3 Protocol Security Policies**

1953 The response must be signed by the NEMO authentication key of the DRM Client. This
1954 allows for the authenticity of the links validity to be verified.
1955

1956 Because the response requires freshness the request SHOULD obey the 'Freshness'
1957 only policy (Section 5.2.3.2) and the response MUST obey the 'Integrity+Freshness'
1958 policy (Section 5.2.4.3.)
1959

1960 The identifier for this policy is:

urn:marlin:core:1-2:nemo:services:drm-client-information:get-domain-links:policy:0

1961 **5.7.2.5 Get Scuba Secret Sharing Key**

1962 **5.7.2.5.1 Request Parameters**

1963 None

1964 **5.7.2.5.2 Response Data**

- 1965 • *Key Data*: structure carrying the base 64 encoded plain Scuba Sharing key of the
1966 DRM Client.

1967 **5.7.2.5.3 Protocol Security Policies**

1968 The request must be signed and the DRM Object Provider role of the requesting NEMO
1969 Node MUST be attached to the request.
1970

1971 The response must be signed by the NEMO authentication key and encrypted by the
1972 requestor's public key. This enables the recipient to verify the authenticity of the links
1973 validity and protects the confidentiality of the Scuba Secret Sharing key. It is OPTIONAL
1974 for a client to distribute its Scuba Secret Sharing key.
1975

1976 The request MUST obey the 'Integrity+Freshness' policy (Section 5.2.3.4) and the
1977 response MUST obey the response 'Full Security' policy (Section 5.2.3.5.)
1978

1979 The identifier for this policy is:

urn:marlin:core:1.0:nemo:services:drm-client-information:get-scuba-sharing-key:policy:0

1980 **5.7.3 Provide Domain Information**

1981 **5.7.3.1 Overview**

1982 This service can be used to get metadata regarding the Domains that the Domain
1983 Information Provider has access to.

1984 The XML schema for this protocol is defined in the XML Namespace:

1985

1986 urn:marlin:core:1-1:nemo:services:schemas

1987

1988 A copy of the XML schema and WSDL is in Appendix A.3 and B.3, respectively.

1989 **5.7.3.2 Request Parameters**

1990 None

1991 **5.7.3.3 Response Data**

- 1992
- 1993 • *Domain Info (one or more)*: Data structure encoding the ID of the Octopus Node
1994 representing the domain as well as the policy type for this domain and the
1995 Provide DRM Objects service endpoint that can be invoked to request a
1996 registration.
 - 1997 • *Domain Policy (one or more)*: the data structure encoding the policy referred to in
1998 the Domain Info structure. This structure SHALL be used for User Interface
purposes only.

1999 **5.7.3.4 Protocol Security Policies**

2000 The response must be signed by the NEMO Authentication key of the Domain Manager.
2001 This allows for the authenticity of the Domain Manager Information to be verified.

2002

2003 The request SHOULD obey the 'No Security' policy (Section 5.2.3.1) and the response
2004 MUST obey the 'Integrity Only' policy (Section 5.2.3.2.)

2005

2006 The identifier for this policy is:

urn:marlin:core:1.0:nemo:services:provide-domain-information:policy:0

2007 **5.7.4 Provide DRM Objects**

2008 **5.7.4.1 Overview**

2009 This is a simple REQUEST/RESPONSE protocol. However, the exchange anticipates
2010 the response to bear an Agent. Agents are obligated to supply a confirmation.
2011 Confirming to the DRM Object providing service allows the service to determine that the
2012 object has been processed in a secure environment.

2013

2014 The XML schema for this protocol is defined in the XML Namespace

2015

2016 urn:marlin:core:1-1:nemo:services:schemas

2017

2018 A copy of the XML schema and WSDL is in Appendix A.4 and B.4, respectively.

2019 5.7.4.2 Request parameters

- 2020 • *Octopus Personality Node*: The Octopus Node representing the DRM Client.
- 2021 • *Notification ID*: This OPTIONAL element is present if the request is sent after the
2022 DRM Client has been notified (event driven invocation), then this parameter
2023 MUST be present so that the service can correlate it with the notification it sent to
2024 the DRM Client.
- 2025 • *DRMObjectContext*: This OPTIONAL element supplies the data structure that
2026 encodes the action context of the provisioning of this Octopus Object. It will
2027 indicate the action, if any, intended by the requester (i.e. registration or
2028 deregistration).

2029
2030 An example of a DRMObjectContext follows:

```
<mncs:DRMObjectContext>  
  <mncs:DRMAAction  
name="urn:marlin:core:1.0:nemo:services:provide-drm-  
objects:context:action:registration"/>  
  <ml:ContextList>  
    <ml:Context uid="urn:marlin:broadcast:1-0:domain:243523"/>  
  </ml:ContextList>  
</mncs:DRMObjectContext>
```

2031
2032 Therefore, when the service receives a Provide DRM Object request with this
2033 data structure, it should try to register the client with the domain
2034 urn:marlin:broadcast:1-0:domain:243523
2035

2036 The mncs:name attribute of the <mncs:DRMAAction> element may have one of the
2037 following values:

urn:marlin:core:1.0:nemo:services:provide-drm-objects:context:action:registration
urn:marlin:core:1.0:nemo:services:provide-drm-objects:context:action:deregistration

2038 5.7.4.3 Response Data

- 2039 • *Octopus Bundle*: This OPTIONAL element supplies the data structure containing
2040 the Octopus objects. This bundle SHALL NOT bear Agents.
- 2041 • *Agent Carrier*: This OPTIONAL element supplies the data structure containing
2042 the Agent as well as the input parameters and the context ID. The name and
2043 controllID attributes MUST be specified to unambiguously identify the Agent.
- 2044 • *DRMObjectContext*: This OPTIONAL element supplies the data structure that
2045 encodes the action context for provisioning of the Octopus Object. This data
2046 structure also carries the context identifiers that the application SHOULD use in
2047 order to do the necessary cleanup. This element SHALL be present when the
2048 action context is related to domain registration or de-registration.

2049
2050 An example of a DRMObjectContext follows:

```
<mncs:DRMObjectContext>  
  <mncs:DRMAAction  
name="urn:marlin:core:1.0:nemo:services:provide-drm-  
objects:context:action:deregistration"/>  
  <ml:ContextList>  
    <ml:Context uid="urn:marlin:broadcast:1-0:domain:243523"/>  
  </ml:ContextList>
```

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

```
</ml:ContextList>
</mncs:DRMObjectContext>
```

2051 Therefore, when the client receives Provide DRM Object response with this data
2052 structure, it should cleanup all the Octopus links that have a domain-id attribute
2053 equal to "urn:marlin:broadcast:1-0:domain:243523".

2054 **5.7.4.4 Confirmation parameters**

2055 A confirmation MUST be sent. This is necessary regardless of whether the response
2056 contains an Agent Carrier or not. By making the confirmation mandatory we ensure that
2057 the communicating entities can be prepared for a multi-round message exchange
2058 pattern.

2059 The DRM Client may also refuse the objects provided by the service. In this case, it will
2060 send a DRM Object Refusal in the confirmation.

- 2061 • **DRMObjectRefusal:** This OPTIONAL element contains the DRMObjectContext
2062 that was sent in the response.
- 2063 • *Agent Result Block:* This OPTIONAL element represents the data resulting from
2064 processing the Agent.
2065

2066 **5.7.4.5 Notification**

2067 If a DRM Client has subscribed to the topic space defined in Section 5.6.2.2, the Provide
2068 DRM Objects service (event source) notifies the DRM Client when it has new DRM
2069 Objects for it. The payload of the notification SHALL be:

- 2070 • *Notification ID:* The ID of the notification
2071

2072 The notification signals to the DRM Client that it MUST contact the Provide DRM Objects
2073 service to get the object(s).

2074 **5.7.4.6 Protocol Security Policies**

2075 The request and confirmation MUST obey the 'Integrity+Freshness' policy (Section
2076 5.2.3.4) and the response MUST obey the 'Integrity+Freshness' policy (Section 5.2.4.3.)
2077

2078 Moreover, in order to correlate the request with the confirmation messages, the
2079 Message Correlation pattern described in [NEMO] §2.3 MUST be used. The specific
2080 information in the SOAP header guarantying the correlation MUST be covered by the
2081 message signature.

2082 The identifier for this policy is:

```
urn:marlin:core:1.0:nemo:services:provide-drm-objects:obtain-objects:policy:0
```

2084

2085 **5.7.5 Provide Security Data**

2086 **5.7.5.1 Overview**

2087 This is a simple REQUEST/RESPONSE protocol.

2088

2089 The XML schema for this protocol is defined in the XML Namespace

2090
2091
2092
2093
2094

urn:marlin:core:1-1:nemo:services:schemas

A copy of the XML schema and WSDL is in Appendix A.5 and B.5, respectively.

2095 **5.7.5.2 Request parameters**

- 2096 • *Security Metadata*: The security metadata possessed by the Device which the
2097 Service may inspect for currency.
- 2098 • *Notification ID*: This OPTIONAL element is present if the request is sent after the
2099 Device has been notified (event driven invocation), then this parameter MUST be
2100 present so that the service can correlate it with the notification it sent to the
2101 Device.

2102 **5.7.5.3 Response Data**

- 2103 • *Security Metadata*: The data to be processed by the Device
2104

2105 **5.7.5.4 Notification**

2106 If a Device has subscribed to the topic space defined in Section 5.6.2.1, the Provide
2107 Security Data service (event source) notifies the Device when it has new Security Data
2108 for it. The payload of the notification SHALL be:

- 2109 • *Notification ID*: The ID of the notification
2110

2111 The notification signals to the Device that it MUST contact the Provide Security Data
2112 service to get the update.

2113 **5.7.5.5 Protocol Security Policies**

2114 Because the response requires freshness the request SHOULD obey the 'Freshness'
2115 only policy (Section 5.2.3.2) and the response MUST obey the 'Integrity+Freshness'
2116 policy (Section 5.2.4.3.)
2117

2118 The identifier for this policy is:

urn:marlin:core:1-2:nemo:services:security-data:obtain-data:policy:0

2119 **5.7.6 License Transfer**

2120 **5.7.6.1 Overview**

2121 In order to ensure consistent behaviour among implementations some of the service
2122 interactions must uphold usage rules. For the License Transfer service the usage rule is
2123 defined in Section 11. This protocol specifies the service interaction used to support this
2124 usage rule.
2125

2126 The XML schema for this protocol is defined in the XML Namespace

2127

urn:marlin:core:1-1:nemo:services:schemas

2128

2129

2130


A copy of the XML schema and WSDL is in Appendix A.6 and B.6, respectively.

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

2131
2132

The figure below indicates the message flow for this protocol.



2133
2134

2135 5.7.6.2 Setup Message Parameters

- 2136 • *License*: Data structure that carries the license to be transferred.
- 2137 • *Operation*: The type of transfer operation.
- 2138 • *Octopus Bundle*: the data structure containing the public Octopus Personality
- 2139 Node representing the DRM Client.
- 2140 • *SessionId*: OPTIONAL element. It SHALL NOT be present except if the operation
- 2141 is urn:marlin:core:1-3:service:license-transfer:release in which case it MAY be
- 2142 present if a SessionId parameter was received in the Extended Status Block fo
- 2143 for the corresponding render or checkout action.
- 2144 • *RequireContentKeys*: OPTIONAL element. It SHOULD be present with a value of
- 2145 false if the sink knows that it is already capable of decrypting the content keys.
- 2146 The absence of this element means that the Source has to re-encrypt the
- 2147 Content Keys of the sink in case of success of the protocol.

2148
2149

The types of operation are defined in the following table:

urn:marlin:core:1-0:service:license-transfer:move
urn:marlin:core:1-0:service:license-transfer:copy
urn:marlin:core:1-0:service:license-transfer:render
urn:marlin:core:1-0:service:license-transfer:checkout
urn:marlin:core:1-3:service:license-transfer:release

2150

In the case of streaming, the identifier

2151 urn:marlin:core:1-0:service:license-transfer:render
2152 is used ([8pus] §3).

2153

2154 When the Setup Message is received, the Source SHALL do the following:

- 2155 1. Collect all the contentId attributes found in the LicensePart elements (see XML
2156 schema).
- 2157 ○ When a contentId attribute in a LicensePart element is omitted, all of the
2158 contentId(s) in Bundle element (LicensePart/Bundle) are target for LTP
2159 transaction.
 - 2160 ○ When a contentId attribute in a LicensePart element is specified, the
2161 corresponding contentId in Bundle element (LicensePart/Bundle) is a
2162 target for LTP transaction.
- 2163 2. Process all the Bundle elements found in the LicensePart elements
- 2164 3. Open the set of content IDs collected above
- 2165 4. Verify the appropriate signatures on the relevant objects
- 2166 5. Populate the relevant context for the Control.Actions.Transfer method
- 2167 6. Optionally invoke the Control.Actions.Transfer.Check method on the processed
2168 Control object.
- 2169 7. Invoke the Control.Actions.Transfer.Perform on the process Control object.
- 2170 8. Read the Extended Status Block (ESB) returned by the
2171 Control.Actions.Transfer.Perform entry point.
- 2172 ○ If this ESB contains a RunAgentOnPeer obligation / OnAgentCompletion
2173 callback (see [8pus] §3), the RunAgentOnPeer obligation SHALL contain
2174 all the parameters that the Source application needs in order to build the
2175 RunAgent message. Note that this message will also be sent if the
2176 application encounters another RunAgentOnPeer/OnAgentCompletion
2177 callback/obligation pair in the Extended Status Block of the
2178 OnAgentCompletion callback (after one or more RunAgent/AgentResult
2179 message exchange).
 - 2180 ○ If this ESB does not contain a RunAgentOnPeer obligation /
2181 OnAgentCompletion callback, it means that the Teardown message (see
2182 section 3.4) MUST be sent. Note that this ESB MAY contain a
2183 ProximityCheck obligation / OnSinkProximityChecked callback in which
2184 case the harpoon protocol SHALL be performed and the result will be
2185 read from the ESB of the OnSinkProximity checked callback before
2186 sending the Teardown message.

2187 5.7.6.3 RunAgent Message Parameters

- 2188 • *Agent Carrier*: The data structure containing the Agent as well as the input
2189 parameters and the context ID. The name and controlId attributes MUST be
2190 specified to unambiguously identify the Agent.

2191

2192 When the Sink receives the agent it MUST run it as specified in section 3.2.8 of the
2193 [8pus] specifications.

2194 5.7.6.4 AgentResult Message Parameters

- 2195 • *Agent Result Block*: The data resulting from the processing of the Agent.

2196 **5.7.6.5 Teardown Message Parameters**

- 2197
- 2198 • *Extended Status Block*: This is the ESB of the last invocation of the Control that
2199 contains no agent related obligation / callback pair. It contains the protocol result
2200 so that the sink knows if the protocol has succeeded or not. In case of failure, this
2201 ESB MAY point to resources located in the ResourceList extension of the Control
2202 that was sent in the Setup message.
 - 2203 • *Content Key List*: OPTIONAL element. If the protocol is not successful as
2204 indicated by the Extended Status Block above, this element SHALL NOT be sent.

2205 NOTE: In the case of the urn:marlin:core:1-0:service:license-transfer:render operation,
2206 the sink MUST use the ESB in the Teardown message as is and MUST NOT locally re-
2207 evaluate the Control for the Control.Actions.Play action. For all other operations, the
2208 Control.Actions.Play action MUST be performed before playing the content.

2209 NOTE: in the case of the urn:marlin:core:1-0:service:license-transfer:render and
2210 urn:marlin:core:1-0:service:license-transfer:checkout actions, the ESB MAY contain a
2211 SessionId critical parameter (see [8pus] §3) that the sink MUST send back when doing a
2212 urn:marlin:core:1-3:service:license-transfer:release on the same piece of content.
2213

2214 **5.7.6.6 Protocol Security Policies**

2215 The Setup and AgentResult messages MUST obey the 'Integrity+Freshness' policy
2216 (Section 5.2.3.4.) The RunAgent and Teardown messages MUST obey the
2217 'Integrity+Freshness' policy (Section 5.2.4.3.)
2218

2219 Moreover, in order to correlate the messages, the Message Correlation pattern
2220 described in [NEMO] §2.3 MUST be used. The specific information in the SOAP header
2221 guarantying the correlation MUST be covered by the message signature.
2222

2223 The identifier for this policy is:

urn:marlin:core:1.3:nemo:services:license-transfer:policy:0

2224 **6 Marlin Protocol Bindings**

2225 Except where noted, Marlin Protocols SHALL use the Nemo SOAP/HTTP Message
2226 Bindings.

2227 **6.1 HTTP/OBEX Binding**

2228 The purpose of this section is to offer a binding of HTTP over a non-IP stack to support
2229 directly attached devices. When using OBEX as a transport over a non-IP stack this
2230 binding is REQUIRED.

2231
2232 This binding supports the conveyance of HTTP messages over an OBEX transport. The
2233 general notion behind this binding is to map the HTTP-message as defined in
2234 [RFC2616] §4 and §5 to objects in the OBEX Object Model [OBEX13] §2. In so doing,
2235 this binding is a generic HTTP binding and could be used to exchange any content that
2236 the HTTP protocol supports.

2237
2238 The following identifiers are defined to support this binding.

Identifier	Type	Value	Description
HOB_UUID	UUID	0ba38ad4-018b-3b48-b0ad-14946ef90493	Target header Connection Id to connect to the service supporting this binding
HOB_INSPECT	URI	/inspect.xml	An absolute-path reference form of a relativeURI [RFC2396] §5 to the device inspection document. For a device supporting the Marlin inspection service the result of dereferencing this URI would be an XML document containing a <mc:X_MarlinDeviceInfo> element.
HOB_SCHEME	URI scheme	httpobex	A protocol scheme identifier used as the prefix to URLs.

2239
2240 To further elaborate on the construction of URLs a client using this binding would make
2241 http-like requests to the OBEX connected server using the following static syntax:
2242 httpobex://0ba38ad4-018b-3b48-b0ad-4946ef90493/
2243

2244 For example, to retrieve the well-known inspection service document (HOB_INSPECT)
2245 the URL would be:

2246 httpobex://0ba38ad4-018b-3b48-b0ad-4946ef90493/inspect.xml
2247

2248 The following OBEX Operations are REQUIRED to support this binding.
2249

OBEX Operation	Opcode
CONNECT	0x80
DISCONNECT	0x81

GET	0x03 (0x83)
ABORT	0xFF

2250
2251

2252 **6.1.1 Connection Establishment**

2253 This binding REQUIRES that a session between the client and server endpoints be
2254 established prior to exchanging HTTP messages over the transport. This is
2255 accomplished by sending a CONNECT request and the remote device indicates that the
2256 connection has been established by returning a successful response.

2257

2258 The OBEX CONNECT request MUST contain the following fields:

- 2259 • CONNECT Opcode (0x80)
- 2260 • Packet Length
- 2261 • OBEX Version Number
- 2262 • Flags
- 2263 • Maximum OBEX Packet Length

2264

2265 In addition to the above fields the CONNECT message MUST include a Target header
2266 bearing the value of the HOB_UUID.

2267

2268 A successful OBEX CONNECT response MUST contain the following fields:

- 2269 • OBEX Response code (0xA0)
- 2270 • Packet Length
- 2271 • OBEX Version Number
- 2272 • Flags

2273

2274 In addition to the above fields a successful response message MUST include a
2275 Connection ID header. This header MUST be the first header.

2276

2277 The Connection ID is used to supply context in subsequent interactions between the
2278 client and server.

2279 **6.1.2 Connection Termination**

2280 Once a session has been established multiple message exchanges may occur over the
2281 connection. Once an application has completed its message exchanges it MUST tear
2282 down the session. This is accomplished by sending a DISCONNECT request, and the
2283 remote device indicates that the connection has been terminated, by returning a
2284 successful response.

2285

2286 The OBEX DISCONNECT request MUST contain the following fields:

- 2287 • DISCONNECT Opcode (0x81)
- 2288 • Packet Length

2289

2290 In addition to the above fields the DISCONNECT message MUST include a valid
2291 CONNECTION ID header to indicate which session to terminate.

2292

2293 A successful OBEX DISCONNECT response MUST contain the following fields:
 2294 • OBEX Response code (0xA0)
 2295 • Packet Length
 2296

2297 **6.1.3 Message Exchange**

2298 Following the successful establishment of a connection, HTTP message exchanges may
 2299 commence.
 2300

2301 This binding REQUIRES that the OBEX GET operation be used for all such message
 2302 exchanges. This binding also REQUIRES that the connection id returned from the
 2303 connection establishment phase of this binding be included in the Connection ID header
 2304 of each GET request message.

2305 **6.1.4 Aborting a Message Exchange**

2306 In the advent that a multi-packet message exchange needs to be abandoned by the
 2307 client application the OBEX ABORT operation may be used. See [OBEX13] for details.

2308 **6.1.5 Mapping HTTP Messages to OBEX**

2309 This binding leverages the many similarities between the OBEX protocol and HTTP to
 2310 define mechanism by which to exchange HTTP messages over OBEX.
 2311

2312 The general approach is to map HTTP methods to OBEX operations, HTTP status
 2313 codes to OBEX response codes, HTTP message header to OBEX HTTP header, and
 2314 the HTTP message body to OBEX Body (or End-of-Body) header objects.
 2315

2316 The following table provides the mapping and the section number within the respective
 2317 specifications where the mapped entity is defined.
 2318

HTTP 1.1 Tokens [RFC2616]	Section	OBEX Field/Object [OBEX13]	Section
Method	§5.1.1	Opcode	§3.3
Status-Code	§6.1	Response code	§3.2
message-header	§4.2	HTTP header	§2.2.8
message-body	§4.3	Body/End-of-Body header	§2.2.9
Content-Type entity-header	§7.2.1	Type header	§2.2.3

2319

2320 **6.1.5.1 HTTP Method to OBEX Opcode Mapping**

2321 This binding supports all of the HTTP Methods defined in [RFC2616] §9.2-§9.9. All of
 2322 these methods are mapped onto the OBEX GET operation. The rationale being that the
 2323 OBEX GET operation is much more flexible than the OBEX PUT in handling variable
 2324 sized HTTP request and response messages. That is unlike the OBEX GET operation
 2325 the OBEX PUT operation does not support multi-packet responses.
 2326

2327 **6.1.5.2 HTTP Status Code to OBEX Response Code Mapping**
 2328 OBEX natively supports a direct mapping between HTTP status codes and OBEX
 2329 response codes. This binding REQUIRES the use of the native mapping.

2330 **6.1.5.3 HTTP Content-Type entity-header to OBEX Type Header Mapping**
 2331 To aid in dispatching and processing protocol messages the OBEX Type header
 2332 SHOULD include the equivalent value as the value conveyed in the HTTP Content-Type
 2333 entity-header.
 2334

2335 **6.1.5.4 HTTP message-header to OBEX HTTP Header Mapping**
 2336 The OBEX HTTP header MUST contain the contents of the HTTP 1.1 message-header.

2337 **6.1.5.5 HTTP message-body to OBEX Body or End-of-Body Mapping**
 2338 The OBEX Body header (or End-of-Body) MUST deliver the payload of the HTTP
 2339 message. The payload MUST only include the message-body as described in [HTTP]
 2340 §4.3. For example, when exchanging SOAP messages the HTTP message-body would
 2341 be consumed by the entire SOAP message (<Envelope>...</Envelope>). Note that the
 2342 message may be split into smaller messages and transferred in several OBEX GET
 2343 messages.

2344 **6.1.5.6 Example HTTP Message Exchange (Informative)**
 2345 The following tables give a generalized example of the protocol message flows used to
 2346 exchange an HTTP request and response, respectively. These examples assume that
 2347 an OBEX session was previously established.
 2348

HTTP Client Request:	Bytes	Description
Opcode	0x03	GET, Final bit NOT set
	0xnxxx	Length of packet
	0xCB	Connection Id header
	0xnxxx	Connection Id
	0x42	Type header
	0x09	Length of type object
	text/xml	Type of object (NULL terminated ASCII)
	0x47	HTTP header
	0x...	HTTP 1.1 header
	0x48	Body header
	0xnxxx	Length of Body header
	0x...	Body (HTTP message-body)
HTTP Server Response:		
	0x90	CONTINUE, Final bit set
	0x0003	Length of response packet
HTTP Client Request:		
Opcode	0x03	GET, Final bit NOT set
	0xnxxx	Length of packet
	0x47	HTTP header
	0x...	HTTP 1.1 header
	0x48	Body header

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

	0xn... 0x...	Length of Body header Body (continuation of HTTP message-body)
HTTP Server Response:		
	0x90 0x0003	CONTINUE, Final bit set Length of response packet
HTTP Client Request:		
Opcode	0x83 0xn... 0x47 0x... 0x49 0xn... 0x...	GET, Final bit set Length of packet HTTP header HTTP 1.1 header End-of-Body header Length of End-of-Body header End-of-Body (last part of HTTP message-body)

2349
2350

2351

HTTP Server Response:	Bytes	Description
	0x90 0xn... 0x42 0x09 text/xml 0x47 0x... 0x48 0xn... 0x...	CONTINUE, Final bit NOT set Length of response packet Type header Length of type object Type of object (NULL terminated ASCII) HTTP header HTTP 1.1 header Body header Length of Body header Body (HTTP message-body)
HTTP Client Request:		
Opcode	0x83 0x0003	GET, Final bit set Length of packet
HTTP Server Response:		
	0xA0 0xn... 0x47 0x... 0x49 0xn... 0x...	SUCCESS, Final bit set Length of response packet HTTP header HTTP 1.1 header End-of-Body header Length of End-of-Body header End-of-Body (last part of HTTP message-body)

2352

2353 **6.2 SOAP 1.1/HTTP 1.1 Binding (Informative)**

2354 This binding is normatively defined in [SOAP11] 6§. However to aid the reader germane
2355 aspects of the binding are informatively described here.

2356 **6.2.1 HTTP Headers**

2357 **6.2.1.1 HTTP Method**

2358 The HTTP request method must be POST as defined in the SOAP HTTP Binding
2359 [SOAP11].

2360 **6.2.1.2 Content-Type**

2361 The Content-Type header must be 'text/xml; charset="utf-8"' as defined in the SOAP
2362 HTTP Binding [SOAP11].

2363 **6.2.1.3 Content-Length**

2364 The Content-Length header must be supplied in accordance with HTTP 1.1 [RFC2616].

2365 **6.2.1.4 SOAPAction**

2366 The SOAP Action header must be supplied to give the intent of the SOAP HTTP request
2367 [SOAP11] §6.1.1. However, this is an application specific value and therefore its
2368 definition is out of scope for this specification.

2369 **6.2.1.5 Caching Policy**

2370 It is the intent of this binding to not preclude the use of HTTP proxies. However, a SOAP
2371 based application typically does not desire an HTTP intermediary to cache requests and
2372 responses.

2373
2374 The following HTTP headers should be supplied to inhibit HTTP proxies from caching
2375 protocol messages.

2376
2377 Requesters should include the following HTTP headers:

- 2378
2379
 - Cache-Control: no-cache, no-store
 - Pragma: no-cache

2380
2381
2382 Responders should include the following HTTP headers:

- 2383
 - Cache-Control: no-cache, no-store, must-revalidate, private
 - Pragma: no-cache

2384
2385
2386 Additionally, it is not recommended to use the HTTP headers defined to support the
2387 HTTP 1.1 Validation Model.

2388 **6.3 NEMO Message Binding**

2389 This binding shall comply with the SOAP Message Binding as defined in [NEMO] §2.

2390 Additionally, the security of message exchanges MUST conform to the NEMO Security
2391 Bindings specification [NEMO] §3. Section 9.1.4.4 and section 9.1.4.5 describe signature
2392 verification and confidentiality protection of various target data, respectively. The proper
2393 application of the verification or encryption MUST align with NEMO usages as defined
2394 by [NEMO] §3. Thus, the signing/encryption targets for secure NEMO messaging MUST
2395 adhere to the following rules:

- 2396
2397
 1. A Marlin certificate containing a key used in a NEMO message with either of the
2398 NEMO usages;
2399
 - <http://nemo.intertrust.com/2005/10/security/secure-protocol/basic/1.0#response-signingKey>
 - <http://nemo.intertrust.com/2005/10/security/secure-protocol/basic/1.0#request-encryptionKey>
- 2400
2401
2402
2403
2404
2405 MUST contain the certificate policy;
- 2406
 - id-cp-nemo-marlin-service-key
- 2407

- 2408
2409
2410
2411
2412
2413
2414
2415
2416
2417
2. A Marlin certificate containing a key used in a NEMO message with either of the NEMO usages;
 - <http://nemo.intertrust.com/2005/10/security/secure-protocol/basic/1.0#request-signingKey>
 - <http://nemo.intertrust.com/2005/10/security/secure-protocol/basic/1.0#response-encryptionKey>
- MUST contain the certificate policy;
- `id-cp-nemo-marlin-client-drm-key`

2418 **7 Marlin Key Management**

2419 **7.1 Introduction (Informative)**

2420 In the Octopus DRM scheme an encrypted Content Key is delivered in the Octopus
2421 License Object. In the Marlin Key Management System, the Content Key may be
2422 encrypted with two different sets of keys:

- 2423 • **Scuba Keys**
2424 A key management system in which Octopus objects, such as Nodes and Links,
2425 carry keys needed to allow users and devices to derive the Content Key to
2426 access the protected content.
- 2427 • **[Starfish] Revocation Keys**
2428 A type of broadcast encryption that allows a Content Key to be encrypted in such
2429 a way that selected clients (for example, those that have been compromised in
2430 some way) are no longer able to access them. [Starfish] defines and uses the
2431 HBES (Hierarchical Hash-Chain Broadcast Encryption Scheme) key tree for
2432 creating and assigning revocation keys.

2433
2434 If no Nodes have yet been revoked, the Content Key is only encrypted with the Scuba
2435 Sharing Key. After one or more revocations have taken place, the Content Key is
2436 additionally encrypted using the [Starfish] revocation mechanism.

2437 **7.2 HBES Broadcast Key Block Validity**

2438 [Starfish] defines a binary and XML encoding of the HBES Broadcast Key Block (BKB).
2439 Conformant implementations of this specification MUST support the XML BKB encoding
2440 defined in [Starfish] §4.3. This specification requires that the BKB revocation information
2441 be signed by a trusted authority. The license issuing entity MUST verify the validity and
2442 integrity of the distributed BKB. However, a license consuming entity, such as a Octopus
2443 DRM Engine, SHOULD NOT verify the signature over the BKB revocation information.

2444 **7.3 Content Key Object before Exclusion**

2445 The ContentKey Object (<oct:ContentKey> element) contains a <oct:SecretKey>
2446 element which represents the actual key used to encrypt the content.

2447
2448 Before the first revocation of a device (or application), the Content Key CK (represented
2449 by the <oct:SecretKey> element) SHALL only be encrypted by the Scuba key (public or
2450 secret) of the entity the license is targeted to (the user for example) [8pus] §6. This
2451 results in the following algorithm:

$$2452 \quad K_{\text{Marlin}} = E(K_{\text{scuba}}, CK)$$

2453
2454 In this algorithm the following keys are introduced:

- 2455 **K_{scuba}** The key distributed by Scuba [SCUBA].
- 2456 **K_{Marlin}** The key to be stored in the Content Key Object
- 2457 **CK** The key used to encrypt the content.

2458
2459
2460 K_{scuba} is calculated according to [8pus] §6. K_{Marlin} is generated from K_{scuba} and CK.

2461

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

2462 After encryption with K_{scuba} (public or secret) of the entity the license is targeted to, the
2463 resulting encrypted data K_{Marlin} MUST be represented by <oct:SecretKey> in the
2464 <oct:ContentKey> element.
2465

2466 **7.4 Content Key Object after Exclusion**

2467 After the first exclusion, the CK SHALL be encrypted using the [Starfish] revocation
2468 mechanism. All DRM Clients SHALL implement the [Starfish] revocation mechanism.
2469 The resulting data SHALL then be encrypted with the Scuba key (public or secret) of the
2470 entity the license is targeted to. This results in the following algorithm:

2471
2472
$$K_{Marlin} = E(K_{scuba}, (E(K_{root}, CK))$$

2473

2474 In this algorithm the following keys are introduced:

2475 **K_{root}** The Broadcast Key extracted from the BKB. See [Starfish] for a detailed
2476 description of how the Broadcast Key is recovered for a given receiver.

2477 **K_{scuba}** The key distributed by Scuba Key Distribution ([8pus] §6).

2478 **K_{Marlin}** The key to be stored in the Content Key Object

2479 **CK** The key used to encrypt the content.

2480

2481 When exclusion is used, K_{root} is recovered from the BKB. The BKB MUST be carried in
2482 the same Bundle as the Content Key Object per Section 3.3.2.

2483

2484 After encryption with K_{root} , the byte sequence of <xenc:EncryptedData> is encrypted with
2485 K_{scuba} (public or secret) of the entity the license is targeted to. The resulting super-
2486 encrypted data K_{Marlin} MUST be represented by <oct:SecretKey> in <oct:ContentKey>.

2487

2488 Since CK is encrypted by both K_{root} and K_{scuba} , the ContentKey object SHALL follow the
2489 super-encryption guidance given in [xmlenc] §2.1.5. The algorithm used to encrypt the
2490 CK with K_{root} SHALL be 128 bit AES in CBC mode and the padding SHALL follow the
2491 guidance given in [xmlenc] §5.2. The [xmlenc] representation of the CK encrypted with
2492 K_{root} is signaled with an <xenc:EncryptionMethod> element Algorithm attribute with a
2493 value of:

2494 <http://marlin-drm.com/starfish/algorithmID/1.0>
2495

2496 The following example depicts the contents of the Octopus Bundle including the Content
2497 Key Object and the exclusion information supplied by the BKB:
2498

```
[01] <oct:Bundle xmlns:oct="http://www.octopus-drm.com/profiles/base/1.0">
[02]
[03] <!-- ContentKey -->
[04] <oct:ContentKey uid="urn:foo:bar:content-key:551881195">
[05] <oct:SecretKey uid="urn:foo:bar:content-key:551881195:secret-key">
[06] <KeyData encoding="xmlenc" format="RAW">
[07] <EncryptedData xmlns="http://www.w3.org/2001/04/xmlenc#"
      Type="http://www.w3.org/2001/04/xmlenc#Element">
[08] <EncryptionMethod
      Algorithm="http://www.w3.org/2001/04/xmlenc#aes128-cbc"/>
[09] <KeyInfo xmlns="http://www.w3.org/2000/09/xmldsig#">
[10] <KeyName>urn:marlin:organization:phony:01:secret-sharing</KeyName>
[11] </KeyInfo>
[12] <CipherData>
[13] <CipherValue>K3K9Idxk...MjoyW+w2S9i...=</CipherValue>
[14] </CipherData>
[15] </EncryptedData>
[16] </KeyData>
[17] </oct:SecretKey>
[18] </oct:ContentKey>
[19]
[20] <!-- Other Octopus Objects -->
[21] <oct:Protector>
[22] <oct:ContentKeyReference>
[23] <oct:Uid>urn:foo:bar:content-key:551881195</oct:Uid>
[24] </oct:ContentKeyReference>
[25] <oct:ProtectedTargets>
[26] <oct:ContentReference>
[27] <oct:Uid>urn:x-octopus.intertrust.com:content:0012</oct:Uid>
[28] </oct:ContentReference>
[29] </oct:ProtectedTargets>
[30] </oct:Protector>
[31] <oct:Controller Id="controller"
[32] <uid="urn:foo:bar:controller:2031011164">
[33] <oct:ControlReference>
[34] <oct:Uid>urn:foo:bar:control:874685522</oct:Uid>
[35] <oct:Digest>
[36] <DigestMethod xmlns="http://www.w3.org/2000/09/xmldsig#"
[37] <Algorithm="http://www.w3.org/2000/09/xmldsig#sha1"/>
[38] <DigestValue xmlns="http://www.w3.org/2000/09/xmldsig#">
[39] fj9yTLt4b90/SsYQyj8wB2dzRBU=</DigestValue>
[40] </oct:Digest>
[41] </oct:ControlReference>
[42] <oct:ControlledTargets>
[43] <oct:ContentKeyReference>
[44] <oct:Uid>urn:foo:bar:content-key:551881195</oct:Uid>
[45] <oct:Digest>
[46] <DigestMethod xmlns="http://www.w3.org/2000/09/xmldsig#"
[47] <Algorithm="http://www.w3.org/2000/09/xmldsig#sha1"/>
[48] <DigestValue xmlns="http://www.w3.org/2000/09/xmldsig#">
[49] yDOqz1Bs1lqstZpbp94jig3h5kY=</DigestValue>
```

```

[50]     </oct:Digest>
[51]     </oct:ContentKeyReference>
[52]     </oct:ControlledTargets>
[53] </oct:Controller>
[54] <oct:Control uid="urn:foo:bar:control:874685522">
[55]   <oct:ControlProgram
[56]     protocol="http://www.octopus-drm.com/specs/scp-1_0">
[57]     <oct:CodeModule
[58]       type="http://www.octopus-drm.com/specs/pkcm-1_0">
[59]       AAABsHB...LkdldExvY2FsVGltZQAAAAAA</oct:CodeModule>
[60]     </oct:ControlProgram>
[61]   </oct:Control>
[62]   ...
[63] <!-- BroadcastKeyBlock -->
[64] <sf:BroadcastKeyBlock xmlns:sf="http://marlin-drm.com/starfish/1.2"
[65]   keyTreeName="urn:marlin:starfish:keytree:1">
[66]   <sf:RevocationInformation structureVersion="0"
[67]     revocationVersion="0"
[68]     distributionURIs="http://marlin-tmo/bkb/bkb.xml"
[69]     issuedOn="..." nextUpdate="..."
[70]     ID="sYdkN33vvLG9sAN9bKp/8q0NKU=">
[71]     mQEMAzR ... S5qp =q9mn</sf:RevocationInformation>
[72]   <sf:EncryptedBroadcastKeys>
[73]     QvAsufa ... W3zu =a4bq</sf:EncryptedBroadcastKeys>
[74]   <!-- Signature -->
[75]   <Signature xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
[76]     <SignedInfo>
[77]       ...
[78]       <ds:Reference URI="#sYdkN33vvLG9sAN9bKp/8q0NKU=">
[79]         <ds:DigestMethod
[80]           Algorithm="http://www.w3.org/2000/09/xmldsig#sha1"/>
[81]         <ds:DigestValue>GyGsF0Pi4xPU.. </ds:DigestValue>
[82]       </ds:Reference>
[83]     </SignedInfo>
[84]   </Signature>
[85] </sf:BroadcastKeyBlock>
[86] </oct:Bundle>

```

2499 **Example 7-1 XML Depicting super-encrypted content key**

2500 Line [04] begins the <oct:ContentKey> element. Line [08] indicates that the symmetric
 2501 encryption method is in use.

2502
 2503 Line [10] signals the name of the secret key with the <ds:KeyName> element.

2504
 2505 On line [13] the <xenc:CipherValue> element carries the base64 encoded representation
 2506 of the super-encrypted CK. Decrypting this would reveal the XML representation of the
 2507 encrypted content key as exemplified below:

```

2508
2509   <EncryptedData xmlns="http://www.w3.org/2001/04/xmldsig#">
2510   <EncryptionMethod Algorithm="http://marlin-drm.com/starfish/algorithmID/1.0"/>
2511   <KeyInfo xmlns="http://www.w3.org/2000/09/xmldsig#">
2512     <KeyName>urn:marlin:starfish:keytree:1</KeyName>
2513   </KeyInfo>

```

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

2514 <CipherData>
2515 <CipherValue>YOUENCRYPTEDRCONTENTKEYCOMESHERE</CipherValue>
2516 </CipherData>
2517 </EncryptedData>

2518

2519 On line [64] of Example 7-1 the <sf:BroadcastKeyBlock> element is included in an
2520 <oct:Bundle> element.

2521

2522 The integrity of the BKB revocation information must be protected. Line [66] depicts the
2523 <sf:RevocationInformation> element and line [74] shows the <ds:Signature> element
2524 which carries the integrity protection information.

2525

2526 Line [71] illustrates the <sf:EncryptedBroadcastKeys> element which carries the base64
2527 encoding of the encrypted (with interval keys derived from the device key set [Starfish]
2528 §3.3.1) broadcast key.

2529

8 Renewability

2530

8.1 Overview

2531

Renewability in Marlin Core System implementations is supported in several ways:

2532

- Via implementation of upgrade mechanisms – devices that implement Marlin Core System Specifications MUST support a mechanism for updating the version of their implementation.

2533

2534

2535

- Licenses MAY encode a minimum security specification version requirement in control programs (see Section 8.2 and Section 12.5.4.3).

2536

2537

- Via distribution and checking of Certificate Revocation Lists. Certificates that have been revoked MUST be published in a Certificate Revocation List (CRL). The distribution of the CRL MAY be accomplished via the Marlin Security Data Provider or some other mechanism. Additionally, certificates MAY be issued with the CRL Distribution Point (CDP) extension which can be used to aid in retrieving the freshest CRL. If revocation lists are used, only the serial number of revoked certificates SHOULD be include. That is, expired certificates SHOULD NOT remain in a CRL subsequent to their expiration. This practice may significantly reduce the size of the CRL.

2538

2539

2540

2541

2542

2543

2544

2545

- Via denial of service to devices whose certificates have been revoked or that do not implement an acceptable version of the specification

2546

2547

2548

- Marlin protocols MUST include assertions that certify the version of their implementation. Service policies MUST require these assertions be present in the request messages.

2549

2550

2551

- Licenses MAY encode a minimum specifications version requirement.

2552

- As a last resort, [Starfish] Broadcast Encryption may be used to permanently prevent a device from accessing further content in a Marlin ecosystem.

2553

2554

2555

2556

2557

2558

2559

2560

2561

2562

However, once revoked, version upgrade of the DRM Client will not suffice to restore its ability to participate in the ecosystem, as it would need to re-acquire a personality node and all content previously bound to that node would be invalid. The distribution of the Broadcast Key Block MAY be accomplished via the Marlin Security Data Provider or some other mechanism. Additionally, a Broadcast Key Block MAY be issued with a list of Distribution URIs. The Distribution URIs MAY be used to retrieve the current Broadcast Key Block in a manner specific to the URI.

2563

8.2 Specification Version Attributes

2564

A client MUST be provisioned with (at manufacturing time or personalization time) a

2565

trusted representation of the Security Specification Version attributes. The Security

2566

Specification Version Attributes convey trusted attributes about a system entity (a Nemo

2567

node). The lifecycle and security properties of these asserted attributes signal the

2568

security facilities of the underlying specification. In practice Security Specification

2569

Version attributes would only change if a security issue required some fundamental

2570

change in security components of the specification. For example, if one of the requisite

2571

encryption algorithms were found to have a design flaw then a new algorithm would be

2572

adopted. In this example, that would require the Security Specification Version attributes

2573

of the affected specification to change so as to reflect the new security component.

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

2574
2575 The Security Specification Version attribute information is decoupled from a particular
2576 product implementation so as to independently manage and renew the security
2577 infrastructure. Specifically the lifecycle of, and the type of information signaled with
2578 Security Specification Version attributes are generally bound to the lifecycle of specified
2579 security mechanisms.
2580
2581 The Security Specification Version and Role attributes are conveyed within a SAML
2582 assertion. As an optimization, Security Specification Version attributes SHOULD be
2583 asserted in the same SAML assertion as the Role attributes. The authority to generate
2584 this assertion may be delegated to Marlin Services however this operational detail is not
2585 in the scope of this specification.
2586
2587 The asserted attributes apply to the entire Nemo node. The assertion MUST be bound to
2588 the Nemo Node of the DRM Client or other system entities and MUST be bound to the
2589 Security Specification Version attributes of the implementation itself. An implementation
2590 MUST ensure that the actual Security Specification Version attributes of the
2591 implementation are greater or equal to that of the assertion it possesses.
2592
2593 The assertion(s) bearing Security Specification Version attributes MUST be included in
2594 appropriate Nemo protocols along with the asserted Role attributes to allow services to
2595 evaluate the attributes when deciding to provide service.
2596

- When the client assertion(s) is rejected by the service, the client SHOULD
2597 attempt to update its Security Specification Version attributes to an acceptable
2598 level. This may require a software update (or simply an upgrade to an existing
2599 assertion if the implementation was already updated).
- The above allows software update and Security Specification Version attribute
2600 assertion acquisition to occur independently. If the versions in the assertion are
2601 less than what the current client software supports, it may be sufficient to acquire
2602 a new assertion that reflects the current software capabilities. Only if the client
2603 does not support an acceptable version of the specifications are software update
2604 and assertion renewal required.
2605

2606
2607 The Security Specificatin Version attributes referenced in the assertion MUST be made
2608 visible to the Octopus DRM Engine to be resolved at license evaluation time. Refer to
2609 the Section 12.5.4.3 of the DRM Usage Profiles for the specific attributes and arguments
2610 to the Octopus System.Host.GetObject() that allow an Octopus engine to access the
2611 value of the Security Specification Version certified in the assertion.
2612

2613 **9 Marlin Trust Management**

2614 **9.1 Certificates**

2615 Certificates assert a binding between an identity and a public key. The format of the
2616 certificates used in Marlin is X.509 v3 [X509]. Additionally, the certificates used in Marlin
2617 rely upon [PKIX] as a certificate profile. Except where otherwise noted the certificate
2618 fields SHALL comply with the X.509 specification [X509] and the IETF PKIX profile
2619 [PKIX].

2620
2621 Certificates for NEMO Nodes are subject to the NEMO Trust Management Bindings
2622 ([NEMO] §4) specification.

2623
2624 The certified public keys used in Marlin have specific policies attached to them. The
2625 various Certification Authorities manage the lifecycle of the keys and their usage.

2626 **Certificate Contents**

2627 Typical contents of X.509 certificates used in Marlin consist of the following fields:

- 2628 • Version.
- 2629 • Serial Number.
- 2630 • Signature.
- 2631 • Issuer.
- 2632 • Validity.
- 2633 • Subject.
- 2634 • Subject Public Key Information.
- 2635 • Extensions:
 - 2636 ○ Authority Key Identifier.
 - 2637 ○ Subject Key Identifier.
 - 2638 ○ Key Usage.
 - 2639 ○ Basic Constraints.
 - 2640 ○ Certificate Policies
 - 2641 ○ CRL Distribution Points

2642 **9.1.1.1 Version**

2643 The value of this field MUST be 2, which corresponds to X.509 version 3 Certificates.

2644
2645 `Version ::= INTEGER { v3(2) }`

2646 **9.1.1.2 Signature**

2647 The value of this field SHALL be either *sha-1WithRSAEncryption*⁶ [RFC3279] or
2648 *sha256WithRSAEncryption* [PKIXALGS].
2649

```
2650 sha-1WithRSAEncryption OBJECT IDENTIFIER ::= {  
2651     iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-1(1) 5 }  
2652  
2653 sha256WithRSAEncryption OBJECT IDENTIFIER ::= {  
2654     iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-1(1) 11 }
```

2655 **9.1.1.3 Issuer**

2656 The distinguished name of the Issuer MUST be represented with a single directory name
2657 attribute. The attribute type MUST be either a X.500 commonName or a directory name
2658 attribute whose syntax adheres to a URN and is identified by the object identifier is *id-*
2659 *nat-uri*. The latter is the preferred attribute type and it MUST be used for all CA or end-
2660 entity certificates managed outside of the trust authority (see Sections 9.4.) This attribute
2661 SHALL be encoded using UTF-8.

```
2662  
2663 cf.  
2664     id-marlin   OBJECT IDENTIFIER ::= { iso(1) identified-organization(3) dod(6)  
2665         internet(1) private(4) enterprise(1) marlin(23727) }  
2666     id-nemo     OBJECT IDENTIFIER ::= { id-marlin nemo(1) }  
2667     id-nemo-nat OBJECT IDENTIFIER ::= { id-nemo nameAttribute(1) }  
2668     id-nat-uri  OBJECT IDENTIFIER ::= { id-nemo-nat 1 }
```

2670 See [NEMO] §4 for more information.

2671 **9.1.1.4 Subject**

2672 The distinguished name of the Subject field MUST be represented with a single attribute.
2673 The attribute type MUST be either a X.500 commonName or a URI attribute whose
2674 object identifier is *id-nat-uri*. The latter is the preferred attribute type and it MUST be
2675 used for all CA or end-entity certificates managed outside of the trust authority (see
2676 Sections 9.4.) This attribute SHALL be encoded using UTF-8.

2677 **9.1.1.5 Subject Public Key Info**

2678 This field carries the public key of the subject and identifies the algorithm with which the
2679 key is used. Presently the only supported algorithm is *rsaEncryption*.

```
2680 pkcs-1 OBJECT IDENTIFIER ::= { iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) 1 }  
2681  
2682 rsaEncryption OBJECT IDENTIFIER ::= { pkcs-1 1 }
```

2684 **9.1.2 Excluded Certificate Extensions**

2685 Generally we are silent regarding optional certificate extensions. However, in some
2686 cases the use of the optional extension may have an adverse impact on interoperability,
2687 performance or implementation complexity. Therefore, the remainder of this sub-section
2688 indicates which of these extensions SHOULD NOT be included in certificates adhering
2689 to this profile.

⁶ Note that the key size is a matter to be determined by a compliance body. Also note that current best practices are for the trust anchors to have larger key sizes, which, as of this writing, is typically 2048 bits.

2690 **9.1.2.1 Policy Mappings**

2691 The Policy Mappings extension SHOULD NOT be included in certificates adhering to
2692 this profile. Doing so may impact interoperability and performance.

2693 **9.1.2.2 Policy Constraints**

2694 The Policy Constraint extension SHOULD NOT be included in certificates adhering to
2695 this profile. The Policy Constraint extension could be used as a technical mechanism by
2696 which to enforce the above recommendation to prevent Policy Mappings. However,
2697 using Policy Constraints may have an adverse effect on implementation complexity and
2698 interoperability.

2699 **9.1.2.3 Subject Alternative Name**

2700 The Subject Alternative Name extension SHOULD NOT be included in certificates
2701 adhering to this profile.

2702 **9.1.2.4 Issuer Alternative Name**

2703 The Issuer Alternative Name extension SHOULD NOT be included in certificates
2704 adhering to this profile.

2705 **9.1.3 Certificate Extensions**

2706 Marlin Core System implementation certificate extension fields include Authority Key
2707 Identifier, Subject Key Identifier, Basic Constraints, Certificate policy, and CRL
2708 Distribution Points.

2709 **9.1.3.1 Authority Key Identifier**

2710 This field contains a hash of the issuer's public key.

```
2711  
2712 extnID : id-ce-authorityKeyIdentifier OBJECT IDENTIFIER ::= { id-ce 35 }  
2713 critical : FALSE  
2714 value : hash(PublicKey)  
2715
```

2716 The key identifier SHOULD be composed of the 160-bit SHA-1 hash (as defined in [PKIX]
2717 §4.2.1.2 method 1) of the value of the bit string *issuerPublicKey* (excluding the tag, length,
2718 and number of unused bits). This field is used to enable key changeover.

2719 **9.1.3.2 Subject Key Identifier**

2720 This field contains a hash of the subject's public key.

```
2721  
2722 extnID : id-ce-subjectKeyIdentifier OBJECT IDENTIFIER ::= { id-ce 14 }  
2723 critical : FALSE  
2724 value : hash(PublicKey)  
2725
```

2726 The key identifier is composed of the 160-bit SHA-1 hash (as defined in [PKIX] §4.2.1.2
2727 method 1) of the value of the bit string *subjectPublicKey* (excluding the tag, length, and
2728 number of unused bits).

2729 **9.1.3.3 Key Usage**

2730 The key usage extension defines the purpose for which the key has been certified. For
2731 example, it specifies whether a key can be used for signature, certificate signing and key
2732 or data encipherment. The key usage field contains a bit string consisting of a series of

2733 flags, as indicated in [PKIX] §4.2.1.3. The particular key usages utilized by this profile
2734 are specified in Section 9.4.

```
2735  
2736 extnID : id-ce-keyUsage OBJECT IDENTIFIER ::= { id-ce 15 }  
2737 critical : TRUE
```

2738 9.1.3.4 Basic Constraints

2739 This field contains the value of the certificate's basic constraints. The basic constraints
2740 extension specifies whether the subject of the certificate is a Certificate Authority (CA)
2741 and in that case the maximum number of CA certificates that can follow this certificate in
2742 a certification path. This profile MUST adhere to the definition provided in [PKIX]
2743 §4.2.1.10.

```
2744  
2745 extnID : id-ce-basicConstraints OBJECT IDENTIFIER ::= { id-ce 19 }  
2746 critical : TRUE
```

2747 9.1.3.5 CRL Distribution Points Field

2748 This field identifies how CRL information is obtained. This profile relies upon an indirect
2749 CRL as described in [PKIX] §5. The CRL Distribution Points field MUST contain a
2750 *DistributionPointName*. This name MUST contain a general name of type URI. This URI
2751 is a pointer to the current CRL and is issued by the entity identified in *cRLIssuer*.

```
2752  
2753 extnID : id-ce-cRLDistributionPoints OBJECT IDENTIFIER ::= { id-ce 31 }  
2754
```

2755 All implementations SHALL be prepared to resolve the URI using the HTTP GET
2756 method. The URI MUST point to a file that has an extension of ".crl". The file MUST
2757 contain the DER encoded CRL [RFC 2585]. The mime-type of the returned resource
2758 SHALL be "application/pkix-crl".

2759
2760 The following is an (non-normative) example of how the cRLDistributionPoints field is
2761 populated:

```
2762  
2763 cRLDistributionPoints:  
2764   DistributionPoint:  
2765     distributionPoint: fullName: uniformResourceIdentifier: http://marlin-  
2766     tmo.com/crl/mtmocrls.crl  
2767     cRLIssuer: directoryName: URI=urn:marlin:datacertification:revocation  
2768
```

2769 9.1.3.6 Certificate Policies

2770 As specified in [PKIX] §4.2.1.5, this field indicates the policies under which the certificate
2771 has been issued and the purposes for which the certificate may be used. It plays a
2772 critical role in the construction of certification paths and the validation there of.

```
2773  
2774 extnID : id-ce-certificatePolicies OBJECT IDENTIFIER ::= {id-ce 32}  
2775 critical : TRUE  
2776
```

2777 The field contains *policyIdentifier* parameters within the *PolicyInformation* to indicate the
2778 OIDs of the policies. Certificates SHALL NOT include *policyQualifiers* other than those
2779 defined in [PKIX] §4.2.1.5, the CPS Pointer and the User Notice qualifiers.

2780 The CA MAY include the special policy *anyPolicy* as prescribed in [PKIX] §4.2.1.5.

```
2781  
2782 anyPolicy OBJECT IDENTIFIER ::= { id-ce-certificatePolicies 0 }  
2783
```

2784 The application specific policy OIDs are defined in Sections 9.1.3.6.1 and 9.1.3.6.2. The
2785 certificate policies and end-entity purposes for these different policy identifiers are further
2786 described in Sections 9.1.4.4, 9.1.4.5 and 9.4.

2787 **9.1.3.6.1 Certificate Policy OIDs for Octopus**

2788 The certificate policy OIDs defined for Octopus are shown below.

```
2789 id-octopus          OBJECT IDENTIFIER ::= {id-marlin octopus(2)}  
2790 id-octopus-cp      OBJECT IDENTIFIER ::= {id-octopus certificatePolicies(2)}  
2791 id-octopus-marlin-cp OBJECT IDENTIFIER ::= {id-octopus-cp marlin(10)}
```

2792 The following Marlin policy identifier OIDs are defined for the Octopus DRM.

```
2793  
2794 id-cp-octopus-marlin-scuba-sharing-key      ::= {id-octopus-marlin-cp 1}  
2795 id-cp-octopus-marlin-scuba-confidentiality-key ::= {id-octopus-marlin-cp 2}  
2796 id-cp-octopus-marlin-signing-personality   ::= {id-octopus-marlin-cp 3}  
2797 id-cp-octopus-marlin-signing-node         ::= {id-octopus-marlin-cp 4}  
2798 id-cp-octopus-marlin-signing-link         ::= {id-octopus-marlin-cp 5}  
2799 id-cp-octopus-marlin-signing-controller   ::= {id-octopus-marlin-cp 6}  
2800 id-cp-octopus-marlin-signing-control      ::= {id-octopus-marlin-cp 7}
```

2801 Note: The OIDs represented by the identifiers id-cp-octopus-marlin-scuba-sharing-key
2802 and id-cp-octopus-marlin-scuba-confidentiality-key are reserved for future use.
2803

2804 **9.1.3.6.2 Certificate Policy OIDs for NEMO**

2805 The Certificate policy OIDs defined for NEMO are shown below.

```
2806 id-nemo          OBJECT IDENTIFIER ::= {id-marlin nemo(1)}  
2807 id-nemo-cp      OBJECT IDENTIFIER ::= {id-nemo certificatePolicies(2)}  
2808 id-nemo-marlin-cp OBJECT IDENTIFIER ::= {id-nemo-cp marlin(10)}
```

2809 The following Marlin policy identifier OIDs are defined for the NEMO protocol and
2810 services.

```
2811 id-cp-nemo-marlin-client-drm-key          ::= {id-nemo-marlin-cp 1}  
2812 id-cp-nemo-marlin-service-key            ::= {id-nemo-marlin-cp 3}  
2813 id-cp-nemo-marlin-signing-data-certification ::= {id-nemo-marlin-cp 4}  
2814 id-cp-nemo-marlin-signing-service-role   ::= {id-nemo-marlin-cp 5}  
2815 id-cp-nemo-marlin-signing-client-role    ::= {id-nemo-marlin-cp 6}  
2816 id-cp-nemo-marlin-signing-security-metadata ::= {id-nemo-marlin-cp 7}  
2817 id-cp-nemo-marlin-signing-bootstrap     ::= {id-nemo-marlin-cp 8}  
2818 id-cp-nemo-marlin-signing-content-metadata ::= {id-nemo-marlin-cp 9}
```

2819 Note: OID {id-nemo-marlin-cp 2} is reserved.
2820

2821 **9.1.4 Certificate Validation**

2822 The certificate user MUST check a sequence of certificates until reaching a trust anchor
2823 to verify the validity of the certified public key.

2824 Except where otherwise noted, the process of validating a certificate SHALL produce the
2825 same results and exhibit the same behavior as the path validation process defined in
2826 [PKIX] §6.1.

2827 The certificate validation process consists of the following steps:

- 2828 • Certificate Verification Process.

- 2837 • Certificate Checking Process.
- 2838 • Signature Verification Process.
- 2839 • Key/Data Encipherment Process.

2840 **9.1.4.1 Trust Anchors**

2841 To validate a certificate, a certificate user MUST have the proper trust anchor or utilize
2842 an online certificate validation service. If the certificate user performs path validation it
2843 MUST manage trust anchor information securely to prevent unauthorized changes. The
2844 secure distribution of trust anchors is out of scope for this specification. However, a
2845 description of a trust hierarchy which supports these best practices and enables certain
2846 operational efficiencies is discussed in Section 9.4.

2847 **9.1.4.2 Certificate Path Validation**

2848 Each certificate MUST be verified by checking the certificate against its issuer. The
2849 issuer certificate MUST be checked against its issuer, in turn, until the trust anchor is
2850 reached. It is RECOMMENDED that the algorithm defined in [PKIX] §6.1 is
2851 implemented.

2852 Input data to the certificate path validation process include the following items:

- 2853 • A certificate (target).
- 2854 • Issuer certificate information, including the following:
 - 2855 ○ Trust Anchor.
 - 2856 ○ Public key.
 - 2857 ○ Subject.
 - 2858 ○ Basic constraints.
 - 2859 ○ Key usage.
 - 2860 ○ Certificate Policies.
- 2861 • List of acceptable certificate policies
- 2862 • The current date and time.
- 2863

2864 The validation algorithm defined in [PKIX] §6.1 takes into consideration Certificate
2865 Policies. Thus the validation algorithm implemented MUST also meet the following
2866 conditions:

2867 • **Check Certificate Policies**

2868 The policy information terms of the issuing certificate MUST be either *anyPolicy*
2869 or one or more of the intended certificate policy terms. See [PKIX] §4.2.1.5 and
2870 §6.1.3. The policy terms MUST be checked against the acceptable policies. See
2871 Section 9.1.3.6.1 and 9.1.3.6.2 for the policy identifiers. The acceptability of the
2872 policy terms are described in Sections 9.3 and 9.4.

2873 **9.1.4.3 Certificate Checking Process**

2874 The certificate checking process determines if the certificate can act on the specified
2875 target type. Input data to the certificate checking process includes a valid end-entity
2876 certificate from the path validation process and the key usage required to act on the
2877 target. To check the validity of the certificate, the system MUST check the following
2878 values:

2879 • **Key Usage**

2880 The key usage MUST be appropriate for the target type.

2881 **9.1.4.4 Signature Verification of Signed Data**

2882 Input data to the signature verification process includes the following items:

2883 • Trust Anchor.

2884 • Target data.

2885 • Target signature.

2886 • Target type.

2887 • Certificate information (verified, as in Section 9.1.4.2), including the following:

2888 ○ Trust Anchor

2889 ○ Public Key

2890 ○ Subject

2891 ○ Basic Constraint

2892 ○ Key Usage

2893

2894 The output from the signature verification process is either a positive or negative result.

2895 To validate a signature, the system MUST check the following items:

2896 • **Target Signature**

2897 The target data MUST be signed by the public key of the certificate.

2898 • **Key Usage**

2899 The *digitalSignature* bit MUST be set in the key usage field of the certificate.

2900

2901 For the signing keys used to secure NEMO messages refer to Section 6.3 for processing
2902 rules regarding the NEMO security bindings as they relate to the NEMO signing targets.

2903 **9.1.4.5 Key/Data Encipherment Process**

2904 Input to the key or data encipherment process includes the following information:

- 2905 • Target information includes the following:
 - 2906 ○ Target data.
 - 2907 ○ Target type.
- 2908 • Certificate information (verified, as in Section 9.1.4.2) includes the following:
 - 2909 ○ Trust Anchor
 - 2910 ○ Public Key
 - 2911 ○ Subject
 - 2912 ○ Key Usage

2913
2914 Output from the key or data encipherment process consists of the encrypted data.

2915 To encrypt data or keys, the system must check the following items:

- 2916 • **Key Usage**
 - 2917 If target data is a key, the KeyEncipherment bit must be set in key_usage of the
 - 2918 certificate. If target data is not a key, the DataEncipherment bit must be set in
 - 2919 key_usage of the certificate.

2920 For processing rules regarding the NEMO security bindings as they relate to the NEMO
2921 encryption targets refer to Section 6.3.

2922 **9.2 Certificate Revocation List**

2923 A Certificate Revocation List (CRL) is used to convey to a certificate user the set of
2924 revoked certificates. The format of the CRL used in Marlin is X.509 v2 CRL [X509].
2925 Additionally, the CRL used in Marlin rely upon [PKIX] as a CRL profile. This document
2926 specifies the use of indirect CRLs and their contents. The balance of this section
2927 describes the necessary fields to support an indirect CRL. Except where otherwise noted
2928 the CRL fields SHALL comply with the X.509 specification [X509] and the IETF PKIX
2929 profile [PKIX].

2930 **CRL Contents**

2931 Contents of X.509 CRLs used in Marlin consist of the following fields:

- 2932 • Version.
- 2933 • Signature.
- 2934 • Issuer.
- 2935 • This Update.
- 2936 • Next Update.

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

- 2937 • Revoked Certificates.
- 2938 ○ User Certificate.
- 2939 ○ Revocation Date.
- 2940 ○ CRL Entry Extension:
- 2941 ▪ Certificate Issuer.
- 2942 • CRL Extensions:
- 2943 ○ Authority Key Identifier
- 2944 ○ CRL Number.
- 2945 ○ Issuing Distribution Point.

2946 **9.2.1.1 Version**

2947 The value of this field MUST be 1, which corresponds to X.509 version 2 CRL.

2948 Version ::= INTEGER { v2(1) }

2950 **9.2.1.2 Signature**

2951 The value of this field SHALL be either *sha-1WithRSAEncryption*⁷ [RFC3279] or *sha256WithRSAEncryption* [PKIXALGS].

2952 sha-1WithRSAEncryption OBJECT IDENTIFIER ::= {

2953 iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-1(1) 5 }

2954 sha256WithRSAEncryption OBJECT IDENTIFIER ::= {

2955 iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-1(1) 11 }

2959 **9.2.1.3 Issuer**

2960 The distinguished name of the CRL Issuer MUST be represented with a single directory name attribute. The attribute type MUST be either a X.500 commonName or a directory name attribute whose syntax adheres to a URN and is identified by the object identifier *id-nat-uri* as defined in Section 9.1.1.3.

2964 **9.2.1.4 CRL Entry Extension**

2965 All mandatory fields for this extension must be present and follow the guidance given in [PKIX] §5.3. Of particular importance is the presence of the *certificateIssuer* field which identifies the authority which issued the revoked certificate.

2968 **9.2.1.5 CRL Extensions**

2969 As previously mentioned, the specification adheres to the [PKIX] CRL profile which mandates which fields must be present in the CRL Extensions. Specifically the *AuthorityKeyIdentifier* and the *CRLNumber* MUST be present. Additionally, since this specification relies upon an indirect CRL the *issuingDistributionPoint* extension MUST be present.

⁷ Note that the key size is a matter to be determined by a compliance body. Also note that current best practices are for the trust anchors to have larger key sizes, which, as of this writing, is typically 2048 bits.

2974 **9.2.1.5.1 Issuing Distribution Point**

2975 This field MUST follow the guidance given in [PKIX] §5.2.5. Specifically since the CRL is
2976 an indirect CRL the *indirectCRL* field MUST be present and MUST have a value of
2977 TRUE.

2978 **9.3 Trust Management of Marlin Services (Informative)**

2979 An implementation of a Marlin Core System may consist of a number of services. These
2980 services rely upon the trust management mechanisms defined by this specification.
2981 Additionally, delivery system specifications which build upon the Marlin Core System
2982 may utilize the same mechanisms defined here. This section gives a general overview of
2983 the types of services and the manner in which they may leverage the trust management
2984 mechanisms defined elsewhere in this specification.

2985 **9.3.1 Secure Peer Interactions**

2986 **9.3.1.1 Keys Used in NEMO Secure Communications**

2987 A short summary of the keys used to secure communications using the NEMO stack is
2988 provided below. The functions of the keys issued to a service are typically common for
2989 all such entities. They are as follows:

- 2990 • **Keys for signing and encrypting protocol data**
2991 All NEMO-based services have these keys.
- 2992 • **Keys for signing the service role attribute assertions**
2993 An entity must have a valid, signed role attribute assertion to be accepted as a
2994 NEMO service. These signing keys are issued under the authority of a service
2995 specific CA.
- 2996 • **Key for signing the client role attribute assertions**
2997 An entity must have a valid, signed client role attribute assertion to be accepted
2998 as a NEMO client. The Personalization Service signs client role attribute
2999 assertions.
- 3000 • **Keys for signing and encrypting data at the client**
3001 All clients have these keys. There may be separate key sets for use by DRM-
3002 related applications and non-DRM related applications.

3003 **9.3.2 DRM Services**

3004 A variety of services which are either defined or enabled by this specification fall into the
3005 category of DRM Services. In general, these services are associated with the
3006 provisioning, management and realization of content sharing and distribution systems.
3007 Examples of the services which are specifically defined by this specification are called
3008 out in the subsequent sections. Examples of services which are enabled by this
3009 specification are those services which directly support a specific delivery system
3010 technology and the business models which they enable. For example a service which
3011 collects content usage information would fall into this category.

3012 **9.3.2.1 Registration Services**

3013 Registration Services are those services which are responsible for the provisioning and
3014 relationship management of Octopus Objects used to influence the governance model.
3015 One such service defined by this specification is the DRM Object Provider service.

3016
3017 Trust Management supports these types of services by defining the certified keys used
3018 to secure the Octopus Objects. These keys are certified by a Registration Services CA
3019 (see 9.4.4.) Specifically, these certified keys enable a service to sign User Nodes, Links,
3020 and Controls.

3021

- **User Nodes**

3022 User Nodes contain a set of Scuba Sharing Keys.

3023

- **Links**

3024 Links are issued by the Registration Service.

3025

- **Controls**

3026 Controls may be issued by the Registration Service.

3027 **9.3.2.2 License Issuing Services**

3028 License Issuing Services are those services which are responsible for the creation of
3029 Octopus Objects used to govern access to content.

3030
3031 Trust Management supports these types of services by defining the certified keys used
3032 to secure some of these Octopus Objects. These keys are certified by a Content License
3033 Services CA (see 9.4.5.) Specifically, these certified keys enable a service to sign
3034 Controller and Control objects.
3035

3036 **9.3.2.3 Marlin Personalization Services**

3037 Personalization Services are those services which are responsible for the provisioning of
3038 Octopus Objects used to represent the personality of a device.

3039
3040 Trust Management supports these types of services by defining the certified keys used
3041 to secure these Octopus Objects. These keys are certified by a DRM Personalization
3042 CA. These certified keys enable the certificate user to sign Personality Nodes.

3043

- **Personality Nodes**

3044 A DRM Client Personality Node contains a set of Scuba Sharing Keys. These
3045 nodes and the keys they carry are issued by a personalization service or device
3046 manufacturer.

3047 **9.3.3 Data Certification Services**

3048 A variety of services which are either defined or enabled by this specification fall into the
3049 category of Data Certification Services. In general, these services are associated with
3050 the provisioning, management and renewal of security and integrity services. Examples
3051 of the services which are specifically defined by this specification are called out in the
3052 subsequent sections.

3053 **9.3.3.1 Security Metadata Certification Services**

3054 Security Metadata Certification Services are those services which are responsible for the
3055 attestation and issuance of security metadata used in the renewal and remediation of
3056 trust objects. Some examples of security metadata items are trusted time and certificate
3057 revocation lists (CRLs). One such service defined by this specification is the Security
3058 Data Provider service (Section 4.2.3.)
3059

3060 Trust Management supports these types of services by defining the certified keys used
3061 to secure the metadata. These keys are certified by a Security Metadata Certification
3062 Services CA. Specifically, these certified keys enable the service to sign tokens attesting
3063 to the freshness or qualities of security metadata.

3064 **9.3.3.2 Content Metadata Certification Services (aka Content Packager)**


3065 Content Metadata Certification Services are those services which are responsible for the
3066 integrity protection of the content metadata.
3067

3068 Trust Management supports these types of services by defining the certified keys used
3069 integrity protect the content metadata.

3070 **9.4 Trust Hierarchies and Policies**

3071 The Marlin Core System implementation employs X.509 Version 3 certificates for binding
3072 an identity to a public key, and constraining the usage of the certified key to a specific
3073 purpose. The following sections define the certificate profile, the certificate contents of
3074 defined fields, and the trust hierarchies for the management and validation of Marlin
3075 Core System implementation specification certificates. Except where otherwise noted
3076 certificates for Marlin Core System implementation SHALL comply with the X.509
3077 Version 3 specification [X509] and the IETF PKIX profile [PKIX].
3078

3079 The symbols in Figure 9-1 are used to depict the relationship of the entities in the trust
3080 hierarchy including the entities which participate and the certificates and keys issued.
3081



3082
3083 **Figure 9-1 Symbol Legend**

3084
3085 A single ended arrow between objects in the diagram describes a "Certifies" relationship.
3086 In essence, this suggests that the certificate from which the arrow sources is used to
3087 sign the object that the arrow points to. A double ended arrow between objects
3088 describes a binding of and identity to a role. A single midline arrow indicates an
3089 'authorizes' relationship.
3090


3091 The distinction between the "Trust Authority" and the "Delegated CA" is that a
3092 "Delegated CA" is operated by Marlin participating companies (or on their behalf)

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

3093 whereas the Trust Authority is operated by a Marlin-wide entity.

3094

3095 The following diagram depicts the top level trust topology of the Marlin Core System.



3096

3097 **Figure 9-2 Top-level Trust Topology**

3098

3099 The trust topology is comprised of a self-signed system root, the Marlin System Root,
3100 and three functional certificate hierarchies, the DRM Services Certificate Hierarchy, the
3101 Data Certification Services Certificate Hierarchy and the Peer Application Interaction
3102 Hierarchy⁸. These trust authorities delegate to subordinate Certification Authorities the
3103 responsibility of issuing and managing the lifecycle of CA and end-entity certificates.
3104 These subordinate CAs may have a certificate policy of “anyPolicy” or a specific set of
3105 certificate policy terms may be bound to their certificates. It is REQUIRED that
3106 downstream subordinate CAs will have specific certificate policy terms in their CA
3107 certificates and that they will propagate those terms into the end-entity certificates they
3108 issue. That said, the certificates issued by the subordinate CAs must adhere to the
3109 policy information terms conveyed in their certificate. Additionally, the subordinate CAs
3110 further constrains their subordinates and end-entities with certificate policies, and key⁹.

3111 **9.4.1 Peer Application Interaction Trust Hierarchy**


3112 The Marlin System Peer Application Interaction Trust Hierarchy is responsible for the
3113 lifecycle and management of end-entity certificates used to secure participant
3114 communication protocol interactions. Generally the certified keys bind a key to an
3115 identity of either a client or service system entity.

3116

3117 The following diagram depicts the certificates managed under this authority.

⁸ To optimize path validation and to minimize the reliance on self-signed certificates a best practice would be to distribute and rely upon these functional root certificates as trust anchors.

⁹ A compliance regime may dictate otherwise but it may be operationally simpler for the Marlin system root authority to not constrain in any way the functional roots and for the functional roots to minimize any constraints it puts on the operational certification authorities. With that in mind the root would not specify any certificate policies and the functional roots would minimally constrain the operational CAs to “anyPolicy”.



3118

3119 **Figure 9-3 Peer Application Interaction Trust Hierarchy**

3120 **9.4.1.1 Peer Application Interaction Authority**

3121 The Peer Application Interaction Authority is used to authorize instances of Peer
 3122 Application Interaction Certification Authorities. This authority is used to issue
 3123 certificates to Marlin participants so that they may operate a CA which certifies end-
 3124 entity certificates for Devices or Client applications and Services such that they may
 3125 communicate application or DRM data in a secure and interoperable manner.

3126

3127 The following table describes the Certificates issued by this authority and the intended
 3128 usage of the keys certified by CA subordinates.

Certificates that Authorize a Subordinate CA to Certify ...	Basic Constraint	Key Usage	Certificate Policy Identifiers
Signing Certificates for Devices and Client Applications Protocol and Service Interaction			
DRM keys of a NEMO Node	CA=TRUE pathLenConstraint>0	keyCertSign	id-cp-nemo-marlin-client-drm-key
Signing Certificates for NEMO Protocol and Service Interaction			
Service keys	CA=TRUE pathLenConstraint>0	keyCertSign	id-cp-nemo-marlin-service-key

3129 **Table 9-1 Peer Application Interaction Certifying Keys**

3130 **9.4.1.2 Peer Application Interaction Certification Authority**

3131 This Certification Authority certifies the keys with the following usage and policies.

3132

Key	Signing/ Encryption Targets	Basic Constraint	Key Usage	Certificate Policy Identifiers
Signing and/or Encrypting DRM or Application Payloads				
Keys for signing DRM/ Application data	Data for use by DRM applications	CA=FALSE	digitalSignature	id-cp-nemo-marlin-client-drm-key
Keys for encrypting DRM/ Application data	Data for use by DRM applications	CA=FALSE	dataEncipherment	id-cp-nemo-marlin-client-drm-key
Keys for encrypting DRM/ Application keys	Keys for use by DRM applications	CA=FALSE	keyEncipherment	id-cp-nemo-marlin-client-drm-key

3133 **Table 9-2 Client End-Entity Certificates**


3134

Key	Basic Constraint	Key Usage	Certificate Policy Identifiers
NEMO Protocol Services Interactions			
Sign protocol data	CA=FALSE	digitalSignature	id-cp-nemo-marlin-service-key
Encrypt protocol data	CA=FALSE	keyEncipherment	id-cp-nemo-marlin-service-key

3135 **Table 9-3 Service End-Entity Certificates**

3136 **9.4.2 DRM Services Trust Hierarchy**

3137 The following diagram depicts the entities which fall under this portion of the trust
3138 topology.



3139
3140

Figure 9-4 DRM Services Trust Hierarchy

3141 **9.4.2.1 DRM Services Authority**

3142 The DRM Services Authority may be used to authorize instances of a three distinct
3143 Certification Authorities. These Certification Authorities are described separately so as to
3144 highlight their individual functions and characteristics. However, other factors which are
3145 out of scope for this document may influence whether this degree of separation is
3146 necessary. For example, compliance criteria or operational efficiencies may be best
3147 served by combining the Content License Service CA with the Registration CA. This
3148 specification does not mandate separation or combination of the CAs but merely
3149 supplies an informative set of guidelines for constructing a trust topology.

3150


3151 The DRM Services Authority may issue certificates to Marlin participants so that they
3152 may operate a CA which certifies end-entity certificates for DRM Device or DRM Client
3153 application Personalization, Content License issuance and Registration services. This
3154 authority may also enable the subordinate CAs to issue certificates used to bind
3155 identities to specific roles.

3156

3157 The following subsections describe the three subordinate CAs independently as if they
3158 had a separate trust authority.

3159 **9.4.3 DRM Client Personalization Trust Hierarchy**

3160 The DRM Services Authority enables a trust hierarchy focused on the personalizing
3161 DRM Devices and Client Applications.



3162

3163 **Figure 9-5 DRM Client Personalization**

3164 **9.4.3.1 Trust Authority**

3165

3166 The DRM Services Authority is used to authorize instances of a DRM Personalization
 3167 Certification Authority. A DRM Personalization Certification Authority issues end-entity
 3168 certificates used to personalize a DRM Client.
 3169

Certificates that Authorize a Subordinate CA to Certify ...	Basic Constraint	Key Usage	Certificate Policy Identifiers
Marlin Octopus Personalization Service or Device Manufacturer			
Keys for signing personality nodes	CA=TRUE pathLenConstraint>0	keyCertSign	id-cp-octopus-marlin-signing-personality
NEMO Protocol and Service Interaction			
Keys for signing the service role	CA=TRUE pathLenConstraint>0	keyCertSign	id-cp-nemo-marlin-signing-service-role
Keys for signing Client Role information	CA=TRUE pathLenConstraint>0	keyCertSign	id-cp-nemo-marlin-signing-client-role

3170 **Table 9-4 Personalization Certifying Keys**

3171

3172

3173 **9.4.3.2 DRM Personalization Certification Authority**

3174 In Marlin, a client application hosts both an Octopus Personality Node, which provides a
3175 secure environment for DRM operations, and a NEMO Node, which is used to establish
3176 secure, interoperable communications with various services.

3177

3178 DRM Devices and DRM client applications require a variety of certificates and keys to
3179 interoperate with services and to participate in the consumption of protected content. An
3180 instance of a subordinate DRM Personalization Certification Authority is responsible for
3181 issuing the certificates which are used to personalize a device or client application. The
3182 certificates issued by this authority should be constrained to specific purposes. The
3183 keys, certificates and assertions which personalize a device or client application may be
3184 provisioned at manufacture time or delivered via a personalization bootstrap protocol.

3185

3186 The keys used to sign a Personality node MUST have key usages, and certificate
3187 policies that allow them to sign Octopus Personality Nodes (digitalSignature and id-cp-
3188 octopus-marlin-signing-personality, respectively.)

3189

Key Used to Sign...	Basic Constraint	Key Usage	Certificate Policy Identifiers
Marlin Octopus Personalization Service or Device Manufacturer			
Personality nodes	CA=FALSE	digitalSignature	id-cp-octopus-marlin-signing-personality

3190 **Table 9-5 Signing Keys and Certificates for Personalization Service or Device Mfg.**

3191 This subordinate CA also issues certificates which may be used for protocol interactions
3192 and to sign Client role attribute assertions.

3193

Key	Basic Constraint	Key Usage	Certificate Policy Identifiers
Personalization Services			
Keys for signing the client role	CA=FALSE	digitalSignature	id-cp-nemo-marlin-signing-client-role
Keys for signing the service role	CA=FALSE	digitalSignature	id-cp-nemo-marlin-signing-service-role

3194 **Table 9-6 Role Signing Certificates**


3195

3196
3197
3198
3199
3200
3201

9.4.4 Registration Services Trust Hierarchy

The DRM Services Authority enables a trust hierarchy focused on a domain management model.

The following diagram depicts the entities which fall under this portion of the trust topology.



3202
3203

Figure 9-6 Registration Trust Hierarchy

3204
3205
3206
3207
3208
3209

9.4.4.1 Trust Authority

The DRM Services Authority is used to authorize instances of a Marlin User/Device Registration Certification Authority. A Marlin User/Device Registration Certification Authority issues end-entity certificates used to operate a domain registration service. That is, this authority is used to delegate to authorized entities the right to issue certificates which may be used to operate a registration service.

Certificates that Authorize a Subordinate CA to Certify ...	Basic Constraint	Key Usage	Certificate Policy Identifiers
NEMO Protocol and Service Interaction			
Keys for signing the service role	CA=TRUE pathLenConstraint>0	keyCertSign	id-cp-nemo-marlin-signing-service-role
Registration Service			
Keys for signing Octopus objects	CA=TRUE pathLenConstraint>0	keyCertSign	id-cp-octopus-marlin-signing-node
			id-cp-octopus-marlin-signing-link
			id-cp-octopus-marlin-signing-control

3210

Table 9-7 Registration Service Authority Subordinate Certifying Keys

3211

9.4.4.2 Registration Certification Authority

3212
3213
3214
3215
3216

A Registration Certification Authority issues certified keys to a registration service (a Registrar) which enable the service to engage in protocol interactions with Nemo clients, sign Octopus User/Domain Nodes, Octopus Links, Octopus Controls and to sign Registrar role attribute assertions.

3217
3218
3219
3220
3221
3222
3223

Marlin supports a model by which a domain of devices or client applications can be formulated to enable a rich user experience. In some circumstances this is accomplished by associating a content rendering application (or device) with a user account. The subordinate Registration Certification Authorities issues end-entity certificates to operational entities which manage these linkages. The certificates issued constrain the operational entities to use the issued certificate for the purpose of signing Octopus Nodes, Links and Controls.

3224
3225
3226
3227
3228

The end-entity signing certificates issued MUST have a certificate policy term that indicates the certified key is intended to be used to sign Controls and Links (*id-cp-octopus-marlin-signing-control* and *id-cp-octopus-marlin-signing-link*, respectively).

3229
3230
3231
3232

Section 3.3.4 describes the mechanism by which Octopus objects are signed. As noted, Controls may be indirectly signed either by reference or as a result of being contained by the object being directly signed. Implementations SHALL take this into consideration when selecting acceptable policy terms. For example, when a Control is covered by the

3233 signature over a Link object, the acceptable policy terms (for the Control) would be *id-cp-*
 3234 *octopus-marlin-signing-link* AND *id-cp-octopus-marlin-signing-control*. Because the
 3235 signed Link object includes the Control, the identity of the Link signer (extracted from the
 3236 Subject distinguished name of the signers X.509 certificate) is also the signer of the
 3237 Control.
 3238

Key Used to Sign...	Basic Constraint	Key Usage	Certificate Policy Identifiers
Registration Service			
Non-Personality Nodes, Links and Controls	CA=FALSE	digitalSignature	id-cp-octopus-marlin-signing-node
			id-cp-octopus-marlin-signing-link
			id-cp-octopus-marlin-signing-control

3239 **Table 9-8 Registration Service Certifying Keys**

3240 This subordinate CA also issues certificates which may be used for protocol interactions
 3241 and to sign Registration Service (aka Registrar) role attribute assertions. The DRM
 3242 Object Provider and Domain Information Provider roles are asserted through a key
 3243 authorized under this Certification Authority.
 3244

Key Used to Sign...	Basic Constraint	Key Usage	Certificate Policy Identifiers
Registration Service			
Keys for signing the service role	CA=FALSE	digitalSignature	id-cp-nemo-marlin-signing-service-role


3245 **Table 9-9 Role Signing Certificate**

3246

3247
3248
3249
3250

9.4.5 Content Licensing Trust Hierarchy

The DRM Services Authority enables a trust hierarchy focused on content license issuance. The following diagram depicts the entities which fall under this portion of the trust topology.



3251
3252

Figure 9-7 Content Licensing Trust Hierarchy

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

3253 **9.4.5.1 Content License Services Authority**

3254 The DRM Services Authority is used to authorize instances of a Marlin Content License
 3255 Certification Authority. A Marlin Content License Certification Authority issues end-entity
 3256 certificates used to operate a License Issuer service. That is, this authority is used to
 3257 delegate to authorized entities the right to issue certificates which may be used to
 3258 operate a License Issuer service.
 3259

Certificates that Authorize a Subordinate CA to Certify ...	Basic Constraint	Key Usage	Certificate Policy Identifiers
NEMO Protocol and Service Interaction			
Keys for signing the service role	CA=TRUE pathLenConstraint>0	keyCertSign	id-cp-nemo-marlin-signing-service-role
License Service			
License Service/Keys for signing License	CA=TRUE pathLenConstraint>0	keyCertSign	id-cp-octopus-marlin-signing-controller
			id-cp-octopus-marlin-signing-control

3260 **Table 9-10 Content License Services Authority Subordinate Certifying Keys**

3261 The certificates issued to the Content License Certification Authority SHOULD include a
 3262 *nameConstraint* extension to constrain the name-space of the subjects (License Service)
 3263 it certifies. For example, the keys for signing controller objects might be constrained
 3264 such that only License Services certified within a particular name-space may be
 3265 authorized to sign the controls of a DRM object.

3266 **9.4.5.2 Content License Certification Authority**

3267 Content which is protected is issued a license by an authorized License Issuer service.
 3268 An instance of a Content License Certification Authority issues X.509 Public Key
 3269 certificates to License Issuer services. These certified keys are used by the License
 3270 Issuer to sign elements of an Octopus license; Controller and Control objects. The
 3271 Content License Certification Authority MAY issue a single certificate with multiple policy
 3272 identifiers in the certificate policy.
 3273

3274 The end-entity signing certificates issued MUST have a certificate policy term that
 3275 indicates the certified key is intended to be used to sign Controls and Controllers (*id-cp-*
 3276 *octopus-marlin-signing-control* and *id-cp-octopus-marlin-signing-controller*, respectively).
 3277

3278 Section 3.3.4 describes the mechanism by which Octopus objects are signed. As noted,
 3279 Controls may be indirectly signed either by reference or as a result of being contained by
 3280 the object being directly signed. Implementations SHALL take this into consideration
 3281 when selecting acceptable policy terms. For example, when a Control is covered by
 3282 secure digest of a referring Controller object, the acceptable policy terms would be *id-cp-*
 3283 *octopus-marlin-signing-controller* AND *id-cp-octopus-marlin-signing-control*. Because the
 3284 signature over the Controller object includes a secure hash of the Control, the identity of

3285 the Controller signer (extracted from the Subject distinguished name of the signers
 3286 X.509 certificate) is also the signer of the Control.
 3287

Key Used to Sign...	Basic Constraint	Key Usage	Certificate Policy Identifiers
License Issuer Service			
Licenses (Controller Objects)	CA=FALSE	digitalSignature	id-cp-octopus-marlin-signing-controller
			id-cp-octopus-marlin-signing-control

3288 **Table 9-11 License Issuer Service Signing Key(s)**

3289 This subordinate CA also issues certificates which may be used for protocol interactions
 3290 and to sign License Issuer role attribute assertions.
 3291

Key Used to Sign...	Basic Constraint	Key Usage	Certificate Policy Identifiers
License Issuer Service			
Keys for signing the service role	CA=FALSE	digitalSignature	Id-cp-nemo-marlin-signing-service-role

3292 **Table 9-12 License Issuer Role Signing Certificate**


3293

3294

3295 9.4.6 Data Certification Trust Hierarchy

3296 The Marlin Data Certification Trust Hierarchy is responsible for the lifecycle and
3297 management of end-entity certificates used to assert authenticity of data relied upon by
3298 participants as part of a governance model, business model or service model.
3299

3300 The following diagram depicts the certificates and certified keys which are managed
3301 under this topology.



3302

3303 **Figure 9-8 Data Certification Service Trust Hierarchy**

3304 **9.4.6.1 Data Certification Services Authority**

3305 The Data Certification Services Authority may authorize instances of a two distinct
 3306 Certification Authorities. These Certification Authorities are described separately so as to
 3307 highlight their individual functions and characteristics. However, other factors which are
 3308 out of scope for this document may influence whether this degree of separation is
 3309 necessary. For example, compliance criteria or operational efficiencies may be best
 3310 served by combining these CAs. This specification does not mandate separation or
 3311 combination of the CAs but merely supplies an informative set of guidelines for
 3312 constructing a trust topology.

3313 The Data Certification Services Authority may authorize instances of a Security
 3314 Metadata Certification Service Certification Authority and/or Content Metadata
 3315 Certification Service Certification Authority.

3316 Additionally this authority issues a certificate for the key used to sign indirect CRLs and
 3317 Broadcast Key Blocks.
 3318
 3319

Key Used to Sign...	Basic Constraint	Key Usage
Indirect CRL and Broadcast Key Block	CA=FALSE	cRLSign, digitalSignature

3320 **Table 9-13 CRL and BKB Signing Certificate**

3321 A Content Metadata Certification Service Certification Authority issues end-entity
 3322 certificates used to operate a Content Metadata Certification Service.

3323
 3324 A Security Metadata Certification Service Certification Authority issues end-entity
 3325 certificates used to operate Secure Metadata services such as the Security Data
 3326 Provider defined by this specification. This specification also enables the operation of
 3327 Data Certification Services. For example, Figure 9-8 depicts signing certificates for a
 3328 Data Certification Service (DCS) and the Data Update Service (DUS.)
 3329

Certificates that Authorize a Subordinate CA to Certify ...	Basic Constraint	Key Usage	Certificate Policy Identifiers
Security Metadata Service NEMO Interactions			
Keys for signing the service role	CA=TRUE pathLenConstraint>0	keyCertSign	Id-cp-nemo-marlin-signing-service-role
Keys for DCS Security Metadata			
Keys for signing Data Certification Assertion	CA=TRUE pathLenConstraint>0	keyCertSign	id-cp-nemo-marlin-signing-data-certification
Keys for Data Update Service Security Metadata			
Keys for signing	CA=TRUE	keyCertSign	id-cp-nemo-marlin-

security metadata items	pathLenConstraint>0		signing-security-metadata
Keys for Content Metadata			
Keys for signing content metadata items	CA=TRUE pathLenConstraint>0	keyCertSign	id-cp-nemo-marlin-signing-content-metadata

3330 **Table 9-14 Data Certification Services Authority Subordinate Certifying Keys**

3331 **9.4.6.2 Security Metadata Service Certification Authority**

3332 The Data Certification Services Authority delegates, to a subordinate Security Metadata
 3333 Certification Services Certification Authority, the authority to issue certificates used to
 3334 sign attribute assertions and security metadata. Finally this CA issues certificates which
 3335 are used to bind these security services to its role attribute
 3336

Key Used to Sign...	Basic Constraint	Key Usage	Certificate Policy Identifiers
Security Metadata Role Signing Certificate			
Keys for signing the service role	CA=FALSE	digitalSignature	Id-cp-nemo-marlin-signing-service-role
Keys for Data Certification Service			
Keys for signing DCS Assertion	CA=FALSE	digitalSignature	id-cp-nemo-marlin-signing-data-certification
Keys for Data Update Service			
Keys for signing security metadata items	CA=FALSE	digitalSignature	id-cp-nemo-marlin-signing-security-metadata

3337 **Table 9-15 End-Entity Certificates for Security Metadata Services**

3338 **9.4.6.3 Content Metadata Certification Service Certification Authority**

3339 The Data Certification Services authority delegates authority to a subordinate Content
 3340 Metadata Certification Services Certification Authority to issue certificates used to
 3341 ensure authenticity of metadata associated with content. The subordinate Content
 3342 Metadata Certification Service CA issues end-entity certificates to instances of a service
 3343 which provides this assurance (e.g. a content packager.)
 3344

3345 The certificates issued to this entity MUST have a certificate policy term that indicates
 3346 the certified key is intended to be used to sign content metadata (*id-cp-nemo-marlin-*
 3347 *signing-content-metadata*.)
 3348

Key Used to Sign...	Basic Constraint	Key Usage	Certificate Policy Identifiers
Keys for Content Metadata			
Keys for signing content	CA=FALSE	digitalSignature	id-cp-nemo-marlin-signing-content-metadata

Key Used to Sign...	Basic Constraint	Key Usage	Certificate Policy Identifiers
metadata items			

3349 **Table 9-16 End-Entity Certificates for signing content metadata**

3350 **10 File Format for Marlin Content**

3351 In order to ensure at least a minimal set of interoperability between implementations of
3352 core system specifications, Marlin specifies a set of content file format profiles in terms
3353 of containers, media encryption mechanisms, codecs profiles, and metadata structures.
3354 However, the media file formats which Marlin supports change periodically and it is best
3355 to specify these formats independently of the core system specification. For that reason
3356 the supported media file formats are defined in a separate supporting specification,
3357 Marlin – File Formats Specification [MFF1.0].

3358 11 Marlin Usage Rules

3359

3360 Marlin Usage Rules are encoded in Octopus Controls. However:

- 3361 • Certain usage rules may require support of a protocol between two participating
- 3362 Marlin DRM Clients, a sequence of preliminary operations to prepare for the
- 3363 execution of a Control's *perform* method (see Move Action in Section 11.1.)
- 3364 • Certain usage rules may require calling an application to perform some obligation
- 3365 after the Control's *perform* method has executed, including executing callbacks
- 3366 to the Octopus engine

3367

3368 Controls generally reference external objects such as Links, Node attributes, or state

3369 objects that are set by other System Calls or Controls.

3370

3371 In order to be interoperable, all core system implementations MUST implement the

3372 Octopus Controls specifications ([8pus] §3). This should enable all implementations to

3373 support such usage rules as:

3374

Actions	High-Level Conditions
Play	Unconstrained Start/End Date Action Counts (per device, not domain) N times For a Period of H hours after the 1st Play Active User/Domain/Subscription link check Any combination of the above

3375

3376 In addition, all core system implementations SHOULD implement the following Marlin

3377 defined actions:

- 3378 • Move (see Section 11.1)
- 3379 • Copy (see Section 11.1)
- 3380 • Export to DTCP
- 3381 • Export to CPRM
- 3382 • Export to VCPS
- 3383 • Export to MG-R
- 3384 • Export to Foreign DRM

3385

3386 [MEXP] defines the parameters required for a targeted export technology.

3387

3388 A license MAY indicate deviations from the default set of output control requirements.

3389 This SHALL be signaled using the mechanism defined by the Octopus Controls

3390 specification ([8pus] §3). All core system implementations SHOULD support the

3391 parameters defined in [MOCS1.0] to enable overriding default output controls.

3392

3393 Additional Usage Rules and supporting Actions and Obligations may be defined for

3394 individual Marlin Delivery System Specifications.

3395 **11.1 Move and Copy Actions**

3396 Moving and copying content to another device is supported using the Transfer action
3397 defined in the Octopus Standard Control Protocol 1.0 ([8pus] §3), in conjunction with the
3398 transfer protocol defined in Section 5.7.6 of this specification.

3399 In addition to the standard Transfer action parameters, this specification defines the
3400 following parameter (visible under the host object /Octopus/Action/Parameters, as
3401 specified in [8pus] §3):

- 3402 • Sink/Proximity/LastProbe = date of the most recent successful proximity probe from
3403 Source to Sink

3404 **11.1.1 Theory of Operation (Informative)**

3405 **11.1.1.1 Overview**

3406 This mechanism may be extended to support other types of control, but is designed to
3407 support the following basic features:

- 3408 • Before the Transfer operation, a content file C is “bound” to the Source device
3409 SRC (that is, the license L for C allows SRC to use the Content Key CK carried in
3410 L). The same license L does not allow the Sink device SNK to use CK).
- 3411 • The content file C can be transferred to SNK as-is, without any special
3412 protection. This means that this Transfer operation does not require that the
3413 content file be re-encrypted.
- 3414 • After the Transfer operation, the license L does not allow SRC to use CK
3415 anymore. The same license L allows SNK to use CK. The Control in L does not
3416 need to be re-generated or re-signed.
- 3417 • This Transfer protocol can at least support the following policy: SRC can transfer
3418 C to SNK if:
- 3419 ○ L allows SRC to use CK (the license is “valid” on SRC) and SNK is a
3420 member of the same domain as SRC.
- 3421 Or
- 3422 ○ L allows SRC to use CK and SNK is in proximity of SRC
3423

3424 **11.1.1.2 License Elements**

3425 The license L for a content file C that supports that type of Transfer semantics is
3426 constructed as follows:

- 3427 • C is encrypted with CK
- 3428 • The ContentKey Object (CKO) contains CK encrypted with the Scuba Sharing key
3429 SSK[*SRC*] of the Source device SRC’s personality node.
- 3430 • The Control is signed by the original Control creator (the import device most likely).

- 3431 • The Control CTRL contains at least the Play and the Transfer actions.
- 3432 ○ The Play action is implemented in a manner similar to the following rule:
- 3433 ▪ Play granted only if the SeaShell ([8pus] §7) state object
3434 /XXX/ContentTokens/C exists (where /XXX/ is some path prefix that
3435 represents a container in the SeaShell database into which the control
3436 can write).
- 3437 ○ The Transfer action is implemented in a manner similar to the following rule:
- 3438 ▪ If the date of the last proximity probe is within acceptable time of the
3439 current date then:
- 3440 • Return a GRANTED status with an Obligation to run an Agent
3441 A1 with parameter P1 and context CTX1 on the Sink and a
3442 Callback request to call back Method CLBK when Agent A1
3443 has been run on the Sink, with the result of the agent as input
3444 to the callback.
3445 Else
- 3446 • Return a GRANTED status with an Obligation to run an Agent
3447 A1 with parameter P2 on the Sink, and a Callback request to
3448 call back Method CLBK when Agent A1 has been run on the
3449 Sink, with the result of the agent as input to the callback.
- 3450 ▪ In the callback method CLBK:
- 3451 • Read the agent's result from our input parameter
- 3452 • If the result indicates a success, then:
- 3453 ○ delete the SeaShell state object
3454 /XXX/ContentTokens/C and return a GRANTED status
3455 with no further callback or obligation. The protocol
3456 ends.
3457 else
- 3458 ○ The result indicates a failure, return a DENIED status
3459 with the appropriate extended status parameters.
- 3460 ▪ The Agent A1 is a control that takes an input parameter indicating
3461 whether a certain domain membership is required or not (the domain
3462 membership node Id is included in the input parameter).
- 3463 • Require that the context host object CTX1 exist (this context
3464 host object MUST be set by the host as specified in the
3465 Transfer service protocol specification). Fail if the required
3466 context does not exist
- 3467 • If a domain membership is required, the control checks that
3468 the device in which it is running is a member of the specified

3469 domain (typically, checks for a link reachability, and possibly
3470 some other conditions). If the device is not a member of the
3471 domain, a failure status is returned

3472 • Create the SeaShell state object XXX/ContentTokens/C

3473 • Return a success result

3474

3475 **11.1.1.3 Sequence of Operations**

3476 a) The content file C is made available to the Sink.

3477 b) The Sink initiates a Transfer protocol for content C with the Source.

3478 c) The Sink provides its own node information (public node object, including
3479 signature and certificates) as well as the license bundle that governs C. The sink
3480 also optionally indicates whether it requires a re-encryption of the content keys or
3481 not.

3482 d) The Source initiates the Transfer action on the license L for C with the sink's
3483 node info and proximity status as action input parameters by calling the Perform
3484 method.

3485 e) When the return status of the Perform method indicates the initial GRANTED
3486 status with the obligation to run an Agent A1 on the sink, the Source sends A1 to
3487 the Sink and waits for the result.

3488 f) Upon receiving the result of A1 from the Sink, the Source calls back the callback
3489 method specified in the Callback return parameter of the previous step, passing
3490 the result of the agent as an input parameter.

3491 g) At this point, the callback method has returned an extended status block
3492 indicating if the protocol is a success or a failure. We assume it is a success.

3493 h) The extended status block is sent to the sink along with the re-encrypted content
3494 keys if the status block indicates a success and the content keys were required in
3495 the request.
3496

3497 **11.1.1.4 Agent**

3498 The agent included in the control for the license L has its own signature, created by the
3499 same entity as the one that created and signed the Controller for the license. This agent
3500 should be carried as an external extension of the Control object.

3501

3502

3503 12 Profiles

3504 This specification defines a variety of mechanisms by which system implementations
3505 can interact. In order to allow for flexibility and future functionality we may have defined
3506 multiple ways to achieve a similar functionality. However, interoperability may suffer if we
3507 do not narrow the choices. The following sections prescribe specific implementation
3508 guidance to aid developers and deployers.

3509 12.1 Cryptographic Algorithm Profiles

3510 This subsection prescribes which cryptographic, encoding and transformation algorithms
3511 are to be utilized.

3512 12.1.1 Hashing (Digest) algorithms:

3513 All implementations of Marlin SHALL support the following hashing algorithms:

- 3514 • SHA1 [SHA1]
- 3515 • SHA256 [SHA256]

3516 12.1.2 Keyed-Hash Message Authentication Code algorithms

3517 All implementations of Marlin SHALL support the following HMAC algorithm:

- 3518 • Keyed-HMAC [hmacwithsha1]

3519 12.1.3 Public Key algorithms

3520 All implementations of Marlin SHALL support the following public key algorithms and key
3521 sizes:

- 3522 • RSA 1.5 with 1024 and 2048 keys [RSA-1_5]
- 3523 • RSA-OAEP [RSA-1_5]]

3524 12.1.4 Signature Hash algorithms

3525 All implementations of Marlin SHALL support the following hash functions in combination
3526 with the above public key algorithms:

- 3527 • SHA1
- 3528 • SHA256

3529

3530 The hash function of the signature algorithm MUST be consistent with the hash
3531 algorithm used in computing the individual digests. For example, if the signature
3532 algorithm is RSA with SHA1 then the digest method must also be SHA1.

3533 12.1.5 Symmetric key algorithms

3534 All implementations of Marlin SHALL support the following algorithms:

- 3535 • AES 128 bit symmetric key [AES] in CBC mode [AES-MODES]
- 3536 • AES 128 bit symmetric key [AES] in CTR mode [AES-MODES, ISMACryp]
- 3537 §10.0.¹⁰

¹⁰ Note 128 bit AES in counter mode is only required by applications which encrypt/decrypt content.

3538 **12.1.6 Canonicalization**

3539 All implementations SHALL implement the following canonicalization methods
3540 • [xml-exc-c14n]

3541 **12.2 XML Digital Signature Profile**

3542 **12.2.1 <ds:Signature> Element**

3543 All signatures MUST be detached. There MAY be multiple signatures covering the same
3544 object.

3545
3546 The <ds:Signature> block MUST contain:

- 3547 • A <ds:SignedInfo> element
- 3548 • A <ds:SignatureValue> element
- 3549 • A <ds:KeyInfo> element

3550 **12.2.2 <ds:SignedInfo>**

3551 The <ds:SignedInfo> MUST embed the following elements:

3552 **12.2.2.1 <ds:CanonicalizationMethod>**

3553 The <ds:CanonicalizationMethod> element is empty and its ds:Algorithm attribute MUST
3554 signal the use of exclusive XML canonicalization using the identifier defined in [xml-
3555 exc-c14n] §4.
3556

3557 **12.2.2.2 <ds:SignatureMethod>**

3558 When a keyed HMAC algorithm is used for computing the signature, the
3559 <ds:SignatureMethod> element SHALL be empty and implementations SHALL ignore
3560 any spurious child elements carried in the <ds:SignatureMethod> element. The
3561 ds:Algorithm attribute of the <ds:SignatureMethod> element SHALL identify the
3562 signature algorithm and the hash function it utilizes. The hash function MUST be either
3563 SHA1 or SHA256. The identifiers are specified in [xmldsig] and [RFC4051], respectively.
3564 As a convenience to the reader these identifiers are repeated here:

3565 <http://www.w3.org/2000/09/xmldsig#hmac-sha1>
3566 <http://www.w3.org/2001/04/xmldsig-more#hmac-sha256>
3567

3568 When an RSA based signature algorithm is used the ds:Algorithm attribute SHALL
3569 identify the signature algorithm and the hash function it utilizes. The hash function
3570 MUST be either SHA1 or SHA256. The identifiers are specified in [xmldsig] and
3571 [RFC4051], respectively. As a convenience to the reader these identifiers are repeated
3572 here:

3573 <http://www.w3.org/2000/09/xmldsig#rsa-sha1>
3574 <http://www.w3.org/2001/04/xmldsig-more#rsa-sha256>
3575

3576 The hash function of the signature algorithm MUST be consistent with the hash
3577 algorithm used in computing the individual digests. For example, if the signature method
3578 is RSA with SHA1 then the digest method must also be SHA1.

3579 **12.2.2.3 <ds:Reference>**

3580 There MAY be one or more <ds:Reference> elements inside the <ds:SignedInfo> block
3581 if more than one object is signed by the same key. For example, signing an Octopus
3582 Control and an Octopus Controller with the same key.

3583
3584 When signing an Octopus object, the value of the ds:URI attribute MUST be the oct:Id
3585 attribute of the element carrying the encoding of the referenced Octopus object.

3586 NOTE:

- 3587 • It MUST be done this way instead of using the Uid attribute (real ID of the
3588 Octopus objects) because the production of xs:ID is not compatible with the
3589 URN syntax (xs:ID is defined as a non-colonized name.)

3590
3591 When signing a local XML element the value of the ds:URI attribute MUST be the value
3592 of the element's xs:ID-typed attribute (Note that the Octopus schema names this
3593 attribute oct:Id.)

3594

3595 When a reference is to an Octopus object, the digest in the reference MUST be
3596 the canonical byte sequence of the Octopus object as specified in [8pus] §5.

3597

3598 The canonicalization of Octopus objects MUST be indicated in a <ds:Tranforms>
3599 element. An example follows:

3600

```
<ds:Tranforms>  
  <ds:Transform  
    Algorithm="http://www.octopus-drm.com/octopus/specs/cbs-1_0"/>  
</ds:Tranforms>
```

3601

3602 No other <ds:Tranform> is allowed for Octopus object references.

3603

3604 The canonicalization for all other signed elements MUST use the exclusive
3605 canonicalization transform defined in [xml-exc-c14n]. An example follows:

3606

```
<ds:Tranforms>  
  <ds:Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#"/>  
</ds:Tranforms>
```

3607 **12.2.2.3.1 <ds:DigestMethod>**

3608 The <ds:DigestMethod> element SHALL be empty and its ds:Algorithm attribute
3609 SHALL identify the hash function it utilizes. The hash function MUST be either SHA1 or
3610 SHA256. The identifiers are specified in [xmldsig] and [xmlenc], respectively. As a
3611 convenience to the reader these identifiers are repeated here:

3612 <http://www.w3.org/2000/09/xmldsig#sha1>

3613 <http://www.w3.org/2001/04/xmlenc#sha256>

3614

3615 The hash function of the signature method MUST be consistent with the hash algorithm
3616 used in computing the individual digests. For example, if the signature algorithm is RSA
3617 with SHA1 then the digest method must also be SHA1.

3618 **12.2.2.3.2 <ds:DigestValue>**

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

3619
3620 The <ds:DigestValue> element MUST contain the base64 encoded value of the digest.

3621 **12.2.3 <ds:SignatureValue>**

3622 The signature value MUST be the base64 encoded value of the signature of the
3623 canonicalized ([xml-exc-c14n]) <ds:SignedInfo> element with the key described in the
3624 <ds:KeyInfo> element.

3625 **12.2.4 <ds:KeyInfo>**

3626 **12.2.4.1 HMAC Signatures**

3627 When signing with HMAC, the <ds:KeyInfo> element MUST have a single child,
3628 <ds:KeyName>, that indicates the key used for computing the HMAC signature. The
3629 guidance given in Section 12.2.2.2 regarding HMAC algorithm identification SHALL be
3630 followed.

3631
3632 For HMAC signatures over Octopus objects this identifier MUST be the oct:uid attribute
3633 of the Octopus secret key object used to compute the signature.

3634
3635 Example:

3636

```
<ds:KeyInfo>
  <ds:KeyName>urn:x-octopus:secret-key:1001</ds:KeyName>
</ds:KeyInfo>
```

3637 **12.2.4.2 Public Key Signatures**

3638 When signing with a public key algorithm, the public key used to verify the signature
3639 MUST be carried in an X.509 v3 certificate, and MUST be accompanied by other
3640 certificates necessary to complete the certificate path to a trust anchor.

3641
3642 These certificates MUST be carried, encoded in base64, in <ds:X509Certificate>
3643 elements. These <ds:X509Certificate> elements are embedded in an <ds:X509Data>
3644 element and this <ds:X509Data> element MUST be a child of the <ds:KeyInfo> element.
3645 The <ds:X509Certificate> elements MUST appear in sequential order, starting from the
3646 end-entity's signing key certificate. The certificate of the trust anchor SHOULD be
3647 omitted (since it can not necessarily be determined to be trusted.)

3648
3649 The guidance given in Section 12.2.2.2 regarding Public Key algorithm identification
3650 SHALL be followed.

3651

```
<ds:KeyInfo>
  <ds:X509Data>
    <!-- cert of the end-entity's signing public key -->
    <ds:X509Certificate>MIICh...</ds:X509Certificate>
    <!-- intermediate cert to the trust anchor -->
    <ds:X509Certificate>MIICo...</ds:X509Certificate>
  </ds:X509Data>
</ds:KeyInfo>
```

3652 **12.3 NEMO Profile for Basic Secure Messaging**

3653 This Profile defines a profile of Basic Secure Messaging defined in [NEMO] §3.

3654

3655 The full security version of the NEMO basic secure messaging protocol provides
3656 confidentiality, integrity, and freshness protection of NEMO service request, response,
3657 and confirmation messages. The balance of this section focuses on defining a profile of
3658 these messages to simplify implementations and to further assure interoperability.

3659 **12.3.1 Notation**

3660 The entities `&nemo;` `&nemoc;` and `nemosec;` are defined so as to provide shorthand
3661 identifiers for URIs defined in this specification. For example

3662 `&nemosec;/Element`

3663 corresponds to

3664 `http://nemo.intertrust.com/2005/10/security/Element`

3665 This entity is used as a shorthand notation in this specification; however, the use of
3666 entities in NEMO is specified in NEMO Message Bindings [NEMO] §2.

3667 **12.3.2 Request Message**

3668 **12.3.2.1 SOAP Header**

3669 **12.3.2.1.1 Action (Informative)**

3670 The `<wsa:Action>` element shall contain a same value specified in a `soapAction` attribute
3671 of the corresponding WSDL.

3672 **12.3.2.1.2 Message ID for the Message**

3673 The `<S11:Header>` element SHALL contain a `<wsa:MessageID>` element.

3674 **12.3.2.1.3 Correlation to Request Message**

3675 The `<S11:Header>` element SHALL NOT contain a `<wsa:RelatesTo>` element.

3676 **12.3.2.2 Security Header**

3677 In this profile, the security header SHALL also contain the requestor's long-term public
3678 message encryption key certificate, SAML assertions [SAML1.1] and a profile identifier
3679 in addition to elements which are described in [NEMO] §3.1.4.1.1.1.

3680

3681 The Marlin System Root SHALL NOT be included in PKIPath certificate chains. Trust

3682 Anchors SHALL NOT be included in PKIPath certificate chains.

3683 **12.3.2.2.1 Protocol Identifier**

3684 The `<nemosec:ProtocolDeclaration>` element SHALL include a `<nemosec:Step>`
3685 element with `Type` attribute containing the string value defined in [NEMO] §3.1.4.1.1.1.1.

3686 The `<nemosec:Step>` element SHALL NOT include an `Index` attribute.

3687 **12.3.2.2.2 Profile**

3688 The <wsse:Security> element SHALL contain a <nemosec:Profile> element to signal the
3689 profile defined by this document. Hence, the <nemosec:Profile> element SHALL include
3690 a URI attribute having the value
3691 urn:marlin:core:1.0:nemo:protocol:profile:1

3692 The <nemosec:Profile> element SHALL contain a nemosec:Usage attribute with the
3693 value defined in [NEMO] §3.1.3.5.6. The <nemosec:Profile> element SHALL be the
3694 immediate sibling element of the <nemosec:ProtocolDeclaration> element.

3695 **12.3.2.2.3 Requestor's Timestamp**

3696 The <wsu:Timestamp> element SHALL contain a nemosec:Usage attribute with the
3697 value defined in [NEMO] §3.1.4.1.1.1.2. The <wsu:Expire> element SHALL NOT be
3698 used in <wsu:Timestamp> element.

3699 **12.3.2.2.4 Requestor's Nonce**

3700 The <wsse:Nonce> element SHALL contain a nemosec:Usage attribute with the value
3701 defined in [NEMO] §3.1.4.1.1.1.3.

3702 **12.3.2.2.5 Responder's Identifier**

3703 The <nemosec:ToNode> element SHALL contain a nemosec:Usage attribute with the
3704 value defined in [NEMO] §3.1.4.1.1.1.5.

3705 **12.3.2.2.6 Requestor's Identifier**

3706 The <wsse:Security> element SHALL NOT contain a <nemosec:FromNode> element.

3707 **12.3.2.2.7 Self-encrypted Message Key**

3708 The <wsse:BinarySecurityToken> element SHALL contain a ValueType attribute as
3709 defined in [NEMO] §3.1.3.5.7. The <wsse:BinarySecurityToken> element SHALL contain
3710 a nemosec:Usage attribute with a value defined in [NEMO] §3.1.4.1.1.1.6. Element
3711 encryption SHALL include the <wsse:BinarySecurityToken> element and its contents.

3712 **12.3.2.2.8 Requestor's Public Signing Key Certificate Chain**

3713 The <wsse:Security> element SHALL contain a <wsse:BinarySecurityToken> with a
3714 ValueType attribute of
3715 http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-x509-token-profile-
3716 1.0#X509PKIPathv1

3717
3718 In other words, following value type SHALL NOT be used.
3719 http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-x509-token-profile-
3720 1.0#PKCS7

3721
3722 The <wsse:BinarySecurityToken> element SHALL contain a nemosec:Usage attribute
3723 with a value defined in [NEMO] §3.1.4.1.1.1.7.

3724 **12.3.2.2.9 Requestor's Public Encryption Key Certificate Chain**

3725 The <wsse:Security> element SHALL contain a <wsse:BinarySecurityToken> with a
3726 ValueType attribute of
3727 http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-x509-token-profile-
3728 1.0#X509PKIPathv1

3729

3730 In other words, following value type SHALL NOT be used.

3731 [http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-x509-token-profile-](http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-x509-token-profile-1.0#PKCS7)
3732 [1.0#PKCS7](http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-x509-token-profile-1.0#PKCS7)

3733

3734 The <wsse:BinarySecurityToken> element SHALL contain a nemosec:Usage attribute
3735 with a value defined in [NEMO] §3.1.4.1.1.1.8.

3736 **12.3.2.2.10 Requestor's Encrypted Message Encryption Key**

3737 Requestor's Message Encryption Key SHALL be used to encrypt <S11:Body> element
3738 and <ds:Signature> element. Element encryption SHALL include the <ds:Signature>
3739 element and its contents. Element encryption SHALL include all the contents of the
3740 <S11:Body> element. The Message Encryption Key SHOULD be unique for each
3741 message (Request, Response, and Confirmation) of the transaction. However, a
3742 message processor need not verify the uniqueness of the keys across the transaction.

3743 **12.3.2.2.11 Requestor's role attribute assertions**

3744 Requestor's role attribute assertion required by the service policy SHALL be placed as a
3745 direct child element of a <wsse:Security> element, and SHALL be referenced from a
3746 single <wsse:KeyIdentifier> element in a <wsse:SecurityTokenReference> element as
3747 specified in [WS-SECSAML] §3.3. Thus, when multiple SAML Assertions are sent in a
3748 request message, multiple <wsse:SecurityTokenReference> elements are used to refer
3749 to respective SAML Assertions.

3750

3751 The <wsse:SecurityTokenReference> element that references a SAML attribute
3752 assertion that asserts a NEMO node role SHALL contain a nemosec:Usage attribute
3753 with the value defined in [NEMO] §3.1.3.5.8.

3754 **12.3.2.2.12 Signature**

3755 In addition to elements described in [NEMO] §3.1.4.1.1.1.10, the signature SHALL cover
3756 the following elements

- 3757 • Profile
- 3758 • Message ID for this message
- 3759 • Requestor's public encryption key certificate chain
- 3760 • <S11:Body>

3761

3762 The <ds:Signature> element SHALL include a <ds:KeyInfo> element. The <ds:KeyInfo>
3763 element SHALL include a <wsse:SecurityTokenReference> element which refers to the
3764 requestor's signing key certificate. This reference MUST use <wsse:Reference> element.
3765 The <wsse:Reference> element SHALL contain URI attribute which refers to the
3766 <wsse:BinarySecurityToken> by a bare name.

3767 **12.3.2.3 Processing Rules**

3768 In addition to the processing rules defined in [NEMO] §3.1.4.1.1.2,

- 3769 • The responder SHALL verify the validity of the requestor's certificate.
- 3770 • The responder SHALL check that the NEMO node ID included in the requestor's
3771 role attribute assertion is identical to a requestor's node ID included in the
3772 requestor's signing certificate.

- 3773 • The responder SHALL verify the requestor has the proper role attribute (see
3774 Table 4-1).

3775 **12.3.3 Response Message**

3776 **12.3.3.1 SOAP Header**

3777 **12.3.3.1.1 Action (Informative)**

3778 The <wsa:Action> element shall contain a same value specified in a soapAction attribute
3779 of the corresponding WSDL.

3780 **12.3.3.1.2 Message ID for the Message**

3781 The <S11:Header> element SHALL contain a <wsa:MessageID> element.

3782 **12.3.3.1.3 Correlation to Request Message**

3783 The <S11:Header> element SHALL contain a <wsa:RelatesTo> element. The
3784 <RelatesTo> element SHALL include RelationshipType attribute having the value

3785

3786 &nemo;/addressing/originatesFrom

3787

3788 and SHALL contain a value which is identical to the value contained in the Message ID
3789 element of the request message.

3790 **12.3.3.2 Security Header**

3791 In this profile, the security header SHALL also contain a profile identifier in addition to
3792 elements which are described in [NEMO] §3.1.4.1.2.1.

3793

3794 The Marlin System Root SHALL NOT be included in PKIPath certificate chains. Trust
3795 Anchors SHALL NOT be included in PKIPath certificate chains.

3796 **12.3.3.2.1 Protocol Identifier**

3797 The <nemosec:ProtocolDeclaration> element SHALL include a Step element with Type
3798 attribute containing the string value defined in [NEMO] §3.1.4.1.2.1.1. The Step element
3799 SHALL NOT include an Index attribute. If a fault occurs related to the security protocol
3800 defined in [NEMO] §3, the value of the Type attribute SHALL be set to "fault".

3801 Otherwise, the value of the Type attribute SHALL be set to "response".

3802 **12.3.3.2.2 Profile**

3803 The <wsse:Security> element SHALL contain a <nemosec:Profile> element to signal
3804 the profile defined in this document. Hence the <nemosec:Profile> element SHALL
3805 include a URI attribute having the value

3806

3807 urn:marlin:core:1.0:nemo:protocol:profile:1

3808

3809 The <nemosec:Profile> element SHALL contain a nemosec:Usage attribute with the
3810 value defined in [NEMO] §3.1.3.5.6. The <nemosec:Profile> element SHALL be the
3811 immediate sibling element of the <nemosec:ProtocolDeclaration> element.

3812 **12.3.3.2.3 Responder's Timestamp**

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

Refer to Notices on page 2 for important legal information

3813 The <wsu:Timestamp> element SHALL contain a nemosec:Usage attribute with the
3814 value defined in [NEMO] §3.1.4.1.2.1.2. The <wsu:Expire> element SHALL NOT be
3815 used in <wsu:Timestamp> element.

3816 **12.3.3.2.4 Requestor's Nonce**

3817 The <wsse:Nonce> element SHALL contain a nemosec:Usage attribute with the value
3818 defined in [NEMO] §3.1.4.1.2.1.6.

3819 **12.3.3.2.5 Responder's Nonce**

3820 The <wsse:Nonce> element SHALL contain a nemosec:Usage attribute with the value
3821 defined in [NEMO] §3.1.4.1.2.1.7.

3822 **12.3.3.2.6 Responder's Identifier**

3823 The <wsse:Security> element SHALL NOT contain a <nemosec:FromNode> element.

3824 **12.3.3.2.7 Requestor's Identifier**

3825 The <nemosec:ToNode> element SHALL contain a nemosec:Usage attribute with the
3826 value defined in [NEMO] §3.1.4.1.2.1.4.

3827 **12.3.3.2.8 Self-encrypted Message Key**

3828 The <wsse:BinarySecurityToken> element SHALL contain a ValueType attribute as
3829 defined in [NEMO] §3.1.3.5.7. The <wsse:BinarySecurityToken> element SHALL
3830 contain a nemosec:Usage attribute with a value defined in [NEMO] §3.1.4.1.2.1.5.
3831 Element encryption SHALL include the <wsse:BinarySecurityToken> element and its
3832 contents.

3833 **12.3.3.2.9 Responder's Public Signing Key Certificate Chain**

3834 The <wsse:Security> element SHALL NOT contain a <wsse:BinarySecurityToken> for a
3835 responder's public signing key certificate.

3836 **12.3.3.2.10 Responder's Encrypted Message Encryption Key**

3837 Responder's Message Encryption Key SHALL be used to encrypt <S11:Body> element
3838 and <ds:Signature> element. Element encryption SHALL include the <ds:Signature>
3839 element and its contents. Element encryption SHALL include all the contents of the
3840 <S11:Body> element. The Message Encryption Key SHOULD be unique for each
3841 message (Request, Response, and Confirmation) of the transaction. However, a
3842 message processor need not verify the uniqueness of the keys across the transaction.
3843

3844 The <xenc:EncryptedKey> element SHALL include <ds:KeyInfo> element. The
3845 <ds:KeyInfo> element SHALL include <wsse:SecurityTokenReference> element which
3846 refers to the requestor's encryption key certificate by using <wsse:KeyIdentifier> element.
3847 The <wsse:KeyIdentifier> element SHALL use the Subject Key Identifier to reference the
3848 X.509 certificate as defined in [WS-SECX509] §3.2.1. The ValueType attribute SHALL
3849 signal this with the value defined in [WS-SECX509-ER] §5.

3850 **12.3.3.2.11 Signature**

3851 In addition to elements described in [NEMO] §3.1.4.1.2.1.10, the signature SHALL cover
3852 the following elements:

- 3853 • Profile

- 3854 • Message ID for this message
- 3855 • Correlation to request message
- 3856 • <S11:Body>

3857

3858 When <nemoc:FaultDetails> element is included in a message and integrity protection
3859 is applied to the message the <nemoc:FaultDetails> element SHALL be signed.

3860

3861 The <ds:Signature> element SHALL include a <ds:KeyInfo> element. The <ds:KeyInfo>
3862 element SHALL include a <wsse:SecurityTokenReference> element which refers to the
3863 responder's signing key certificate. This reference MUST use <wsse:KeyIdentifier>
3864 element. The <wsse:KeyIdentifier> element SHALL use the Subject Key Identifier to
3865 reference the X.509 certificate as defined in [WS-SECX509] §3.2.1. The ValueType
3866 attribute SHALL signal this with the value defined in [WS-SECX509-ER] §5.

3867 **12.3.3.3 Processing Rules**

3868 In addition to the processing rules defined in [NEMO] §3.1.4.1.2.2,

- 3869 • The requestor SHALL verify the validity of the responder's certificate.
- 3870 • The requestor SHALL verify that the NEMO node ID in the responder's role
3871 attribute assertion identifies the same subject as is indicated in the responder's
3872 certificate.
- 3873 • The requestor SHALL verify the responder has the proper role attribute (see
3874 Table 4-1).

3875 **12.3.3.4 Fault Response**

3876 In the event a fault is returned in the response, the fault message MUST follow the rules
3877 given in Sections 12.3.3.1.2, 12.3.3.1.3 and 12.3.3.2.11.

3878 **12.3.4 Confirmation Message**

3879 **12.3.4.1 SOAP Header**

3880 **12.3.4.1.1 Action (Informative)**

3881 The <wsa:Action> element shall contain a same value specified in a soapAction attribute
3882 of the corresponding WSDL.

3883 **12.3.4.1.2 Message ID for the Message**

3884 The <S11:Header> element SHALL contain a <wsa:MessageID> element.

3885 **12.3.4.1.3 Correlation to Request Message**

3886 The <S11:Header> element SHALL contain a <wsa:RelatesTo> element. The
3887 <wsa:RelatesTo> element SHALL include RelationshipType attribute having the value

3888

3889 &nemoc;/addressing/originatesFrom

3890

3891 and SHALL contain a value which is identical to the value contained in the Message ID
3892 of the request message.

- 3893 **12.3.4.2 Security Header**
- 3894 In addition to elements which are described in [NEMO] §3.1.4.1.3.1, the security header
3895 SHALL contain a profile identifier.
- 3896
- 3897 The Marlin System Root SHALL NOT be included in PKIPath certificate chains. Trust
3898 Anchors SHALL NOT be included in PKIPath certificate chains.
- 3899 **12.3.4.2.1 Protocol Identifier**
- 3900 The <nemosec:ProtocolDeclaration> element SHALL include a Step element with Type
3901 attribute containing the string value defined in [NEMO] §3.1.4.1.3.1.1.
3902 The Step element SHALL NOT include Index attribute.
- 3903 **12.3.4.2.2 Profile**
- 3904 The <wsse:Security> element SHALL contain a <nemosec:Profile> element to signal
3905 the profile defined in this document. Hence, the <nemosec:Profile> element SHALL
3906 include an URI attribute having the value
3907
3908 urn:marlin:core:1.0:nemo:protocol:profile:1
3909
- 3910 The <nemosec:Profile> element SHALL contain a nemosec:Usage attribute with the
3911 value defined in [NEMO] §3.1.3.5.6.
3912 The <nemosec:Profile> element SHALL be the immediate sibling element of the
3913 <nemosec:ProtocolDeclaration> element.
- 3914 **12.3.4.2.3 Requestor's Timestamp**
- 3915 The <wsu:Timestamp> element SHALL contain a nemosec:Usage attribute with the
3916 value defined in [NEMO] §3.1.4.1.3.1.2. The <wsu:Expire> element SHALL NOT be
3917 used in <wsu:Timestamp> element.
- 3918 **12.3.4.2.4 Responder's Nonce**
- 3919 The <wsse:Nonce> element SHALL contain a nemosec:Usage attribute with the value
3920 defined in [NEMO] §3.1.4.1.3.1.3.
- 3921 **12.3.4.2.5 Requestor's Identifier**
- 3922 The <wsse:Security> element SHALL NOT contain a <nemosec:FromNode> element.
- 3923 **12.3.4.2.6 Responder's Identifier**
- 3924 The <nemosec:ToNode> element SHALL contain a nemosec:Usage attribute with the
3925 value defined in [NEMO] §3.1.4.1.3.1.5.
- 3926 **12.3.4.2.7 Self-encrypted Message Key**
- 3927 The <wsse:BinarySecurityToken> element SHALL contain a ValueType attribute as
3928 defined in [NEMO] §3.1.3.5.7. The <wsse:BinarySecurityToken> element SHALL
3929 contain a nemosec:Usage attribute with a value defined in [NEMO] §3.1.4.1.3.1.6.
3930 Element encryption SHALL include the <wsse:BinarySecurityToken> element and its
3931 contents.
- 3932 **12.3.4.2.8 Requestor's Public Signing Key Certificate Chain**

3933 The <wsse:Security> element SHALL contain a <wsse:BinarySecurityToken> with a
3934 Value type attribute of

3935
3936 `http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-x509-`
3937 `token-profile-1.0#X509PKIPathv1`

3938
3939 In other words, the following value type SHALL NOT be used.

3940
3941 `http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-x509-`
3942 `token-profile-1.0#PKCS7`

3943
3944 The <wsse:BinarySecurityToken> element SHALL contain a nemosec:Usage attribute
3945 with a value defined in [NEMO] §3.1.4.1.3.1.8.

3946 **12.3.4.2.9 Requestor's Encrypted Message Encryption Key**

3947 Requestor's Message Encryption Key SHALL be used to encrypt the child elements of
3948 the <S11:Body> and <ds:Signature> element. Element encryption SHALL include the
3949 <ds:Signature> element and its contents. Element encryption SHALL include all the
3950 contents of the <S11:Body> element. The Message Encryption Key SHOULD be unique
3951 for each message (Request, Response, and Confirmation) of the transaction. However,
3952 a message processor need not verify the uniqueness of the keys across the transaction.

3953 **12.3.4.2.10 Signature**

3954 In addition to elements described in [NEMO] §3.1.4.1.3.1.9, the signature SHALL cover
3955 the following elements:

- 3956 • Profile
- 3957 • Message ID for this message
- 3958 • Correlation to request message
- 3959 • <S11:Body>

3960
3961 The <ds:Signature> element SHALL include a <ds:KeyInfo> element. The <ds:KeyInfo>
3962 element SHALL include a <wsse:SecurityTokenReference> element which refers to the
3963 requestor's signing key certificate. This reference MUST use <wsse:Reference> element.
3964 The <wsse:Reference> element SHALL contain URI attribute which refers to the
3965 <wsse:BinarySecurityToken> by a bare name.

3966 Note that the signing key is to be repeated in the confirmation, rather than to rely on
3967 server state.

3968

3969 **12.3.4.3 Processing Rules**

- 3970 • The responder SHALL check the responder's nonce to see if it is the same as the
3971 nonce that was passed to the requestor in the corresponding response message.

3972

3973 The responder SHALL check that the value included in <wsa:RelatesTo> element of the
3974 confirmation message is the same as the value included in <wsa:MessageID> element
3975 of the request message.

3976 **12.3.5 License Transfer Protocol Correlation Processing Rules**

3977 The License Transfer Protocol (LTP) involves a series of messages initiated by the Sink
3978 and terminated by the Source. Between the initial setup message and the terminating
3979 teardown message there are potentially multiple rounds of Sink Request and Source
3980 Response messages. The following processing rules augment this profile to ensure
3981 proper message correlation.

3982
3983 The initial Sink Setup Request message and the Source RunAgent Response message
3984 MUST adhere to the correlation techniques specified in Sections 12.3.2 and 12.3.3,
3985 respectively.

3986
3987 Subsequent messages are a series of Sink Request and Source Response messages.
3988 An AgentResult is sent from the Sink to the Source in Request messages. A RunAgent
3989 or Teardown is sent from the Source to the Sink in Response messages.

3990
3991 These subsequent Sink Request messages MUST be constructed like the Confirmation
3992 Message defined in Section 12.3.4 but with the following changes to facilitate the proper
3993 correlation of the multi-round exchanges.

3994 **12.3.5.1 Message ID for the Message**

3995 The <S11:Header> element SHALL contain a <wsa:MessageID> element.

3996 **12.3.5.2 Correlation to Source Response Message**

3997 The <S11:Header> element SHALL contain a <wsa:RelatesTo> element. The
3998 <wsa:RelatesTo> element SHALL include RelationshipType attribute of

3999
4000 <http://www.w3.org/2005/08/addressing/reply>

4001
4002 as defined in [WS-addr] and SHALL contain a value which is identical to the value
4003 contained in the MessageID of the Source Response message being replied to.

4004 **12.3.5.3 Requestor's Nonce**

4005 The <wsse:Nonce> element SHALL contain a nemosec:Usage attribute with the value
4006 defined in [NEMO] §3.1.4.1.3.1.3:

4007
4008 `#confirmation-returnedNonce`

4009
4010 and SHALL contain a value which is identical to the responder's nonce contained in the
4011 Response message being replied to.

4012 **12.4 SAML Assertion Profile**

4013 Marlin utilizes the Security Assertion Markup Language (SAML) for conveying a variety
4014 of information. SAML is extremely flexible insofar as what type of information can be
4015 conveyed within an assertion and the number of statements embodied by an assertion.
4016 The following subsections prescribe simple limitations on how SAML assertions are
4017 constructed so as to simplify the processing of the assertions and to enable
4018 interoperability and accuracy of the information distilled from an assertion.

4019 **12.4.1 Assertion Conditions**

4020 SAML 1.1 allows for an optional <saml:Conditions> element which when processed may
4021 influence the validity of the assertion. Presently we do not require any conditions in this
4022 profile. However, it is expected that temporal attributes (saml:NotOnOrAfter and
4023 saml:NotBefore) are used. If these attributes are present then the processing rules
4024 specified in [SAML1.1] §2.3.2.1.1 SHALL apply.

4025
4026 In general, Marlin uses assertions to reflect some fact that persists for a period longer
4027 than the initial issuance and consumption of the assertion. Hence, the
4028 <saml:DoNotCache> element SHOULD NOT be used for this type of assertion.

4029 **12.4.2 Assertion Subject**

4030 SAML 1.1 allows for an assertion to contain multiple statements. This leads to the
4031 possibility that a given assertion may have multiple unique subjects. There are no
4032 specific usage scenarios in Marlin which requires this flexibility. Therefore, it is
4033 RECOMMENDED that all statements in an assertion refer to the same subject.

4034 **12.4.3 Attributes**

4035 In Marlin, SAML assertions are primarily used to convey trusted attributes about a
4036 system entity (typically a Nemo node.) A DRM Client is NOT REQUIRED to check
4037 whether required attributes appear in the assertion but it MAY return an error if a
4038 required attribute is not in the assertion.

4039
4040 Attributes are qualified by their origin namespace so that two attributes with the same
4041 name may be unambiguously described. However, SAML does not preclude two or more
4042 fully qualified attributes from appearing in either the same statement or in multiple
4043 statements within an assertion. It is RECOMMENDED that no two fully qualified
4044 attributes appear multiple times within an assertion.

4045
4046 The type of attribute values that can be issued in SAML assertions is restricted to the
4047 following XML data types:

- 4048 - xs:string
- 4049 - xs:int
- 4050 - xs:duration
- 4051 - xs:dateTime
- 4052 - xs:base64Binary
- 4053 - xs:nonNegativeInteger

4054
4055 No complex type is allowed. If the type is not indicated, it SHALL be processed as an
4056 xs:string value. The XML data type xs:nonNegativeInteger SHOULD be used whenever
4057 the attribute is used to convey version information.

4058 **12.4.4 Subject Confirmation**

4059 According to [WS-SECSAML] §3.1, systems are required to implement the processing
4060 necessary to support subject confirmation methods (i.e. holder-of-key and sender-
4061 vouches).

4062

4063 In Marlin, subject confirmation processing is realized as described in Section 0.
4064 Therefore, the <saml:SubjectConfirmation> element SHALL NOT be specified in a
4065 SAML assertion.

4066 **12.4.5 Signature**

4067 All assertions MUST be signed so as to enable verification of their authenticity. The
4068 guidance give in Section 12.2 SHALL be followed in addition to the guidance given in
4069 [SAML1.1] §5.

4070 **12.5 Name Management Profile**

4071 A general description of the rules for specifying identifiers was given in Section 1.3. In
4072 this section we give guidance to specific naming conventions used to identify the various
4073 system objects.

4074 **12.5.1 SeaShell Object Ownership**

4075 The SeaShell database specification (see [8pus] §7.5) defines different ways of
4076 determining control program identities. In Marlin, the identities of the Control program
4077 SHALL be acquired from the Subject distinguished name found in a signer's X.509
4078 certificate. Octopus allows for multiple signatures so there may be more than one
4079 identity attributed to a Control. Controls may be signed directly or indirectly. When a
4080 Control is indirectly signed (see Sections 3.3.4, 9.3.2.1 and 9.3.2.2) then the identities of
4081 a Control SHALL also include each of the indirect signers.

4082 **12.5.1.1 Container Delegate**

4083 A Delegate is a Plankton byte code routine, located in a Control object that performs a
4084 task on behalf of another routine, located in a different Control object.

4085
4086 A Delegates primary use is for making it possible for a control to access SeaShell
4087 objects that belong to a different principal than the principal that signed the control. This
4088 is necessary, because SeaShell access control is based on the principal identifiers of the
4089 signers of the Control that contains the code making the SeaShell call.

4090
4091 The path of the root container of the SeaShell database is
4092 /Octopus/SeaShell/Databases/Marlin

4093
4094 This container is owned by the principal
4095 urn:marlin:drmservices:seashell
4096

4097 To bootstrap the process of assigning ownership of descendant containers a signing
4098 certificate must be created and issued under the DRM Services (the issuer
4099 DN=urn:marlin:drmservices) trust hierarchy. This certificate would be used to sign
4100 Delegate Controls which create sub-containers and reassign ownership.

4101
4102 This certificate would have the following attributes:
4103

Delegate Signing Key	Basic Constraint	Key Usage	Certificate Policy Identifiers
DRM Services Container Delegate Signing			
Delegate Control	CA=FALSE	digitalSignature	id-cp-octopus-marlin-signing-control

4104

4105 12.5.2 Octopus Naming

4106 Octopus object names referenced via System.Host.Get/SetObject() fall into one of three
 4107 categories. The first category, Octopus standard names, are object names that allow
 4108 read only access to objects where Octopus specifications define a standard naming path
 4109 such as /Octopus/Personality/Attributes. The second category is SeaShell database
 4110 names. Third is Marlin standard names that are object names that allow read only
 4111 access to objects defined by Marlin standards. Names in the first two categories use the
 4112 Octopus defined path followed by a Marlin defined URN. The third category uses a
 4113 Marlin specific extension.
 4114

Category	Prefix	Example
Octopus	<octopus-prefix>/urn:marlin:<rest of name>	/Octopus/Personality/Attributes/urn:marlin:foo
SeaShell DB	/Octopus/SeaShell/Databases/Marlin	/Octopus/SeaShell/Databases/Marlin/SomeCompany/foo
Marlin	/Marlin	/Marlin/LicenseRevocations/SomeCompany/IdList/foo

4115

4116 All path components that follow the Marlin component are implicitly from the Marlin
 4117 standards name space unless a subsequent name component is a URN in which case
 4118 all following name components are implicitly from the namespace of that URN.
 4119

4120 URN identifiers that are referenced via a System.Host.GetObject call SHALL NOT use
 4121 “/” characters as “/” is a reserved character within the namespace specific string of a
 4122 URN and as the path separator for object paths. If a reserved character is to be
 4123 represented then the %-encoding defined in [URN] §2.2 MUST be used to encode the
 4124 URN portion of the object path.
 4125

4125

4126 Organizations SHOULD use their own domain name for URLs.

4127 12.5.3 Extensions

4128 Entity specific extensions can be defined. These extensions can only be referenced by
 4129 SomeOrganization’s proprietary actions because only SomeOrganization clients SHALL
 4130 make this path available. Non SomeOrganization clients SHALL NOT execute a
 4131 SomeOrganization proprietary action.

Object Path
/SomeOrganization

4132 **12.5.4 SeaShell Database ([8pus] §7)**

4133 The pattern for Marlin global database is as follows.

Object Path
/Octopus/SeaShell/Databases/Marlin

4134 The pattern for Marlin service specific database is as follows.
4135

Object Path
/Octopus/SeaShell/Databases/Marlin/<service container name>

4136 **12.5.4.1 Marlin Core**

4137 Selected information from Marlin assertions SHALL be made available for access via
4138 System.Host.GetObject. Since a client may have multiple distinct instances of
4139 assertions (e.g. role attribute assertions), the naming path includes an index (index
4140 origin 0).

Pattern	Example
/Marlin/Assertions/@<index>/<item-path>	/Marlin/Assertions/@0/Attributes/foo

4141 Marlin core defines a naming pattern for accessing the IssueInstant element of an
4142 assertion and for accessing the attribute values in the assertion.
4143
4144

Pattern
/Marlin/Assertions/@<index>/IssueInstant
/Marlin/Assertions/@<index>/Attributes/<attribute-name>

4145 **12.5.4.2 Role attribute assertions**

4146 According to the NEMO Trust Management Bindings specification ([NEMO] §4), each
4147 role SHALL be represented as an attributes within a SAML assertion and multiple roles
4148 MAY be expressed within the same SAML assertion. A client may play many roles in
4149 Marlin.

4150
4151 We rely on the namespace equivalence defined in Table 1-3 to simplify object path
4152 composition. In general, the path composition for <attribute-name> is accomplished by
4153 taking the value of the saml:AttributeName attribute, appending a “.” and then
4154 appending value of the saml:AttributeName attribute.
4155

4156

Attribute Namespace	Name	Object Path	Value Type
urn:marlin:nemo:2004:attribute	role	/Marlin/Assertions/@<index>/Attributes/urn:marlin:nemo:2004:attribute:role	String

4157 **Table 12-1 Role Attribute Namespace/Name**

4158 By using the equivalence we avoid the need to URL encode the attribute namespace
4159 when using it to construct an object path.

4160

4161 The identifiers for the various role attribute values defined by this specification are
4162 enumerated in Table 4-2.

4163 12.5.4.3 Marlin Security Specification Attribute

4164 The Marlin security specification version attribute represents the security versions of the
4165 various Marlin specifications the client supports. Control programs can encode a check
4166 for the security specification and version. In the event that the security of a version of the
4167 specification is deemed compromised, new licenses may encode the requirement for
4168 the new version of the specification. Also, during peer to peer (or client to server)
4169 interactions, a Nemo node can use the security specification versions in the role attribute
4170 assertion of the entity it is interacting with to determine which security versions of the
4171 specifications (and thus what features) the entity supports

4172

4173 If a client is updated and the supported specifications change, a new role attribute
4174 assertion for the client can be acquired that accurately reflects the new capabilities.
4175 Compliance rules require that the implementation of the client not allow the role attribute
4176 assertion to be referenced (e.g. via System.Host.GetObject) or sent in part of a Nemo
4177 protocol if the specifications and versions in the assertion do not accurately reflect the
4178 capabilities of the client.

4179

Attribute Namespace	Name	Object Path	Value Type
urn:marlin:core	version-major	/Marlin/Assertions/@<index>/Attributes/urn:marlin:core:version-major	nonNegativeInteger
urn:marlin:core	version-minor	/Marlin/Assertions/@<index>/Attributes/urn:marlin:core:version-minor	nonNegativeInteger

4180 12.5.4.4 Capabilities

4181 There are many roles in Marlin. Each role is represented by a distinct role attribute. An
4182 entity implementing a given role may also implement optional capabilities. This
4183 specification defines an attribute namespace and standard values to convey the
4184 capabilities of an entity implementing a particular role.

4185

4186 If a component is updated and the set of capabilities changes, a new role attribute
4187 assertion for the related roles filled by the component can be acquired that accurately
4188 reflects the new capabilities.

4189

4190 The following table enumerates the capability attributes which may be attributed to for a
4191 entity assigned the *urn:marlin:core:role:drm-client* role.

4192

Attribute Namespace	Name	Object Path
urn:marlin:core:client:capabilities	trusted-time	/Marlin/Assertions/@<index>/Attributes/urn:marlin:core:client:capabilities:trusted-time

4193

4194 The presence of the trusted-time attribute indicates that the client implements the
4195 System.Host.GetTrustedTime function in compliance with the Marlin compliance rules
4196 regarding trusted time.

4197 Control programs may query the capabilities of the role attribute assertion to determine if
4198 specific actions are supported.

4199 **12.5.4.5 Role and Capability Example (Informative)**

4200 The previous sections described the various attributes which are conveyed within an
4201 assertion for a given role. The following example depicts a fragment of an SAML 1.1
4202 assertion carrying this information.

4203

```
4204 <saml:AttributeStatement
4205   xmlns="urn:oasis:names:tc:SAML:1.0:assertion">
4206   <saml:Subject>
4207     <saml:NameIdentifier
4208       Format=
4209         "http://nemo.intertrust.com/2004/saml/name-format/uri">
4210       urn:marlin:organization:phony:fuse:nemo:personality:00000001
4211     </saml:NameIdentifier>
4212   </saml:Subject>
4213   <saml:Attribute
4214     AttributeNamespace="urn:marlin:nemo:2004:attribute"
4215     AttributeName="role">
4216     <saml:AttributeValue>
4217       urn:marlin:core:role:drm-client</saml:AttributeValue>
4218   </saml:Attribute>
4219   <saml:Attribute AttributeNamespace="urn:marlin:core"
4220     AttributeName="version-major">
4221     <saml:AttributeValue
4222       xsi:type="xsd:nonNegativeInteger">1</saml:AttributeValue>
4223   </saml:Attribute>
4224   <saml:Attribute AttributeNamespace="urn:marlin:core"
4225     AttributeName="version-minor">
4226     <saml:AttributeValue
4227       xsi:type="xsd:nonNegativeInteger">1</saml:AttributeValue>
4228   </saml:Attribute>
4229   <saml:Attribute
4230     AttributeNamespace="urn:marlin:core:client:capabilities"
4231     AttributeName="trusted-time">
4232     <saml:AttributeValue/>
4233   </saml:Attribute>
4234 </saml:AttributeStatement>
4235
```

4236 **12.6 Type Mapping of Host Objects**

4237 **12.6.1 Mapping XML Types to Host Objects**

4238
 4239 Marlin defines mechanisms by which to make data visible to Plankton programs as Host
 4240 Objects. Whenever this data is transported as XML encoded objects (e.g., SAML
 4241 Assertion) the following table defines the type mapping. If not listed below all other
 4242 types SHALL be treated as a String.
 4243

XML Data Type	Host Object Data Type
<xs:string/>	String
<xs:int/>	Integer
<xs:duration/>	Integer {converted to number of minutes}
<xs:dateTime/>	Integer {converted to number of minutes elapsed since Jan 1, 1970 00:00:00}
<xs:base64Binary/>	Byte Array
<xs:nonNegativeInteger/>	Integer

4244

4245 **Table 12-2 XML to Host Object Data Types**

4246 **12.6.2 Mapping Octopus Object Attributes to Host Objects**

4247 Marlin defines mechanisms by which to transport Octopus Object Attributes and make
 4248 them visible to Plankton programs as Host Objects. The following table defines the type
 4249 mapping, XML mixed content encoding for <oct:Attribute/> elements and the Host Object
 4250 representation.
 4251

Octopus Object Attribute Type	<oct:Attribute/> XML 'type' attribute	<oct:Attribute/> Mixed Content	Host Object Data Type
[Named Attributes]	n/a	n/a	Host Object of the same name

Octopus Object Attribute Type	<oct:Attribute/> XML 'type' attribute	<oct:Attribute/> Mixed Content	Host Object Data Type
[Unnamed Attributes]	n/a	n/a	Host Object with no name
IntegerAttribute	int	string	Integer
StringAttribute	string	string	String
ByteArrayAttribute	bytes	base64Binary	Byte Array
ListAttribute	list	<oct:AttributeList/>	Container
ArrayAttribute	array	<oct:AttributeArray/>	Container

4252 **Table 12-3 Octopus Object Attributes to Host Object Data Types**

4253 **12.6.3 Mapping Agent Parameters to Host Objects**

4254 Agent parameters are transported as XML encoded objects and made visible to
4255 Plankton programs as Host Objects. Agent parameters are transported in an
4256 <mc:AgentCarrier/> element. The parameters are a list of one or more
4257 <pk:ParameterBlock/> elements. Mapping a <pk:ParameterBlock/> to a Host Object is
4258 done using the following rules:

- 4259
- 4260 • The name attribute of the <pk:ParameterBlock/> maps to a Host Object name.
 - 4261 • The value of each parameter is expressed as a <pk:ValueBlock/> element.

4262

4263 The following table defines the <pk:ValueBlock/> type mapping, XML mixed content
4264 encoding for <pk:ValueBlock/> elements and Host Object representation.

4265

<pk:ValueBlock/> Type	<pk:ValueBlock/> Mixed Content	Host Object Data Type
Integer	string	Integer
String	string	String
Date	string	Integer {converted to number of minutes elapsed since Jan 1, 1970 00:00:00}
ByteArray	base64Binary	Byte Array
Parameter	<pk:ParameterBlock/>	see ValueList
ValueList	<pk:ValueListBlock/>	Container

4266 **Table 12-4 Agent Parameters to Host Object Data Types**

4267 The <pk:ValueBlock/> types ExtendedParameter, Real and Resource MUST NOT be
4268 used. For each <pk:ValueBlock/> value in the list there is a corresponding Host Object in
4269 the container. If the value is a <pk:ParameterBlock/>, then it maps to a named Host
4270 Object according to the mapping rules for <pk:ParameterBlock/> elements. Other
4271 <pk:ValueBlock/> types map to an unnamed Host Object according to the mapping rules
4272 for <pk:ValueBlock/> elements as defined in Table 12-3.

4273

4274 The following example depicts XML encoded Agent Parameters.

4275

```

4276 <ValueListBlock>
4277   <ValueBlock type="Parameter">
4278     <ParameterBlock name="ContainerWithNames">
4279       <ValueBlock type="ValueList">
4280         <ValueListBlock>
4281           <ValueBlock type="Parameter">
4282             <ParameterBlock name="Color">
4283               <ValueBlock
4284                 type="String">Red</ValueBlock>
4285             </ParameterBlock>
4286           </ValueBlock>
4287           <ValueBlock type="Parameter">
4288             <ParameterBlock name="Size">
4289               <ValueBlock
4290                 type="Integer">37</ValueBlock>
4291             </ParameterBlock>
4292           </ValueBlock>
4293         </ValueListBlock>

```

```

4294     </ValueBlock>
4295   </ParameterBlock>
4296 </ValueBlock>
4297 <ValueBlock type="Parameter">
4298   <ParameterBlock name="ContainerWithoutNames">
4299     <ValueBlock type="ValueList">
4300       <ValueListBlock>
4301         <ValueBlock type="String">Blue</ValueBlock>
4302         <ValueBlock type="Integer">512</ValueBlock>
4303       </ValueListBlock>
4304     </ValueBlock>
4305   </ParameterBlock>
4306 </ValueBlock>
4307 <ValueBlock type="Parameter">
4308   <ParameterBlock name="SomeInteger">
4309     <ValueBlock type="Integer">156</ValueBlock>
4310   </ParameterBlock>
4311 </ValueBlock>
4312 <ValueBlock type="Parameter">
4313   <ParameterBlock name="SomeString">
4314     <ValueBlock type="String">Hello</ValueBlock>
4315   </ParameterBlock>
4316 </ValueBlock>
4317 <ValueBlock type="Parameter">
4318   <ParameterBlock name="SomeBytes">
4319     <ValueBlock type="ByteArray">SGVsbG8K</ValueBlock>
4320   </ParameterBlock>
4321 </ValueBlock>
4322 </ValueListBlock>
4323

```

4324 The corresponding Host Object tree follows:

```

4325
4326 [ContainerWithNames]
4327   Color="Red"
4328   Size=37
4329
4330 [ContainerWithoutNames?]
4331   Blue
4332   512
4333
4334 SomeInteger=156
4335 SomeString="Hello"
4336 SomeBytes={0x48, 0x65, 0x6c, 0x6c, 0x6f, 0x0a}
4337
4338

```

4339 **12.7 XML Profile**

4340 **12.7.1 XML Attribute Composition Constraints**

4341 Validating XML parsers are not mandated nor recommended by this specification. Thus
4342 it is assumed that the XML parser of an implementation does not know the declared type
4343 of an XML attribute when performing Attribute-Value Normalization ([XML-1-1] §3.3.3).
4344 To ensure interoperability, constraints on the composition of XML attributes are imposed

Copyright (c) Marlin Developer Community, 2003-2013. All Rights Reserved

4345 as follows. XML attributes SHALL NOT contain leading or trailing white space (#x20,
4346 #xD, #xA, #x9) characters or sequences of more than one white space character.

4347 **12.7.2 Using QNames**

4348 Validating XML parsers are not mandated nor recommended by this specification. To
4349 ensure unambiguous treatment of attribute values and element content the following
4350 constraints on the use of QNames is adopted.

4351
4352 QNames SHALL only be used with XML Element and Attribute Names in conformance
4353 with [XMLNs, QNAMEIDS]. Particularly, when an XML element instance explicitly asserts
4354 its type with the xsi:type attribute, the value of the xsi:type attribute SHALL be processed
4355 as a string identifier.

4356 The following table defines string identifiers which can be used in the xsi:type attribute
4357 value to indicate the XML data types ([Schema]).
4358

String Identifier	XML Data Type
xsd:string	xs:string
xsd:int	xs:int
xsd:duration	xs:duration
xsd:dateTime	xs:dateTime
xsd:base64Binary	xs:base64Binary
xsd:nonNegativeInteger	xs:nonNegativeInteger

4359
4360

4361 **12.8 Security Metadata Propagation (Informative)**

4362 The Marlin core specification defines a variety of security metadata types. Some of this
4363 metadata is provisioned at manufacturing time or conveyed to relying parties via a
4364 service interface such as a Security Data Provider. The security metadata provisioned at
4365 manufacture may be out-of-date before the device is sold to the consumer.

4366
4367 Keeping a device current can be a challenge in some deployment scenarios. Marlin core
4368 devices do not presume a specific network transport technology. For example, a Marlin
4369 core device may access a transport via a direct tethered connection to another device.
4370 Another example is a set of devices in a home environment using IP protocols but
4371 absent of a routable Internet connection. Even though Marlin core devices may operate
4372 in this limited setting they still require current security metadata to enable governance.
4373 The intent of the informative text is to describe alternative implementation techniques by
4374 which security metadata can be acquired and disseminated.

4375
4376 In the following sections we describe the traditional mechanism by which security
4377 metadata can be refreshed. Within that section we also discuss how a Security Data

4378 Provider Service can collect (and by its service interface distribute) security metadata by
4379 Marlin specified mechanisms. Finally we describe alternative sources of security
4380 metadata and how a Security Data Provider Service might leverage these alternate
4381 sources to update the security metadata it distributes.

4382 **12.8.1 Common Security Metadata Acquisition Mechanisms**

4383 The primary mechanism by which Marlin core specification enables distribution of
4384 security metadata is through the Security Data Provider service. This service may have
4385 online access so that it can acquire new security metadata where as clients of the
4386 service may not. The obvious example is a tethered device. To support its clients the
4387 Security Data Provider service could periodically retrieve updated security metadata.
4388

4389 To support this deployment environment a Security Data Provider service can resolve a
4390 CRL Distribution Point to retrieve an updated CRL and supply it to the tethered device
4391 the next time it is connected. The same is true for the Broadcast Key Block since it
4392 defines a set of distribution URIs which may be resolved to retrieve a new Broadcast
4393 Key Block. Since both the CRL and the BKB are integrity protected by the issuer and
4394 contains version information the Security Data Provider can keep current.

4395 **12.8.2 Alternate Security Metadata Acquisition Mechanisms**

4396 There are some less obvious mechanisms by which a Security Data Provider service
4397 might acquire updated security metadata. This section describes some of the possible
4398 out-of-band mechanism which might be applied by an implementation.
4399

4400 Content is made available to a DRM Client in many ways and for all intents and
4401 purposes the DRM client is decoupled from the delivery system. Therefore a DRM Client
4402 might aggregate content from different delivery systems. That is, the content may source
4403 from both online and offline delivery systems. More current security metadata may be
4404 attached to content which sources from an online delivery system.
4405

4406 With that in mind it is worth noting that the Broadcast Key Block (BKB) is essentially
4407 attached to a content license when the license is created. DRM Clients must evaluate
4408 this license when they attempt to render content. A DRM Client could assist a Security
4409 Data Provider service by detaching the most current BKB it encounters and then make
4410 the BKB available to the Security Data Provider service. A DRM Client already has a
4411 well defined core service which it must expose which could be used to get the BKB to
4412 the Security Data Provider, the DRM Client Information service. The payload of the DRM
4413 Client Information service has a specific interface to retrieve security metadata from a
4414 DRM Client.
4415

4416 On a similar note, a DRM Client may be provisioned at manufacture time with the most
4417 up to date version of the BKB. Thus by using the same alternative propagation scheme
4418 described above a Security Data Provider can obtain a fresher BKB.
4419

4420 There is also the possibility for the Security Data Provider service to acquire security
4421 metadata out-of-band. For example, in a broadcast distribution setting it may be possible
4422 to embed security metadata in a transport stream. The device receiving the broadcast
4423 could extract the security metadata and make it available to a co-resident
4424 implementation of a Security Data Provider service.

4425
4426 Another out-of-band mechanism that could be utilized in a broadcast environment could
4427 be to acquire current time of day from time of day services in the cable operator's data
4428 network. Depending on the operational security of the cable operator's data network this
4429 source of time might be considered trusted.
4430
4431

4432

4433 Appendix A: XML Schemas File Names

- 4434 ▪ A.1: proximity-check.xsd
- 4435 ▪ A.2: drm-client-information.xsd
- 4436 ▪ A.3: domain-manager-information.xsd
- 4437 ▪ A.4: provide-drm-object.xsd
- 4438 ▪ A.5: provide-security-data.xsd
- 4439 ▪ A.6: license-transfer.xsd
- 4440 ▪ A.7: marlin-nemo-core-exceptions.xsd

4441

4442 Appendix B: WSDLs File Names

- 4443 ▪ B.1: proximity-check.wsdl
- 4444 ▪ B.2: drm-client-information.wsdl
- 4445 ▪ B.3: domain-manager-information.wsdl
- 4446 ▪ B.4: provide-drm-object.wsdl
- 4447 ▪ B.5: provide-security-data.wsdl
- 4448 ▪ B.6: license-transfer.wsdl

4449